

# FUSERBLOC

Fuse combination switches

for industrial fuses up to 1250 A

## References

### BS 88 - External front and side operation - 20 to 160 A

Rating (A) Fuse size Frame size	Number of poles	Reference Switch I - 0 - TEST	Reference Changeover I - 0 - II	External front handle I - 0	TEST External front handle I - 0 - TEST	External right side handle I - 0	Changeover external front handle I - 0 - II	Shaft extensions for handle	Terminal shrouds <sup>(3)</sup>	U type A/C <sup>(2)</sup>	Integrated solid neutral link
CD 20 A A1 0	3 P	3641 <b>3000</b>	3680 <b>3000</b>					320 mm 1401 <b>0532</b>			
	3 P + switched neutral	3641 <b>4000</b>	3680 <b>4000</b>								
	3 P+solid neutral	3641 <b>5000</b>									
CD 32 A A1 0	3 P	3641 <b>3001</b>	3680 <b>3001</b>					IP2x as standard			
	3 P + switched neutral	3641 <b>4001</b>	3680 <b>4001</b>	S1 type	S1 type	S1 type	S1 type				
	3 P + solid neutral	3641 <b>5001</b>		Black IP65 1413 <b>2111</b> <sup>(1)</sup>	Black IP65 1413 <b>2115</b> <sup>(1)</sup>	Black IP65 1417 <b>2111</b> <sup>(1)</sup>	Black IP65 1413 <b>2113</b> <sup>(1)</sup>				
32 A A1 11	2 P	3841 <b>2003</b>									
	3 P	3841 <b>3003</b>	3880 <b>3003</b>	Red/Yellow IP65 1414 <b>2111</b>	Red/Yellow IP65 1414 <b>2115</b>	Red/Yellow IP65 1418 <b>2111</b>	Red/Yellow IP65 1414 <b>2113</b>				
	4 P	3841 <b>6003</b>	3880 <b>6003</b>								
63 A A2-A3 12	2 P	3841 <b>2006</b>								1 contact NO 3999 <b>0701</b>	3829 <b>9310</b>
	3 P	3841 <b>3006</b>	3880 <b>3006</b>								
	4 P	3841 <b>6006</b>	3880 <b>6006</b>								
100 A A4 <sup>(4)</sup> 13	2 P	3841 <b>2010</b>						320 mm 1400 <b>1032</b>		1 contact NC 3999 <b>0702</b>	
	3 P	3841 <b>3010</b>	3880 <b>3010</b>								
	4 P	3841 <b>6010</b>	3880 <b>6010</b>								
CD 160 A A3-A4 <sup>(4)</sup> 13 A	2 P	3841 <b>2014</b>							2 P 3998 <b>2016</b> 3 P 3998 <b>3016</b> 4 P 3998 <b>4016</b>		
	3 P	3841 <b>3014</b>	3880 <b>3014</b>	S2 type	S2 type	S2 type	S2 type				
	4 P	3841 <b>6014</b>	3880 <b>6014</b>	Black IP65 1423 <b>2111</b> <sup>(1)</sup>	Black IP65 1423 <b>2115</b> <sup>(1)</sup>	Black IP65 1427 <b>2111</b> <sup>(1)</sup>	Black IP65 1421 <b>2113</b> <sup>(1)</sup>				
160 A A4 14	2 P	3841 <b>2015</b>									3829 <b>9320</b>
	3 P	3841 <b>3015</b>	3880 <b>3015</b>	Red/Yellow IP65 1424 <b>2111</b>	Red/Yellow IP65 1424 <b>2115</b>	Red/Yellow IP65 1428 <b>2111</b>	Red/Yellow IP65 1424 <b>2113</b>				
	4 P	3841 <b>6015</b>	3880 <b>6015</b>								
160 A B1-B2 14	2 P	3841 <b>2016</b>									
	3 P	3841 <b>3016</b>	3880 <b>3016</b>								
	4 P	3841 <b>6016</b>	3880 <b>6016</b>								

(1) Standard.

(2) 4 auxiliary contacts as standard without additional contact holder.

(3) Top/bottom.

(4) For fuse size A4: max diameter 31 mm.

## BS 88 - External front and side operation - 200 to 1250 A

Rating (A) Fuse size Frame size	Number of poles	Reference Switch I - 0 - TEST	Reference Changeover I - 0 - II	External front handle I - 0	TEST External front handle I - 0 - TEST	External right side handle I - 0	Changeover external front handle I - 0 - II	Shaft extensions for handle	Terminal shrouds <sup>(3)</sup>	U type A/C <sup>(2)</sup>	Integrated solid neutral link
CD 200 A A3-A4 (5) 13 A	2 P	3841 2019							2 P 3998 2016		3829 9320
	3 P	3841 3019	3880 3019					3 P 3998 3016	3 P 3998 4016		
	4 P	3841 6019	3880 6019					4 P 3998 4016			
200 A B1-B2 15	2 P	3841 2021									3829 9325
	3 P	3841 3021	3880 3021						2 P 3998 2025		
	4 P	3841 6021	3880 6021	S2 type	S2 type	S2 type	S2 type		3 P 3998 3025		
250 A B1-B2-B3 15	2 P	3841 2024							4 P 3998 4025		3829 9339
	3 P	3841 3024	3880 3024	Black IP65 1423 2111 <sup>(1)</sup>	Black IP65 1423 2115 <sup>(1)</sup>	Black IP65 1425 2111 <sup>(1)</sup>	Black IP65 1422 2113 <sup>(1)</sup>	320 mm 1400 1032	3 P 3998 3025		
	4 P	3841 6024	3880 6024	Red/Yellow IP65 1424 2111	Red/Yellow IP65 1424 2115	Red/Yellow IP65 1428 2111	Red/Yellow IP65 1424 2113		4 P 3998 4025		
315 A B1-B2-B3 16	2 P	3841 2031								1 contact NO 3999 0701	3829 9339
	3 P	3841 3031	3880 3032 <sup>(6)</sup>						2 P 3898 2040		
	4 P	3841 6031	3880 6032 <sup>(6)</sup>						3 P 3898 3040		
400 A B1-B2- B3-B4 16	2 P	3841 2038							4 P 3898 4040	1 contact NC 3999 0702	3829 9339
	3 P	3841 3038									
	4 P	3841 6038									
630 A C1-C2 17	2 P	3821 2063									3829 9308
	3 P	3821 3063							2 P 3898 2080		
	4 P	3821 6063		S3 type		S3 type			3 P 3898 3080		
800 A C1-C2-C3 17	2 P	3821 2080							4 P 3898 4080		3829 9312
	3 P	3821 3080		Black IP65 1433 3111 <sup>(1)</sup>	Black IP65 1437 3111 <sup>(1)</sup>	Black IP65 1437 3111 <sup>(1)</sup>	Black IP65 1437 3111 <sup>(1)</sup>	320 mm 1400 1232			
	4 P	3821 6080		Red/Yellow IP65 1434 3111	Red/Yellow IP65 1438 3111	Red/Yellow IP65 1438 3111	Red/Yellow IP65 1438 3111				
1250 A D1 18	2 P	3821 2120								1 contact NC 3999 0702	3829 9312
	3 P	3821 3120							3898 2120		
	4 P	3821 6120		S4 type					3898 3120		
				Black IP65 1443 3111 <sup>(1)</sup>					3898 4120		

(1) Standard.

(2) 4 auxiliary contacts as standard without additional contact holder.

(3) Top/bottom.

(4) 8 AC as standard without support (the support is for 8 additional auxiliary contacts).

(5) For fuse size A4: max diameter 31 mm.

(6) Terminal shrouds: 3 P - 3998 3025, 4 P - 3998 4025.