


**L1382 PANEL FUSEHOLDER, BARRIER  
AND PANEL SEALED**

Design facilitates use with either heavy duty size 0 fuse links or glass fuse links. This rugged fuseholder is specified for many government equipment. The end terminal is identified LIVE. A version of this fuseholder with a 2.4mm diameter test probe aperture in the head is available under reference L1382/H.

<b>CURRENT RATING:</b>	<b>7A (temperature rise to &lt;math&gt;&lt;40^{\circ}\text{C}&lt;/math&gt;)</b> <b>15A at 55°C maximum</b>
<b>TEMPERATURE RANGE:</b>	<b>-55°C to +70°C (ambient)</b>
<b>BREAKDOWN VOLTAGE (DC):</b>	<b>&gt;10kV</b>
<b>INSERTION RESISTANCE</b>	<b>&lt;15 milliohms</b>
<b>INSULATION RESISTANCE</b>	<b>&gt;100 megohms</b>
<b>PANEL THICKNESS (MAX):</b>	<b>4mm</b>
<b>FIXING TORQUE:</b>	<b>1.7 Nm</b>
<b>HUMIDITY:</b>	<b>H5 (DEF-5011)</b>
<b>MATERIAL:</b>	<b>Moulding, phenolic</b>
<b>APPROVALS:</b>	<b>Conforms to BT 136F, DEF 59-100</b>

**ORDERING REFERENCE: L1382**



Dialight BLP reserve the right to change without prior notice the information contained within this leaflet

Dialight BLP Ltd., Exning Road, Newmarket, Suffolk, CB8 0AX, England

Tel: +44 (0) 1638 665161 Fax: +44 (0) 1638 660718 email: [sales@blpcomp.com](mailto:sales@blpcomp.com) <http://www.blpcomp.com>

□

A subsidiary of Dialight plc