


Warm-up Time (minutes)	10
Minimum Response Time (ms)	0.5
Spot Size (@ Reference Distance)	0.77 mm x 0.31 mm @ 150 mm
Analog Linearity (mm)	50 mm to 120 mm: ± 0.060 mm, 120 mm to 150 mm: ± 0.070 mm
Minimum Window Size (mm)	0.1
Discrete Output Hysteresis (mm)	Automatically adjusted
Laser Control	Yes
Alarm Output (mA)	50
Max Ambient Light (Lux)	10000
Power/Current Consumption (exclusive of load)	< 62 mA at 24 V dc
Supply Protection Circuitry	Protected against reverse polarity and transient overvoltages
Feature: Remote Teach	Yes
Feature: Clear Object Detection	Yes
Feature: Timing (Hold/Delay)	Yes
Feature: Chemical Resistant	Yes
Feature: Pump-in/ Pump-out	No
Feature: Health/ Marginal Signal Output	Yes
IO Link	Yes
RS-232	No
RS-422	No
RS-485	No
SSI	No
Wireless	No
1-wire Serial Interface	No
Profibus	No


By accepting cookies, we give you the best experience throughout our site, including access to My Account, My Library, and My Wish List. To learn more, visit our privacy policy.

RECOMMENDED PRODUCTS



DOUBLE ENDED CORDSETS

	MQDEC3-506SS
	<p>Euro-style Quick Disconnect Cable; Double-ended 5-pin Male Connector Straight; 5-pin Female Connector Straight 1.83 m Length; Chrome Plated Brass Coupling Nut; Shield Wire Grounded to Coupling Nut</p>
	MQDEC3-515SS
	<p>Euro-style Quick Disconnect Cable; Double-ended 5-pin Male Connector Straight; 5-pin Female Connector Straight 4.58 m Length; Chrome plated brass coupling nut; Shield wire grounded to coupling nut</p>
	MQDEC3-530SS
	<p>Euro-style Quick Disconnect Cable; Double-ended 5-pin Male Connector Straight; 5-pin Female Connector Straight 9.2 m Length; Chrome plated brass coupling nut; Shield wire grounded to coupling nut</p>

SINGLE ENDED CORDSETS

	MQDEC2-506
	<p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 2 m (6.5 ft) in Length; Chrome-plated brass coupling nut</p>
	MQDEC2-515
	<p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 5 m (15 ft) in Length; Chrome-plated brass coupling nut</p>
	MQDEC2-530
	<p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector.C; 9 m (30 ft) in Length; Chrome-plated brass coupling nut</p>

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	SMBLML1
	<p>Bracket: LM Series Right-angle Bracket; 12 gauge Stainless Steel</p>
	SMBLML2
	<p>By accepting cookies, we give you the best experience throughout our site, including access to My Account, My Library, and My Wish List. To learn more, visit our privacy policy.</p>