

Main

| | |
|--------------------------------|---|
| Range of product | GV2L GV2LE GV2ME GV2P TeSys D TeSys U GV2RT |
| Device short name | GV2 |
| Product or component type | Busbars |
| Accessory / separate part type | Connection accessories |
| Poles description | 3P |
| Product compatibility | 4 contactors LC1D09...D18 4 contactors LC1D25...D38 GV2L GV2LE GV2ME GV2P GV2RT LS1D32 TeSys U starter-controller |

Complementary

| | |
|---|------------------------|
| Mounting location | On terminal |
| Number of tap-offs | 4 |
| [Isc] thermal withstand current | 104 x I ² t |
| Permissible current | 11 A |
| [Ith] conventional free air thermal current | 63 A |
| [Ui] rated insulation voltage | 690 V |
| Connection pitch | 45 mm |
| Product weight | 0.077 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.