

# Inductive Proximity Sensors

iProx®



Global Proximity



Accu™ Prox



E56 Pancake



Nonmetallic Tubular



E52 Cube Style



E51, Factory Sealed



<b>3.0</b>	<b>Introduction</b>	
	Quick Reference Guide .....	<b>V8-T3-2</b>
<b>3.1</b>	<b>iProx Sensors</b>	
	Product Description .....	<b>V8-T3-10</b>
<b>3.2</b>	<b>E57 Premium+ Series Sensors</b>	
	Product Description .....	<b>V8-T3-17</b>
<b>3.3</b>	<b>E57 Premium+ Series Short Barrel Sensors</b>	
	Product Description .....	<b>V8-T3-29</b>
<b>3.4</b>	<b>Global Proximity Sensors</b>	
	Product Description .....	<b>V8-T3-36</b>
<b>3.5</b>	<b>AccuProx Analog Sensors</b>	
	Product Description .....	<b>V8-T3-45</b>
<b>3.6</b>	<b>Ferrous Only Tubular Sensors</b>	
	Product Description .....	<b>V8-T3-51</b>
<b>3.7</b>	<b>Metal Face Sensors</b>	
	Product Description .....	<b>V8-T3-54</b>
<b>3.8</b>	<b>High Current Output Sensors</b>	
	Product Description .....	<b>V8-T3-58</b>
<b>3.9</b>	<b>Miniature Short Body Sensors</b>	
	Product Description .....	<b>V8-T3-61</b>
<b>3.10</b>	<b>E56 Pancake Sensors</b>	
	Product Description .....	<b>V8-T3-66</b>
<b>3.11</b>	<b>Nonmetallic Tubular Sensors</b>	
	Product Description .....	<b>V8-T3-71</b>
<b>3.12</b>	<b>E52 Cube Style Sensors</b>	
	Product Description .....	<b>V8-T3-74</b>
<b>3.13</b>	<b>E52 Rectangular Style Sensors</b>	
	Product Description .....	<b>V8-T3-78</b>
<b>3.14</b>	<b>E55 Limit Switch Style Sensors with Nonmetallic Housings</b>	
	Product Description .....	<b>V8-T3-81</b>
<b>3.15</b>	<b>E51 Modular Limit Switch Style Sensors</b>	
	Product Description .....	<b>V8-T3-83</b>
<b>3.16</b>	<b>E51 Limit Switch Style, Factory Sealed 6P+ Sensors</b>	
	Product Description .....	<b>V8-T3-92</b>



Unless otherwise noted, the products contained in this section should not be used for functional safety applications. These products were not designed or tested to IEC 60947-5-3 or recommended for functional safety.








For Customer Service in the U.S. call 1-877-ETN CARE (386-2273),  
in Canada call 1-800-268-3578.  
For Application Assistance in the U.S. and Canada  
call 1-800-426-9184.

### Quick Reference Guide

#### Inductive Proximity Sensors

3

Sensing Application	Sensing Style	Size	Max Range	Product Family	Page
	Shielded tubular	8 mm	3 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		12 mm	4 mm	iProx Sensors	<b>V8-T3-10</b>
			2 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			5 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		18 mm	8 mm	iProx Sensors	<b>V8-T3-10</b>
			5 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			8 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		30 mm	15 mm	iProx Sensors	<b>V8-T3-10</b>
			10 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			15 mm	Global Proximity Sensors	<b>V8-T3-36</b>
	Unshielded tubular	8 mm	6 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		12mm	10 mm	iProx Sensors	<b>V8-T3-10</b>
			10 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			10 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		18 mm	18 mm	iProx Sensors	<b>V8-T3-10</b>
			20 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			18 mm	Global Proximity Sensors	<b>V8-T3-36</b>
		30 mm	29 mm	iProx Sensors	<b>V8-T3-10</b>
			22 mm	E57 Premium + Series	<b>V8-T3-17, V8-T3-29</b>
			29 mm	Global Proximity Sensors	<b>V8-T3-36</b>
	Analog tubular	12 mm	8mm	AccuProx Analog Sensors	<b>V8-T3-45</b>
		18 mm	15 mm	AccuProx Analog Sensors	<b>V8-T3-45</b>
		30 mm	25 mm	AccuProx Analog Sensors	<b>V8-T3-45</b>
	Shielded cube	40 x 40 x 40 mm	20 mm	E52 Cube Style Sensors	<b>V8-T3-74</b>
	Unshielded cube	40 x 40 x 40 mm	40 mm	E52 Cube Style Sensors	<b>V8-T3-74</b>