



Size	Dimensions (L x W x H / H2; L _w in mm)	F0.1 (class Y)	F0.15 (class A)	F0.3 (class B)
232	2.2 x 2.0 x 0.65 / 1.1; 10.0	P0K5.232.6W.Y.010	P0K5.232.6W.A.010	P0K5.232.6W.B.010
Order code		010.00187	010.00186	010.00185
516	5.0 x 1.6 x 0.65 / 1.3; 10.0	P0K5.516.6W.Y.010	P0K5.516.6W.A.010	P0K5.516.6W.B.010
Order code		010.00193	010.00192	010.00191
520	5.0 x 2.0 x 0.65 / 1.3; 10.0	P0K5.520.6W.Y.010	P0K5.520.6W.A.010	P0K5.520.6W.B.010
Order code		010.00199	010.00198	010.00197
102	10.0 x 2.0 x 0.65 / 1.3; 10.0	Upon request	P0K5.102.6W.A.010	P0K5.102.6W.B.010
Order code			010.00205	010.00204
Nominal resistance: 1000 Ω at 0 °C				
161	1.6 x 1.2 x 0.25 / 0.6; 10.0	P1K0.161.6W.Y.010	P1K0.161.6W.A.010	P1K0.161.6W.B.010
Order code		010.00222	010.00221	010.00220
202	2.0 x 2.0 x 0.65 / 1.3; 7.0	Upon request	P1K0.202.6W.A.007	P1K0.202.6W.B.007
Order code			010.02232	010.02250
202	2.0 x 2.0 x 0.65 / 1.3; 10.0	Upon request	P1K0.202.6W.A.010	P1K0.202.6W.B.007
Order code			010.02078	010.02079
216	2.5 x 1.6 x 0.65 / 1.3; 10.0	P1K0.216.6W.Y.010	P1K0.216.6W.A.010	P1K0.216.6W.B.010
Order code		010.02391	010.01109	010.01018
232	2.2 x 2.0 x 0.65 / 1.1; 7.0	P1K0.232.6W.Y.007	P1K0.232.6W.A.007	P1K0.232.6W.B.007
Order code		010.01007	010.01937	010.01008
232	2.2 x 2.0 x 0.65 / 1.1; 10.0	P1K0.232.6W.Y.010	P1K0.232.6W.A.010	P1K0.232.6W.B.010
Order code		010.00238	010.00237	010.00236
420	4.0 x 2.0 x 0.65 / 1.3; 7.0	Upon request	P1K0.420.6W.A.007	P1K0.420.6W.B.007
Order code			010.02464	010.02488
420	4.0 x 2.0 x 0.65 / 1.3; 10.0	Upon request	P1K0.420.6W.A.010	P1K0.420.6W.B.010
Order code			010.02813	010.02554
505	5.0 x 5.0 x 0.65 / 1.3; 10.0	Upon request	Upon request	P1K0.505.6W.B.010
Order code				010.02686
516	5.0 x 1.6 x 0.65 / 1.3; 7.0	Upon request	P1K0.516.6W.A.007	P1K0.516.6W.B.007
Order code			010.01934	010.01935
516	5.0 x 1.6 x 0.65 / 1.3; 10.0	P1K0.516.6W.Y.010	P1K0.516.6W.A.010	P1K0.516.6W.B.010
Order code		010.00260	010.00258	010.00257
520	5.0 x 2.0 x 0.65 / 1.3; 10.0	P1K0.520.6W.Y.010	P1K0.520.6W.A.010	P1K0.520.6W.B.010
Order code		010.00282	010.00280	010.00279
538	5.0 x 3.8 x 0.65 / 1.3; 10.0	Upon request	Upon request	P1K0.538.6W.B.010
Order code				010.00396
102	10.0 x 2.0 x 0.65 / 1.3; 7.0	Upon request	Upon request	P1K0.102.6W.B.007
Order code				010.00754
102	10.0 x 2.0 x 0.65 / 1.3; 10.0	P1K0.102.6W.Y.010	P1K0.102.6W.A.010	P1K0.102.6W.B.010
Order code		010.00309	010.00753	010.00306



Order Information - PU (TCR = 3750 ppm/K)

Size	Dimensions (L x W x H / H2; L _w in mm)	F0.1 (class Y)	F0.15 (class A)	F0.3 (class B)
Nominal resistance: 1000 Ω at 0 °C				
232	2.2 x 2.0 x 0.65 / 1.1; 10.0	Upon request	Upon request	PU1K0.232.6W.B.010
Order code				010.00244

Order Information - 7W² (Pt-wire, Ø 0.2 mm, (161) (232) (520) / Ø 0.15 mm (308))

Size	Dimensions (L x W x H / H2; L _w in mm)	F0.1 (class Y)	F0.15 (class A)	F0.3 (class B)
Nominal resistance: 100 Ω at 0 °C				
161	1.6 x 1.2 x 0.25 / 0.6; 10.0	Upon request	P0K1.161.7W.A.010	P0K1.161.7W.B.010
Order code			010.00738	010.00687
232	2.3 x 2.0 x 0.65 / 1.3; 10.0	P0K1.232.7W.Y.010	P0K1.232.7W.A.010	P0K1.232.7W.B.010
Order code		010.02074	010.00952	010.00402
308	3.0 x 0.8 x 0.25 / 0.6; 7.0	P0K1.308.7W.Y.007	P0K1.308.7W.A.007	P0K1.308.7W.B.007
Order code		010.01037	010.00996	010.00997
520	5.0 x 2.0 x 0.65 / 1.3; 10.0	Upon request	P0K1.520.7W.A.010	P0K1.520.7W.B.010
Order code			010.00107	010.00106
Nominal resistance: 1000 Ω at 0 °C				
161	1.6 x 1.2 x 0.25 / 0.6; 7.0	Upon request	P1K0.161.7W.A.007	P1K0.161.7W.B.007
Order code			010.02530	010.02531
161	1.6 x 1.2 x 0.25 / 0.6; 10.0	Upon request	P1K0.161.7W.A.010	P1K0.161.7W.B.010
Order code			010.01760	010.01766
232	2.3 x 2.0 x 0.65 / 1.3; 10.0	Upon request	P1K0.232.7W.A.010	P1K0.232.7W.B.010
Order code			010.01791	010.00239
308	3.0 x 0.8 x 0.25 / 0.6; 7.0	P1K0.308.7W.Y.007	P1K0.308.7W.A.007	P1K0.308.7W.B.007
Order code		010.01681	010.00955	010.00656

²⁾ Operating temperature range of -200 °C to +600 °C

Order Information - 6W (Pt-cladded Ni-wire, Ø 0.2 mm), D (substrate thickness, 0.4 mm)

Size	Dimensions (L x W x H / H2; L _w in mm)	F0.1 (class Y)	F0.15 (class A)	F0.3 (class B)
Nominal resistance: 100 Ω at 0 °C				
232	2.3 x 2.0 x 0.4 / 1.05; 10.0	Upon request	P0K1.232.6W.A.010.D	P0K1.232.6W.B.010.D
Order code			010.00731	010.00730
516	5.0 x 1.6 x 0.4 / 1.05; 10.0	Upon request	P0K1.516.6W.A.010.D	P0K1.516.6W.B.010.D
Order code			010.00394	010.00393