

Low Profile Power Relay with 15.7 mm height, ideal for incorporation in miniature equipments

- A wide variety of single pole, double pole, high-capacity (16 A) type and high-sensitivity type (250 mW) Relays are available.
- Low profile; 15.7 mm max. in height.
- Conforms to VDE (EN61810-1), UL508 and CSA22.2.
- IEC/EN 60335-1 conformed. (-HA Model)
- Satisfies ambient operating temperature requirement of 85°C and 105°C (-CV Model).
- Clearance and creepage distance: 8 mm / 8 mm min.
- Coil insulation system: Class F (UL1446).
- G2RL-1(A)-E-ASI: TV3 Rating models available.
- IEC/EN 60079-15 conformed
(Except G2RL-1(A)-H, G2RL-1A-E-CV(-HA) Models).

RoHS Compliant

Model Number Legend

G2RL-□□□-□-□-□-□
1 2 3 4 5 6 7

1. Number of poles

- 1 : 1 pole
- 2 : 2 pole

2. Contact Form

- None : SPDT (1c)
- A : SPST-NO (1a)

3. Enclosure rating

- None : Flux protection
- 4 : Sealed

4. Classification

- None : Standard
- E : High-capacity
- H : High-sensitivity

5. Contact Material

- None : Standard (Ag-alloy, Cd free)
- ASI : AgSnIn

6. Special Requirement

- None : Standard
- CV : 16 A, pinning 5 mm, switching at 105°C
- PW : Coil Holding Voltage type

7. Market Code

- None : General purpose
- HA : Home Appliance according to IEC/EN60335-1

Ordering Information

Terminal Shape	Market Code	Classification	Contact form	Enclosure rating	Model	Rated coil voltage	Minimum packing unit	
PCB terminals	General Purpose	Standard	SPST-NO (1a)	Flux protection	G2RL-1A	5, 12, 24, 48 VDC	20 pcs/tube	
				Sealed	G2RL-1A4			
			SPDT (1c)	Flux protection	G2RL-1			
				Sealed	G2RL-14			
			DPST-NO (2a)	Flux protection	G2RL-2A			
				Sealed	G2RL-2A4			
			DPDT (2c)	Flux protection	G2RL-2			
					G2RL-2-ASI			
		Sealed		G2RL-24				
				High-capacity		SPST-NO (1a)		
		G2RL-1A-E-ASI						
		G2RL-1A-E-CV	5, 12, 24 VDC					
		Sealed			G2RL-1A4-E	5, 12, 24, 48 VDC		
					SPDT (1c)			Flux protection
	G2RL-1-E-ASI		5, 12, 24 VDC					
	Sealed	G2RL-1-E-PW		5, 12, 24 VDC				
		G2RL-14-E	5, 12, 24, 48 VDC					
	Home Application	High-sensitivity	SPST-NO (1a)	Flux protection	G2RL-1A-H	5, 12, 24 VDC		
					SPDT (1c)			G2RL-1-H
			SPDT (1c)		G2RL-1-HA			
					DPST-NO (2a)			
		DPDT (2c)	G2RL-2-HA					
High-capacity			SPST-NO (1a)				G2RL-1A-E-HA	
			G2RL-1A-E-CV-HA					
SPDT (1c)			G2RL-1-E-HA					

Note 1. When ordering, add the rated coil voltage to the model number.

Example: G2RL-1A DC5

Rated coil voltage

However, the notation of the coil voltage on the product case will be marked as □□VDC.

Note 2. Place your order in tube (20 pcs/tube) units.

Note 3. Contact your OMRON sales representative for sealed models.



Application Examples

- Home appliances
- OA equipments
- Industrial machinery

■ Ratings

● Coil

	Item	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
	Rated voltage			% of rated voltage			
Standard, High- Capacity	5 VDC	80.0	62.5	70% max.	10% min. 10 to 32%*	130% (at 85°C)	Approx. 400 Approx. 100*
	12 VDC	33.3	360				
	24 VDC	16.7	1,440				Approx. 430
	48 VDC	8.96	5,358				
High- sensitivity	5 VDC	50	96	75% max.	10%		Approx. 250
	12 VDC	20.8	576				
	24 VDC	10.42	2,304				

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.

Note 2. The operating characteristics are measured at a coil temperature of 23°C.

Note 3. The "Max. voltage" is the maximum voltage that can be applied to the relay coil.

* These numbers are only for -PW type. Power consumption with Holding Voltage is approx.100mW. Please confirm the detail in page 6 Coil Voltage Reduction (Holding Voltage).

● Contacts: Flux Protection Type

Classification		Standard type (resistive load)		High-capacity type (resistive load)	High-sensitivity type (resistive load)
Item	Model	1-pole	2-pole	1-pole	
Contact type		Single			
Contact material		Ag-alloy (Cd free)			
Rated load		12 A at 250 VAC 12 A at 24 VDC (See note)	8 A at 250 VAC 8 A at 30 VDC (See note)	16 A at 250 VAC 16 A at 24 VDC (See note)	10 A at 250 VAC (See note)
Rated carry current		12 A (See note)	8 A (70°C)/5 A (85°C) (See note)	16 A (See note)	10 A (See note)
Max. switching voltage		440 VAC, 300 VDC			
Max. switching current		12 A	8 A	16 A	10 A
Failure rate (P level) (reference value*)		40 mA at 24 VDC			

* This value was measured at a switching frequency of 120 operations/min.

Note: Contact your OMRON representative for the ratings on sealed models.

■ Characteristics

● Flux Protection Type

Classification		Standard type		High-capacity type	High-sensitivity type
Item	Number of poles	1-pole	2-pole	1-pole	
Contact resistance *1		100 mΩ max.			
Operate (set) time		15 ms max.			
Release (reset) time		5 ms max.			
Insulation resistance *2		1,000 MΩ min.			
Dielectric strength	Between coil and contacts	5,000 VAC, 50/60 Hz for 1min			
	Between contacts of the same polarity	1,000 VAC, 50/60 Hz for 1min			
	Between contacts of different polarity	—	2,500 VAC, 50/60 Hz for 1min	—	
Impulse withstand voltage		10 kV (1.2 x 50 μs)			
Vibration resistance	Destruction	10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude)			
	Malfunction	10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude)			
Shock resistance	Destruction	1,000 m/s ²			
	Malfunction	Energized: 100 m/s ² , De-energized: 100 m/s ²			
Durability	Mechanical	20,000,000 operations (at 18,000 operations/hr)			
	Electrical *3 (resistive load)	G2RL-1A, G2RL-1(-HA): 50,000 operations at 250 VAC, 12 A 30,000 operations at 24 VDC, 12 A	G2RL-2(A)(-HA), G2RL-2-ASI: 30,000 operations at 250 VAC, 8 A 30,000 operations at 30 VDC, 8 A	G2RL-1A-E(-ASI,-HA), G2RL-1-E(-ASI,-HA,-PW): 30,000 operations at 250 VAC, 16 A 30,000 operations at 24 VDC, 16 A G2RL-1A-E-CV(-HA): 50,000 operations at 250 VAC, 16 A at 105°C	G2RL-1(A)-H: 50,000 operations at 250 VAC, 10 A
Ambient operating temperature		-40°C to 85°C (with no icing or condensation) -40°C to 105°C (with no icing or condensation) by G2RL-1A-E-CV			
Ambient operating humidity		5% to 85% (with no icing or condensation)			
Weight		Approx. 12 g			

Note 1. Values in the above table are the initial values at 23°C.

Note 2. Contact your OMRON sales representative for sealed models.

*1. Measurement conditions: 5 VDC, 1 A, voltage drop method

*2. Measurement conditions: Measured at the same points as the dielectric strength using a 500 VDC ohmmeter.

*3. 1,800 operations per hour.