

■ Model Number Legend

E2A□-□□□□□-□-□□-□□
1 2 3 4 5 6 7 8 9 10 11 12

Example: E2A-M12LS04-M1-B1 Standard, M12, long barrel, shielded, Sn=4 mm, M12 connector, PNP-NO
E2A-M08KN04-WP-B1 5M Standard, M8, short barrel, non-shielded, Sn=4 mm, pre-wired PVC cable, PNP-NO, cable length=5 m

1. Basic name
E2A
2. Sensing technology
Blank: Standard double distance
3. Housing shape and material
M: Cylindrical, metric threaded, brass
S: Cylindrical, metric threaded, stainless steel
4. Housing size
08: 8 mm
12: 12 mm
18: 18 mm
30: 30 mm
5. Barrel length
K: Standard length
L: Long body
6. Shield
S: Shielded
N: Non-shielded
7. Sensing distance
Numeral: Sensing distance: e.g. 02=2 mm, 16=16 mm

8. Kind of connection
WP: Pre-wired, PVC
M1: M12 connector (4-pole)
M3: M8 connector (4-pole)
M5: M8 connector (3-pole)
9. Power source and output
B: DC, 3-wire, PNP open collector
C: DC, 3-wire, NPN open collector
D: DC, 2-wire
E: DC, 3-wire, NPN voltage output
F: DC, 3-wire, PNP voltage output
- 10.Operation mode
1: Normally open (NO)
2: Normally closed (NC)
- 11.Specials (e.g., cable material, oscillating frequency)
- 12.Cable length
Blank: Connector type
Numeral: Cable type

Specifications

■ DC 3-wire Models

Item		Size Type	M8		M12	
			Shielded	Non-shielded	Shielded	Non-shielded
			E2A-M08□S02-M1-B1 E2A-M08□S02-M1-B2 E2A-M08□S02-M1-C1 E2A-M08□S02-M1-C2 E2A-S08□S02-□□-B1 E2A-S08□S02-□□-B2 E2A-S08□S02-□□-C1 E2A-S08□S02-□□-C2	E2A-M08□N04-M1-B1 E2A-M08□N04-M1-B2 E2A-M08□N04-M1-C1 E2A-M08□N04-M1-C2 E2A-S08□N04-□□-B1 E2A-S08□N04-□□-B2 E2A-S08□N04-□□-C1 E2A-S08□N04-□□-C2	E2A-M12□S04-□□-B1 E2A-M12□S04-□□-B2 E2A-M12□S04-□□-C1 E2A-M12□S04-□□-C2	E2A-M12□N08-□□-B1 E2A-M12□N08-□□-B2 E2A-M12□N08-□□-C1 E2A-M12□N08-□□-C2
Sensing distance		2 mm ± 10%	4 mm ± 10%	4 mm ± 10%	8 mm ± 10%	
Setting distance		0 to 1.6 mm	0 to 3.2 mm	0 to 3.2 mm	0 to 6.4 mm	
Differential travel		10% max. of sensing distance				
Target		Ferrous metal (The sensing distance decreases with non-ferrous metal.)				
Standard target (mild steel ST37)		8×8×1 mm	12×12×1 mm	12×12×1 mm	24×24×1 mm	
Response frequency (See note 1.)		1,500 Hz	1,000 Hz	1,000 Hz	800 Hz	
Power supply voltage (operating voltage range)		12 to 24 VDC. Ripple (p-p): 10% max. (10 to 32 VDC)				
Current consumption (DC 3-wire)		10 mA max.				
Output type		-B models: PNP open collector -C models: NPN open collector				
Control output	Load current (See note 2.)	200 mA max. (32 VDC max.)				
	Residual voltage	2 V max. (under load current of 200 mA with cable length of 2 m)				
Indicator		Operation indicator (Yellow LED)				
Operation mode (with sensing object approaching)		-B1/-C1 models: NO -B2/-C2 models: NC For details, refer to the timing charts.				
Protection circuit		Power source circuit reverse polarity protection, Surge suppressor, Short-circuit protection		Output reverse polarity protection, Power source circuit reverse polarity protection, Surge suppres- sor, Short-circuit protection		
Ambient air temperature		Operating: -40°C to 70°C, Storage: -40°C to 85°C (with no icing or condensation)				
Temperature influence (See note 2.)		±10% max. of sensing distance at 23°C within temperature range of -25°C to 70°C ±15% max. of sensing distance at 23°C within temperature range of -40°C to 70°C				
Ambient humidity		Operating: 35% to 95%, Storage: 35% to 95%				
Voltage influence		±1% max. of sensing distance in rated voltage range ±15%				
Insulation resistance		50 MΩ min. (at 500 VDC) between current carry parts and case				
Dielectric strength		1,000 VAC at 50/60 Hz for 1 min between current carry parts and case				
Vibration resistance		10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y and Z directions				
Shock resistance		500 m/s ² , 10 times each in X, Y and Z directions		1,000 m/s ² , 10 times each in X, Y and Z directions		
Standard and listings (See note 3.)		IEC60529: IP67, Degree of protection EN60947-5-2: EMC				
Connection method		-WP models: Pre-wired models (Standard length: 2 m) -M1 models: M12 4-pin connector models -M5 models: M8 3-pin connector models				
Weight (packaged)	Pre-wired model	Approx. 65 g		Approx. 85 g		
	M12 connector model	M12 connector models: Approx. 20 g M8 connector models: Approx. 15 g		Approx. 35 g		
Material	Case	Stainless steel or brass-nickel plated		Brass-nickel plated		
	Sensing surface	PBT				
	Cable	PVC				
	Clamping nut	Brass-nickel plated				

Note 1. The response frequency is an average value. Measurement conditions are as follows: standard target, a distance of twice the standard target distance between targets, and a setting distance of half the sensing distance.

2. When using any model at an ambient temperature between -40°C and -25°C and a power voltage between 30 and 32 VDC, use a load current of 100 mA max.,

3. For USA and CANADA : use class 2 circuit only.