

3. Electric life

1. Each 1 Form A contact connected in series

Conditions: Ambient temperature: 20°C 68°F (L/R ≤ 1 ms) (ON : OFF = 1s : 9s)

Resistive load	20A 800V DC	Min. 1×10 ³ ope.
	20A 600V DC	Min. 1×10 ⁴ ope.
Overload	20A 1,000V DC	Min. 10 ope.
Reverse	-20A 400V DC	Min. 1×10 ³ ope.
Inrush current	40A 800V DC	Min. 1×10 ³ ope.

2. 1 Form A contact only

Conditions: Ambient temperature: 20°C 68°F (L/R ≤ 1 ms) (ON : OFF = 1s : 9s)



Resistive load	20A 400V DC	Min. 1×10 ³ ope.
	20A 300V DC	Min. 1×10 ⁴ ope.
Overload	20A 500V DC	Min. 10 ope.
Reverse	-20A 200V DC	Min. 1×10 ³ ope.
Inrush current	40A 400V DC	Min. 1×10 ³ ope.

Recommended circuit

Positive polarity of load should be connected to pin 1 and pin 3, refer to the following circuit schematics.


1. Each 1 Form A contact connected in series (Bottom view)

2. 1 Form A contact only (Bottom view)




REFERENCE DATA

1. Maximum switching power




2. Ambient temperature characteristics

Tested sample: HEV2aN-P-DC12V, 6pcs




3. Coil temperature rise

Measured portion: Inside the coil
Ambient temperature: 25°C 77°F, 55°C 131°F, 85°C 185°F
Contact current: 20 A




4.-(1) Cut-off life curve (forward direction)

Contact connected in series



4.-(2) Cut-off life curve (forward direction)

1 Form A contact only




DIMENSIONS (mm inch)


The CAD data of the products with a **CAD Data** mark can be downloaded from: <http://industrial.panasonic.com/ac/e/>

CAD Data

External dimensions




PC board pattern (Bottom view)



Tolerance: $\pm 0.1 \pm 0.004$

Schematic (Bottom view)



General tolerance: $\pm 0.3 \pm 0.012$

SAFETY STANDARDS

UL/C-UL (Recognized)		VDE (Certified)	
File No.	Contact rating	File No.	Contact rating
E43028	20A 600V DC 10,000 ope. (at 85°C 185°F, Same polarity only)	40006681	20A 600V DC 10,000 ope. (at 85°C 185°F) 20A 800V DC 1,000 ope. (at 85°C 185°F) 20A 1000V DC 10 ope. (at 85°C 185°F)


NOTES

- For cautions for use, please read "GENERAL APPLICATION GUIDELINES" on page B-1.
- Usage, transport and storage conditions
 - Temperature:
 - 40 to +55°C -40 to +131°F (When coil holding voltage is 33 to 110%V)
 - 40 to +85°C -40 to +185°F (When coil holding voltage is 33% to 60%V)
 - Humidity: 5 to 85% RH (Avoid freezing and condensation.) The humidity range varies with the temperature. Use within the range indicated in the graph.

3) Atmospheric pressure: 86 to 106 kPa

Temperature and humidity range for usage, transport, and storage

(Coil holding voltage: 33 to 110%V)



(Coil holding voltage: 33 to 60%V)

