



Schneider Electric Relays


200 N. Martingale Rd., Suite 1000

Schaumburg, IL 60173

Phone: 847-441-2540 • Fax: 847-881-0741

E-Mail: relays@schneider-electric.com • Web site: www.serelays.com

ITEM # 788XBXR69C-120A, 788 POWER RELAYS / DPDT, 10 AMP RATING



[SPECIFICATIONS](#) | [COIL CHARACTERISTICS](#) | [PERFORMANCE CHARACTERISTICS](#) | [ENVIRONMENT](#)

Specifications	
Check Inventory	Check Distributor Inventory
Status	Standard
Legacy Part No.	788XBXR69C-120A
Contact Configuration	DPDT
Thermal (Carrying) Current	10 A
Terminal Style	Plug-in
Coil Resistance (Ohms)	1700 Ohm
Load Type	Standard
Contact Materials	Silver Alloy with Gold Flash
Cover Options	Plain Cover
Maximum Switching Voltages	UL: 300 VAC/125 VDC

Switching Current at Voltage (AC, Resistive)	IEC: 10 A at 250 VAC 50/60 Hz UL: 10 A at 277 VAC 50/60 Hz
---	---

Switching Current at Voltage (DC, Resistive)	IEC: 10 A at 28 VDC UL: 10 A at 30 VDC
---	---

Current Rating with Magnetic Blowout - Code 69	UL: 3 A at 150 VDC
---	--------------------

Minimum Switching Requirement	10 mA at 17 VDC
--------------------------------------	-----------------

Features	LED, Blow-out magnet, Mechanical flag indicator
-----------------	---

California Proposition 65 Warning



WARNING: This product can expose you to chemicals including:
Substance 1: Nickel compounds, which is known to the State of California to cause cancer.
Substance 2: DIDP, which is known to the State of California to cause birth defects or other reproductive harm.
 For more information go to www.p65warnings.ca.gov

Coil Characteristics

Operating Range - % of Nominal (AC)	85 to 110 %
--	-------------

Operating Range - % of Nominal (DC)	80 to 110 %
--	-------------

Average Consumption (AC / VA)	3 VA
--------------------------------------	------

Drop-out Voltage Threshold (AC)	15 %
--	------

Performance Characteristics

Electrical Life (UL508), Operations at Rated Current (Resistive)	100000
---	--------

Mechanical Life, Unpowered	5000000
-----------------------------------	---------

Operating Time (Response Time)	20 ms
---------------------------------------	-------

Dielectric Strength - Between Coil and Contact (AC)	2500 V(rms)
--	-------------

Dielectric Strength - Between Poles (AC)	2000 V(rms)
---	-------------

Environment

Product Certifications

UL (E164862)
 CSA (225619 Class 3211-07)
 CE
 RoHs

Vibration Resistance - Operational	3 g-n at 35-150 Hz
---	--------------------

Shock Resistance	10 g-n
-------------------------	--------

Degree of Protection	IP 40
-----------------------------	-------

Weight	2.93 oz 83 g
---------------	-----------------