






ORDER GUIDE**GX-6 type**






Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation
NPN output	Front sensing			GX-F6A	NPN open-collector transistor	Normally open
	Top sensing			GX-F6AI		Normally closed
				GX-F6B		Normally open
				GX-F6BI		Normally closed
				GX-H6A		Normally open
				GX-H6AI		Normally closed
PNP output	Front sensing			GX-F6A-P	PNP open-collector transistor	Normally open
	Top sensing			GX-F6AI-P		Normally closed
				GX-F6B-P		Normally open
				GX-F6BI-P		Normally open
				GX-H6A-P		Normally closed
				GX-H6AI-P		Normally closed

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.

GX-8 type






Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation
NPN output	Front sensing	 7.4 0.291 8 0.315 23 0.906	 Maximum operation distance 2.5 mm 0.098 in Stable sensing range (0 to 2.1 mm 0 to 0.083 in)	GX-F8A	NPN open-collector transistor	Normally open
	Top sensing	 8.2 0.323 8 0.315 25 0.984		GX-F8AI		Normally closed
				GX-F8B		Normally open
				GX-F8BI		Normally open
				GX-H8A		Normally closed
				GX-H8AI		Normally closed
PNP output	Front sensing	 7.4 0.291 8 0.315 23 0.906		GX-F8A-P	PNP open-collector transistor	Normally open
	Top sensing	 8.2 0.323 8 0.315 25 0.984		GX-F8AI-P		Normally closed
				GX-F8B-P		Normally open
				GX-F8BI-P		Normally open
				GX-H8A-P		Normally closed
				GX-H8AI-P		Normally open
			GX-H8B-P	Normally closed		
			GX-H8BI-P	Normally closed		

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.






ORDER GUIDE**GX-12 type**

Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation	
NPN output	Front sensing			GX-F12A	NPN open-collector transistor	Normally open	
		GX-F12AI		Normally closed			
		GX-F12B					
		GX-F12BI					
	Top sensing			GX-H12A		Normally open	
		GX-H12AI					
	GX-H12B	Normally closed					
	GX-H12BI						
PNP output	Front sensing			(0 to 3.3 mm 0 to 0.130 in) Stable sensing range	GX-F12A-P	PNP open-collector transistor	Normally open
		GX-F12AI-P			Normally closed		
		GX-F12B-P					
		GX-F12BI-P					
	Top sensing		GX-H12A-P		Normally open		
		GX-H12AI-P					
		GX-H12B-P					
		GX-H12BI-P	Normally closed				

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.

GX-15 type

Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation
NPN output	Front sensing		 Maximum operation distance 5.0 mm 0.197 in (0 to 4.2 mm 0 to 0.165 in) Stable sensing range	GX-F15A	NPN open-collector transistor	Normally open
		GX-F15AI				
		GX-F15B				
		GX-F15BI				
	Top sensing			GX-H15A		Normally open
		GX-H15AI				
	GX-H15B					
	GX-H15BI					
PNP output	Front sensing			GX-F15A-P	PNP open-collector transistor	Normally open
		GX-F15AI-P				
		GX-F15B-P				
		GX-F15BI-P				
	Top sensing		GX-H15A-P	Normally open		
		GX-H15AI-P				
		GX-H15B-P				
		GX-H15BI-P				
					Normally closed	

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.

FIBER
SENSORSLASER
SENSORSPHOTO-
ELECTRIC
SENSORSMICRO
PHOTO-
ELECTRIC
SENSORSAREA
SENSORSLIGHT
CURTAINS /
SAFETY
COMPONENTSPRESSURE /
FLOW
SENSORSINDUCTIVE
PROXIMITY
SENSORSPARTICULAR
USE
SENSORSSENSOR
OPTIONSSIMPLE
WIRE-SAVING
UNITSWIRE-SAVING
SYSTEMSMEASURE-
MENT
SENSORSSTATIC
ELECTRICITY
PREVENTION
DEVICESLASER
MARKERS

PLC

HUMAN
MACHINE
INTERFACESENERGY
CONSUMPTION
VISUALIZATION
COMPONENTSFA
COMPONENTSMACHINE
VISION
SYSTEMSUV
CURING
SYSTEMSSelection
GuideAmplifier
Built-inAmplifier-
separated**GX-F/H****GXL****GL****GX-M**GX-U/GX-FU/
GX-N**GX**