

Relays



easy Programmable Relay



XC152 PLCs



XV HMI-PLCs



Preset Counters



Hour Meters



Encoders



3.1 Relays

Product Overview	V9-T3-2
Terminal Block Relays	V9-T3-8
General Purpose Plug-In Relays	V9-T3-9
General Purpose Type AA Relays	V9-T3-23
XTRE Control Relays	V9-T3-24
Solid-State Relays	V9-T3-26
TR Series Timing Relays	V9-T3-29

3.2 Programmable Controllers

Product Overview	V9-T3-33
Fusion Integrated Machine Controller	V9-T3-36
easy Programmable Relays	V9-T3-37
easy802/806 Programmable Relays with SmartWire-DT	V9-T3-41
XC152 PLCs with and without SmartWire-DT	V9-T3-42
XV Series HMI-PLCs with and without SmartWire-DT	V9-T3-44
ELC Series Programmable Logic Controllers	V9-T3-46

3.3 Preset Counters

Product Overview	V9-T3-49
1/16 DIN LCD Preset Counter	V9-T3-50
1/8 DIN Eclipse Series Preset Counter	V9-T3-51

3.4 Ratemeters

Product Overview	V9-T3-52
Courier Series Battery Powered Ratemeter	V9-T3-53
Eclipse Series 1/8 DIN LED Ratemeter	V9-T3-54

3.5 Hour Meters

Product Overview	V9-T3-55
Electromechanical Hour Meters	V9-T3-56
Electronic LCD Hour Meters	V9-T3-57

3.6 Totalizers

Product Overview	V9-T3-58
Electromechanical Totalizers	V9-T3-59
Electronic 1/32 DIN Totalizers	V9-T3-60
Electronic Courier Series Battery Powered LCD Totalizers	V9-T3-61
Electronic 1/8 DIN LED Totalizers	V9-T3-62

3.7 Encoders

Product Overview	V9-T3-63
Shaft Encoders	V9-T3-64

For our complete product offering, see Volume 7—Logic Control, Operator Interface and Connectivity Solutions, CA08100008E and PG05400001E

Product Overview

Relays Selection Guide



3

Description	XR Series Terminal Block Relays			D1 Series	D2 Series		
	Page V9-T3-8			Page V9-T3-9	Page V9-T3-11		
Approvals							
Features	Pluggable relay allows easy field replacement, LED indicator standard, functional plug-in bridges available Only 6.2 mm wide for SP and 14 mm wide for DP DIN rail mounting			Polycarbonate cover Indicator lamp and pushbutton available Panel and DIN mounting		Polycarbonate cover Indicator lamp and pushbutton available Panel, DIN and flange mounting Latching	
Contact Data							
Configuration	SPDT	DPDT	OctoCoupler	SPDT	DPDT	DPDT Latching	4PDT
Maximum allowable load	6A or 10A	6A	2A	20A	10A	10A	10A
Material	—			Silver alloy	Silver alloy		
Dielectric strength between poles	—			1500V	1500V		
Coil Data							
AC	24 Vac or 120 Vac			6–240 Vac	6–240 Vac		
DC	12, 24, 110 Vdc			6–110 Vdc	6–110 Vdc		
Power							
VA (Vac)	1.5			0.9 VA	1.2 VA		
Watts (Vdc)	0.12			0.7 Watts	0.9 Watts		
General Data							
Ambient temperature							
Storage	—			–40° to 185°F (–40° to 85°C)	–40° to 185°F (–40° to 85°C)		
Operational	–4° to 140°F (–20° to 60°C)			–40° to 131°F (–40° to 55°C)	–40° to 131°F (–40° to 55°C)		
Response time	Available upon request			20 milliseconds	20 milliseconds		
Life							
Mechanical operations	20 million			10 million	10 million		
Electrical operations	—			100,000	200,000		

For our complete product offering, see Volume 7—Logic Control, Operator Interface and Connectivity Solutions, CA08100008E and PG05400001E.