


Elektrische Daten
Electrical data

Bemessungs- strom Rated current	Spannungsfall Voltage drop @ I_N [mV]	Leistungsabgabe Power loss @ $1,0 \times I_N$ [W]	Schmelzintegral Pre-arcing i^2t -value @ $10 \times I_N$ [A ² s]	Bemessungs- Ausschaltvermögen Rated breaking capacity		Approbationen Approvals 
				AC	DC	
100 mA	2500	0,3	0,0009	30 kA @ 1000 V	30 kA @ 1000 V	✓
125 mA	2200	0,3	0,0017	30 kA @ 1000 V	30 kA @ 1000 V	✓
160 mA	2000	0,4	0,004	30 kA @ 1000 V	30 kA @ 1000 V	✓
200 mA	900	0,2	0,01	30 kA @ 1000 V	30 kA @ 1000 V	✓
250 mA	800	0,2	0,02	30 kA @ 1000 V	30 kA @ 1000 V	✓
315 mA	700	0,3	0,035	30 kA @ 1000 V	30 kA @ 1000 V	✓
400 mA	650	0,3	0,07	30 kA @ 1000 V	30 kA @ 1000 V	✓
500 mA	650	0,4	0,15	30kA @ 1000V *	30kA @ 1000V *	✓
630 mA	650	0,5	0,15	30 kA @ 1000 V	30 kA @ 1000 V	✓
800 mA	600	0,5	0,32	30 kA @ 1000 V	30 kA @ 1000 V	✓
1 A	750	0,8	0,32	30 kA @ 1000 V	30 kA @ 1000 V	✓
1,6 A	650	1,1	0,31	30 kA @ 1000 V	30 kA @ 1000 V	✓
2 A	650	1,4	0,64		30 kA @ 1000 V	✓

* **Zusätzliches Bemessungs-Ausschaltvermögen: 50 kA @ 1000 V AC/DC**
Additional rated breaking capacity: 50 kA @ 1000 V AC/DC

Bemessungsspannung des Sicherungshalters berücksichtigen
Rated voltage of the fuse-holder has to be considered