Communication	Communication interface, can be used with WAGO USB Communication Cable (750-923) or WAGO IO-Link Communication Module (2789-9080)

Efficiency/Power losses:

Power loss P_l	≤ 1 W (Stand-by); ≤ 2,2 W (No load); ≤ 12 W (230 VAC; Nominal load)
Efficiency (typ.)	95,3 % (230 VAC; 10 ADC; 25 °C)

Fuse protection:

Internal fuse	T 6.3 A / 250 VAC
External fuse (required)	An external DC fuse is required for the DC input voltage.
External fuse (recommended)	16 A (for USA/Canada: 15 A)

Safety and protection:

Insulation voltage (SEC-GND)	DC 0,5 kV
Insulation voltage (SEC-Signal)	DC 0,5 kV
Protection class	I
Protection class	IP20 (per EN 60529)
Feedback voltage	≤ DC 35 V
Overvoltage category	III (≤ 2000 m a. s.l.); II (> 2000 m a. s.l.)
Transient protection, primary	Yes
Overvoltage protection, secondary	Internal protective circuit ≤ 35 VDC (in the event of a fault)
Short circuit protection	Yes
No-load proof	Yes
Parallel operation	Yes
Series connection	Yes
MTBF	> 1,200,000 h (per IEC 61709)

Connection data

Connection type (1)	Input/Output/Signaling
Connection technology	CAGE CLAMP®
WAGO terminal	WAGO 721 Series
Solid conductor	0,08 … 2,5 mm² / 28 … 12 AWG
Fine-stranded conductor	0,08 … 2,5 mm² / 28 … 12 AWG
Fine-stranded conductor with ferrule with plastic collar	0,25 … 1,5 mm² / 20 … 16 AWG

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Fine-stranded conductor with ferrule without plastic collar	0,25 … 2,5 mm² / 20 … 14 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inch

Geometrical Data

Width	50 mm / 1.969 inch
Height	130 mm / 5.118 inch
Length from upper-edge of DIN-35 rail	130 mm / 5.118 inch
Note on dimensions	Height without connector Height with connector: 166 mm

Mechanical data

Type of mounting	DIN-35 rail (EN 60715)

Material Data

Weight	1000 g

Environmental Requirements

Surrounding air (operating) temperature	-25 … 70 °C (Device starts at −40 °C (type-tested))
Surrounding air (storage) temperature	-40 … 85 °C
Relative humidity	5 … 96 % (no condensation permissible)
Derating	−3 %/K (> +55 °C and U_i < 230 VAC); −3 %/K (> +60 °C and U_i ≥ 230 VAC)
Pollution degree	2
Climatic category	3K3 (per EN 60721)
Max. operating altitude	5000 m

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61010-1; EN 61010-2-201; EN 61204-3; UL 61010-1; UL 61010-2-201

Commercial data

Packaging type	BOX
Country of origin	CN
GTIN	4055143907330
Customs Tariff No.	85044082900

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.