

- Enclosed power supply with screw terminal connection
- Certification according to IEC/EN/ES 60601-1 3rd edition for 2 x MOPP
- Low leakage current <75 µA rated for BF applications
- Risk management process according to ISO 14971 incl. risk management file
- Acceptance criteria for electronic assemblies acc. to IPC-A-610 Level 3
- EMC compliance to IEC 60601-1-2 ed. 4
- Protection class I and II prepared
- Operating up to 5000 m altitude
- Ready to meet ErP directive, <0.15 W no load power consumption
- 5 year product warranty



ES 60601-1 IEC 60601-1

The TPP 40 Series of 40 Watt AC/DC power supplies feature a reinforced double I/O isolation system according to latest medical safety standards IEC/EN/ES 60601-1 3rd edition for 2 x MOPP up to 5000 m altitude. The earth leakage current is below 75 µA what makes the units suitable for BF (body floating) applications.

The excellent efficiency of up to 92% allows a high power density for the standard 2.44" x 3.0" packaging format. The full load operating temperature range is -40°C to +70°C while it goes up to 85°C with 50% load derating. The EMC characteristic complies to IEC 60601-1-2 ed.4 and is dedicated for applications in industrial and domestic fields. High reliability is provided by use of industrial quality grade components and an excellent thermal management. It makes the products an ideal solution for medical devices and for demanding safety and space critical applications.

Models

Order Code	Output Power	Output 1		Output 2		Output 3		Efficiency typ.
		Vnom	I _{max}	Vnom	I _{max}	Vnom	I _{max}	
TPP 40-105	40 W	5 VDC	8'000 mA					90 %
TPP 40-112		12 VDC	3'340 mA					92 %
TPP 40-115		15 VDC	2'670 mA					92 %
TPP 40-124		24 VDC	1'670 mA					92 %
TPP 40-221		+12 VDC	3'340 mA	+5 VDC	6'000 mA			89 %
TPP 40-231		+15 VDC	2'670 mA	+5 VDC	6'000 mA			89 %
TPP 40-251		+24 VDC	1'670 mA	+5 VDC	6'000 mA			86 %
TPP 40-321M2		+12 VDC	3'340 mA	+5 VDC	6'000 mA	-12 VDC	500 mA	88 %
TPP 40-331M3		+15 VDC	2'670 mA	+5 VDC	6'000 mA	-15 VDC	500 mA	88 %
TPP 40-3512		+24 VDC	1'670 mA	+5 VDC	6'000 mA	+12 VDC	500 mA	86 %

- Note
- Total output power must not exceed 40 W.
 - Other output models are available on request.
 - Multi output models have a common ground.

Input Specifications

Input Voltage	- AC Range	85 - 264 VAC (Full Range)
	- DC Range	120 - 370 VDC (designed for, no certification)
Input Frequency		47 - 63 Hz
Input Current	- Full Load & Vin = 230 VAC	single output models: 500 mA max. dual output models: 550 mA max. triple output models: 550 mA max.
	- Full Load & Vin = 115 VAC	single output models: 1000 mA max. dual output models: 1050 mA max. triple output models: 1050 mA max.
Power Consumption	- at no Load	150 mW max. (Ready to meet ErP directive)
Input Inrush Current	- at 230 VAC	60 A max.
Input Protection		T 3.15 A / 250 VAC (Internal Fuse in L & N)

Output Specifications

Output Voltage Adjustment		±10% (by trim potentiometer) (only Output 1) Output power must not exceed rated power!
Voltage Set Accuracy		±1% max. (Output 1) ±2% max. (Output 2 and 3)
Regulation	- Input Variation (Vmin - Vmax)	single output models: 0.2% max. dual output models: 0.2% max. triple output models: 0.2% max.
	- Load Variation (0 - 100%)	single output models: 0.5% max. 0.7% max. (5 VDC model) dual output models: 0.5% max. (Output 1) 1.5% max. (Output 2) triple output models: 0.5% max. (Output 1) 1.5% max. (Output 2) 0.7% max. (Output 3)
	- Cross Regulation (25% / 100% asym. load)	dual output models: 1.5% max. triple output models: 1.5% max.
Ripple and Noise (20 MHz Bandwidth)	- single output	5 VDC model: 75 mVp-p typ. (with 10 µF X7R) 12 VDC model: 75 mVp-p typ. (with 10 µF X7R) 15 VDC model: 75 mVp-p typ. (with 10 µF X7R) 24 VDC model: 75 mVp-p typ. (with 1 µF X7R)
	- dual output	12 / 5 VDC model: 120 / 100 mVp-p typ. (with 10 µF X7R) 15 / 5 VDC model: 150 / 100 mVp-p typ. (with 10 µF X7R) 24 / 5 VDC model: 240 / 100 mVp-p typ. (with 10 µF X7R)
	- triple output	12 / 5 / -12 VDC model: 120 / 100 / 120 mVp-p typ. (with 10 µF X7R) 15 / 5 / -15 VDC model: 150 / 100 / 150 mVp-p typ. (with 10 µF X7R) 24 / 5 / 12 VDC model: 240 / 100 / 120 mVp-p typ. (with 10 µF X7R)
Capacitive Load	- single output	5 VDC model: 16'000 µF max. 12 VDC model: 2'785 µF max. 15 VDC model: 1'780 µF max. 24 VDC model: 700 µF max.
	- dual output	12 / 5 VDC model: 1'750 / 2'000 µF max. 15 / 5 VDC model: 1'670 / 2'000 µF max. 24 / 5 VDC model: 440 / 2'000 µF max.
	- triple output	12 / 5 / -12 VDC model: 1'750 / 2'000 / 420 µF max. 15 / 5 / -15 VDC model: 1'670 / 2'000 / 420 µF max. 24 / 5 / 12 VDC model: 440 / 2'000 / 420 µF max.
Minimum Load		not required 0.5 W for Vout1 and Vout2 if Vout3 = Full Load
Temperature Coefficient		±0.02 %/K
Hold-up Time	- at 115 VAC	25 ms min.
Start-up Time	- at 230 VAC	1'000 ms max.
Output Current Limitation		115 - 180% of Iout max.

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.