

NON-ISOLATED DC/DC CONVERTERS

8.3 Vdc - 14 Vdc Input

0.75 Vdc - 5.0 Vdc/10 A Output

bel
POWER PRODUCTS

SRBC-10A2Ax

RoHS Compliant

Rev.A

- Non-Isolated
- High Efficiency
- High Power Density
- Excellent Thermal Performance
- Low Cost
- Flexible Output Voltage Sequencing
- Remote Sense
- Able to Sink/Source Current
- Under-voltage Lockout (UVLO)
- Over Temperature Protection
- OCP/SCP
- Wide Input
- Wide Trim
- Remote On/Off
- Active Low/High (option)
- Industrial Temperature Range



Description

The Bel SRBC-10A2Ax modules are a series of non-isolated dc/dc converters that deliver up to 10 A of output current with full load efficiency of 93% at 3.3 Vdc output. These modules provide precisely regulated voltage programmable via external resistor from 0.75 Vdc to 5.0 Vdc over a wide range of input voltage (8.3 Vdc - 14 Vdc). These modules have a sequencing feature that enables designers to implement various types of output voltage sequencing when powering multiple voltages on a board. The open-frame construction and small footprint enable designers to develop cost and space-efficient solutions. Standard features include remote On/Off, over current protection, short current protection, wide input, and programmable output voltage.

Part Selection

| Output Voltage | Input Voltage | Max. Output Current | Max. Output Power | Typical Efficiency | Model Number Active Low | Model Number Active High |
|----------------|---------------|---------------------|-------------------|--------------------|-------------------------|--------------------------|
| 0.75 V - 5.0 V | 8.3 V - 14 V | 10 A | 50.0 W | 95% | SRBC-10A2AL | SRBC-10A2A0 |

- Notes:** 1. Add "G" suffix at the end of the model number to indicate Tray Packaging.
2. All part numbers above indicate RoHS 6. Change the second letter "R" to "7" for RoHS 5 part numbers.

Absolute Maximum Ratings

| Parameter | Min | Typ | Max | Notes |
|---------------------------------|--------|-----|-----------------|-------|
| Input Voltage (continuous) | -0.3 V | - | 15 V | |
| Output Enable Terminal Voltage | -0.3 V | - | 15 V | |
| Sequencing Voltage ¹ | -0.3 V | - | V _{in} | |
| Ambient Temperature | -40 °C | - | 85 °C | |
| Storage Temperature | -55 °C | - | 125 °C | |

- Notes:** All specifications are typical at 25 °C unless otherwise stated.
1. SRBC-10A2Ax series of modules include a sequencing feature that enables users to implement various types of output voltage sequencing in their applications. This is accomplished via an additional sequencing pin. When the sequencing feature is not used, tie the SEQ pin to V_{in} or leave it unconnected.

NON-ISOLATED DC/DC CONVERTERS

8.3 Vdc - 14 Vdc Input

0.75 Vdc - 5.0 Vdc/10 A Output



Input Specifications

| Parameter | Min | Typ | Max | Notes |
|---|-------|-----------------------|-----------------------|---|
| Input Voltage | | | | |
| Vo, set ≤ 3.63 V | 8.3 V | 12 V | 14 V | |
| Vo, set > 3.63 V | 8.3 V | 12 V | 13.2 V | |
| Input Current (full load) | - | - | 6.5 A | An input line fuse must always be used. |
| Input Current (no load) | - | 50 mA | - | |
| Remote Off Input Current | - | 2 mA | - | |
| Input Reflected Ripple Current (pk-pk) | - | - | 400 mA | Tested with one 1000 uF/25 V AL input capacitor with ESR=0.03 ohm max and 4 × 47 uF/16 V tan capacitors with ESR=0.013 ohm max at 100 kHz, & simulated source impedance of 1000 nH, 5 Hz to 20 MHz. |
| Input Reflected Ripple Current (rms) | - | - | 150 mA | |
| I ² t Inrush Current Transient | - | 0.04 A ² s | 0.08 A ² s | |
| Turn-on Voltage Threshold | - | 8.2 V | | |
| Turn-off Voltage Threshold | - | 7.9 V | | |

Note: All specifications are typical at 25 °C unless otherwise stated.

Output Specifications

| Parameter | Min | Typ | Max | Notes | |
|--|-------------------|--------------------|--------------------|--|--|
| Output Voltage Set Point | -2% Vo,set | - | 2% Vo,set | Vin=12 V, full load | |
| Load Regulation | - | 0.1% Vo,set | - | | |
| Line Regulation | - | 0.1% Vo,set | - | | |
| Regulation Over Temperature (-40 °C to +85 °C) | - | 0.3% Vo,set | - | Tref=Tamin to Tamax | |
| Output Current | 0 A | - | 10 A | | |
| Current Limit Threshold | - | 200% Io | - | | |
| Short Circuit Surge Transient | - | 1 A ² s | 3 A ² s | | |
| Ripple and Noise (pk-pk) | - | 50 mV | 100 mV | Tested with 0-20 MHz, with 10 uF tantalum capacitor & 1 uF ceramic capacitor | |
| Ripple and Noise (rms) | - | 20 mV | 40 mV | | |
| Turn on Time | - | 6 mS | 10 mS | | |
| Overshoot at Turn on | - | - | 1% Vo,set | | |
| Output Capacitance | - | - | 5000 uF | | |
| Transient Response | | | | | |
| 50% ~ 100% Max Load | Vo = 0.75 V - 5 V | - | 100 mV | - | di/dt=2.5 A/uS; Vin=12 V; and with 2 × 150 uF polymer capacitors at the output |
| Settling Time | | - | 50 uS | - | |
| 100% ~ 50% Max Load | | - | 100 mV | - | |
| Settling Time | | - | 50 uS | - | |

Note: All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.