




## Glass fibre Insulated Flat Pair Types 'K', 'J' & 'T' 1/0.3 solid strand– to IEC584



- Glass fibre insulated flat pair construction, conductors laid flat, Glass fibre insulated with Glass fibre overall, silicone varnished throughout
- Good temperature resistance but not suitable where fluids are present
- All types; conductors are made from associated K, J or T thermocouple alloy type
- Tolerance Class 2 to IEC-584
- Insulation rating -60°C to 350°C (short periods up to 400°C)
- Colour code (cores & jacket) to IEC-584-3

Type	Conductors	Cores	Jacket	Reel Length	Manufacturers Code	order code
KX	1/0.3mm	+Green/-White	Green	10 metres	WK-351-D	708-5930
KX	1/0.3mm	+Green/-White	Green	25 metres	WK-351-D	XF-1315-FAR
KX	1/0.3mm	+Green/-White	Green	50 metres	WK-351-D	708-5941
KX	1/0.3mm	+Green/-White	Green	100 metres	WK-351-D	XF-1290-FAR
KX	1/0.3mm	+Green/-White	Green	200 metres	WK-351-D	XF-1301-FAR
K	1/0.508mm	+Green/-White	Green	25 metres	WK-352-D	XF-1253-FAR
K	1/0.508mm	+Green/-White	Green	50 metres	WK-352-D	XF-1258-FAR
JX	1/0.3mm	+Black/-White	Black	10 metres	WJ-032-D	708-5928
TX	1/0.3mm	+Brown/-White	Brown	10 metres	WT-356-D	708-5953

### About Labfacility

Formed in 1971, Labfacility specialize in the field of Temperature and Process Measurement.

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors

### Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

### Contact Details

Email  
sales@labfacility.com

Website  
www.labfacility.com