

— at 110 V Rated value	0.25 A
— at 24 V Rated value	15 A
Operating current with 3 current paths in series	
• at DC-1	
— at 24 V Rated value	15 A
— at 110 V Rated value	15 A
— at 220 V Rated value	15 A
— at 440 V Rated value	0.9 A
— at 600 V Rated value	0.7 A
• at DC-3 at DC-5	
— at 110 V Rated value	15 A
— at 220 V Rated value	1.2 A
— at 24 V Rated value	15 A
— at 440 V Rated value	0.14 A
— at 600 V Rated value	0.14 A
Operating power	
• at AC-1	
— at 230 V at 60 °C Rated value	6 kW
— at 400 V at 60 °C Rated value	10.5 kW
— at 690 V at 60 °C Rated value	18 kW
Operating power for ≥ 200000 operating cycles at AC-4	
• at 400 V Rated value	1.15 kW
• at 690 V Rated value	1.15 kW
Active power loss at AC-3 at 400 V for rated value of the operating current per conductor	0.4 W
Operating frequency	
• at AC-1 maximum	1 000 1/h
• at AC-2 maximum	750 1/h
• at AC-3 maximum	750 1/h
• at AC-4 maximum	250 1/h
No-load switching frequency	
• for DC	10 000 1/h
Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage for DC	
• Rated value	220 V
Operating range factor control supply voltage rated value of the magnet coil for DC	0.8 ... 1.1
Closing power of the magnet coil for DC	4 W
Holding power of the magnet coil for DC	4 W
Closing delay	

<ul style="list-style-type: none"> • for DC 	30 ... 100 ms
Opening delay	
<ul style="list-style-type: none"> • for DC 	7 ... 13 ms
Arcing time	10 ... 15 ms
Residual current of the electronics for control with signal <0>	
<ul style="list-style-type: none"> • with AC at 230 V maximum permissible 	3 mA
<ul style="list-style-type: none"> • for DC at 24 V maximum permissible 	10 mA

Auxiliary circuit:

Number of NC contacts	
<ul style="list-style-type: none"> • for auxiliary contacts — instantaneous contact 	0
Number of NO contacts	
<ul style="list-style-type: none"> • for auxiliary contacts — instantaneous contact 	1
Product expansion Auxiliary switch	Yes
Operating current at AC-12 maximum	10 A
Operating current at AC-15	
<ul style="list-style-type: none"> • at 230 V Rated value 	10 A
<ul style="list-style-type: none"> • at 400 V Rated value 	3 A
<ul style="list-style-type: none"> • at 690 V Rated value 	1 A
Operating current at DC-12	
<ul style="list-style-type: none"> • at 60 V Rated value 	6 A
<ul style="list-style-type: none"> • at 110 V Rated value 	3 A
<ul style="list-style-type: none"> • at 125 V Rated value 	2 A
<ul style="list-style-type: none"> • at 220 V Rated value 	1 A
<ul style="list-style-type: none"> • at 600 V Rated value 	0.15 A
Operating current at DC-13	
<ul style="list-style-type: none"> • at 24 V Rated value 	10 A
<ul style="list-style-type: none"> • at 60 V Rated value 	2 A
<ul style="list-style-type: none"> • at 110 V Rated value 	1 A
<ul style="list-style-type: none"> • at 125 V Rated value 	0.9 A
<ul style="list-style-type: none"> • at 220 V Rated value 	0.3 A
<ul style="list-style-type: none"> • at 600 V Rated value 	0.1 A
Contact reliability of the auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)

UL/CSA ratings:

Full-load current (FLA) for three-phase AC motor	
<ul style="list-style-type: none"> • at 480 V Rated value 	4.8 A
<ul style="list-style-type: none"> • at 600 V Rated value 	6.1 A
yielded mechanical performance [hp]	
<ul style="list-style-type: none"> • for single-phase AC motor 	