

power contactor, AC-3 110 A, 55 kW / 400 V, 1 NO + 1 NC, 24 V AC, 50 Hz 3-pole, 3NO, Size S3 Spring-type terminal



| | |
|--------------------------|-----------------|
| Product brand name | SIRIUS |
| Product designation | Power contactor |
| Product type designation | 3RT2 |

| General technical data | |
|---|-----------------------------|
| Size of contactor | S3 |
| Product extension | |
| <ul style="list-style-type: none"> function module for communication | No |
| <ul style="list-style-type: none"> Auxiliary switch | Yes |
| Surge voltage resistance | |
| <ul style="list-style-type: none"> of main circuit rated value | 8 kV |
| <ul style="list-style-type: none"> of auxiliary circuit rated value | 6 kV |
| maximum permissible voltage for safe isolation | |
| <ul style="list-style-type: none"> between coil and main contacts acc. to EN 60947-1 | 690 V |
| Protection class IP | |
| <ul style="list-style-type: none"> on the front | IP20 |
| <ul style="list-style-type: none"> of the terminal | IP00 |
| Shock resistance at rectangular impulse | |
| <ul style="list-style-type: none"> at AC | 6.7 g / 5 ms, 4.0 g / 10 ms |

| | |
|---|------------------------------|
| Shock resistance with sine pulse | |
| • at AC | 10.6 g / 5 ms, 6.3 g / 10 ms |
| Mechanical service life (switching cycles) | |
| • of contactor typical | 10 000 000 |
| • of the contactor with added electronics-compatible auxiliary switch block typical | 5 000 000 |
| • of the contactor with added auxiliary switch block typical | 10 000 000 |
| Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | K |
| Reference code acc. to DIN EN 81346-2 | Q |

Ambient conditions

| | |
|--|----------------|
| Installation altitude at height above sea level | |
| • maximum | 2 000 m |
| Ambient temperature | |
| • during operation | -25 ... +60 °C |
| • during storage | -55 ... +80 °C |

Main circuit

| | |
|---|---------|
| Number of poles for main current circuit | 3 |
| Number of NO contacts for main contacts | 3 |
| Operating voltage | |
| • at AC-3 rated value maximum | 1 000 V |
| Operating current | |
| • at AC-1 at 400 V | |
| — at ambient temperature 40 °C rated value | 130 A |
| • at AC-1 | |
| — up to 690 V at ambient temperature 40 °C rated value | 130 A |
| — up to 690 V at ambient temperature 60 °C rated value | 110 A |
| — up to 1000 V at ambient temperature 40 °C rated value | 70 A |
| — up to 1000 V at ambient temperature 60 °C rated value | 60 A |
| • at AC-2 at 400 V rated value | 110 A |
| • at AC-3 | |
| — at 400 V rated value | 110 A |
| — at 500 V rated value | 110 A |
| — at 690 V rated value | 98 A |
| • at AC-4 at 400 V rated value | 97 A |
| • at AC-5a up to 690 V rated value | 120 A |
| • at AC-5b up to 400 V rated value | 110 A |