Mini contactors, relays, contactors

Contents

Ordering

Mini contactor relays DILER, DILEEM, DILEM

Mini contactor relays, contactors 2

Auxiliary contact modules 6

Accessories 8

Actuating voltages 66

DILA contactor relays

Contactor relays 10

Auxiliary contact modules 12

Actuating voltages 68

Technical overview

Contactors DILM, DILH 14

System overview

Contactors DILM, DILH 16

Ordering

Contactors DILM, DILH

Basic devices up to 170 A 18

Complete units up to 170 A 24

Standard devices greater than 170 A 28

Comfort devices greater than 170 A 30

Basic devices up to 200 A, 4 pole 34

Auxiliary contact modules 36

Engineering

Auxiliary contact modules 40

Ordering

DILK contactors for capacitors 41

Engineering

Contactors for power factor correction 42

Ordering

Star-delta combinations SDAINL 44

Engineering

Star-delta combinations SDAINL 46

Ordering

DIUL reversing combinations 48

Description

CMD contactor monitoring device 64

Ordering

CMD contactor monitoring device 64

Ordering

DILM contactor relays, DILM, DILH contactors

suppressor circuit 50

Accessories 52

Ordering

Actuating voltages contactors DILM, DILH

Basic devices up to 170 A 69

Basic devices up to 200 A, 4 pole 74

Contactors up to 150 A
with electronic actuation 76

Replacement coils 71

Comfort devices greater than 170 A 77

Standard devices greater than 170 A 77

Electronic modules including coil 77

Contactors for capacitors 77

Engineering

Contact travel diagrams 78

Enclosure 79

UL/CSA-approved rating data 80

UL/CSA special purpose ratings 81

UL/CSA short circuit current rating 82

Contactors for resistive loads 84

Electrical life span 86

Short-time loading 90

Operating frequency 91

Switching of DC current 92

Technical data

Mini contactor relays, contactor relays 93

Contactor monitoring device 96

Basic devices up to 170 A 104

Basic devices up to 200 A, 4 pole 120

Comfort devices greater than 170 A 112

Standard devices greater than 170 A 112

Contactors for capacitors 123

Contactors up to 150 A
with electronic actuation 126

Lighting contactors 125

Auxiliary contact modules 128

Accessories 128

Dimensions

Mini contactor relays 130

Contactor relays 131

Basic devices up to 170 A 131

Basic devices up to 200 A, 4 pole 133

Contactors larger than 170 A 134

Contactors for capacitors 136

Lighting contactors 136

Contactor combinations 137

Accessories 138

1 Ordering

Screw terminals



DILER mini contactor relays

Rated operational current AC-15 220 V 230 V 240 V	Rated operational current AC-15 380 V 400 V 415 V	Conventional free air thermal current	Contact N/O = normally open contact NC = normally closed contact		Distinctive number	Circuit symbol	For use with
I_e A	I_e A	I_{th} A					
6	3	10	4 N/O	–	40E		DILE…
			3 N/O	1 NC	31E		DILE…
			2 N/O	2 NC	22E		DILE…

Notes

Coil terminal marking as specified in EN 50005
Contact numbers to EN 50011
The following applies to DC-operated contactors:
- Integrated diode-resistor combination
- Coil rating 2.6 W

Information relevant for export to North America

Product Standards	IEC/EN 60947-4-1; UL508; CSA-C22.2 No.14-05; CE marking
UL File No.	E29184
UL CCN	NKCR
CSA File No.	012528
CSA Class No.	3211-03
NA Certification	UL Listed, CSA certified