

Head-mounted transducer - MCR-FL-HT-T-I-EX - 2864532

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



MCR head-mounted temperature transducers, programmable, intrinsically safe, for resistance thermometers, thermocouples, resistance-type sensors and voltage sensors. For Pt 100 resistance thermometers

Your advantages

- Input for resistance thermometers, thermocouples, and linear mV signals, Ex ia IIC
- Configuration via software
- Can be installed in zone 0
- 2-way electrical isolation
- Loop-powered
- 1-channel
-



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4017918893231
Weight per Piece (excluding packing)	82.300 g
Custom tariff number	85437090
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 55 °C
Degree of protection	IP00
	IP66 (Installed in the connection head)

Input data

Configurable/programmable	Yes, programmable
---------------------------	-------------------

Head-mounted transducer - MCR-FL-HT-T-I-EX - 2864532

Technical data

Input data

Sensor types (RTD) that can be used	Pt, Ni (100, 500, 1000); min. measurement range 10 K
Sensor types that can be used (TC)	B, C, D, E, J, K, L, N, R, S, T, U; min. measurement range 50 K/500 K
Connection technology	2, 3, 4-wire
Input signal range	10 Ω ... 400 Ω (min. measurement range 10 Ω)
	10 Ω ... 2000 Ω (min. measurement range 100 Ω)
	-10 mV ... 100 mV (min. measurement range 5 mV)

Output data

Configurable/programmable	Yes, programmable
Current output signal	4 mA ... 20 mA
	20 mA ... 4 mA
Max. current output signal	≤ 25 mA
Output current with short-circuit	≤ 3.6 mA or ≥ 21 mA (adjustable, not for thermocouples)
Output current with wire break	≤ 3.6 mA or ≥ 21 mA (adjustable)
Output current range with overrange/underrange	3.8 mA ... 20.5 mA (linear increase/decrease)
Load/output load current output	≤ 720 Ω (For $U_V = 24 V$; $U_{supply} = 8 V / 0.025 A$)
Configurable/programmable	no

Power supply

Designation	Loop-powered
Supply voltage range	8 V DC ... 30 V DC
Max. current consumption	< 3.5 mA

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 1.75 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.75 mm ²
Conductor cross section AWG	24 ... 15
Torque	0.5 Nm ... 0.6 Nm
pluggable	no

General

Step response (10-90%)	< 2 s
Switch-on delay	6 s
Configuration	Using MCR-PI-CONF-WIN configuration software package
Standards/regulations	NAMUR recommendation NE 21
Housing material	Polycarbonate, PC
Color	green
Line monitoring	NE 43
Conformance	CE-compliant
ATEX	# II 1 G Ex ia IIC T6/T5/T4