



2NO+2NC CONTACTOR, AC3: 7.5KW AC 230V 50HZ 4-POLE,
2NO+2NC, SZ: S00, SCREW TERMINAL

product brand name	SIRIUS
Product designation	3RT2 contactor
General technical data:	
Product expansion function module for communication	No
Insulation voltage	
• Rated value	690 V
maximum permissible voltage for safe isolation between coil and main contacts acc. to EN 60947-1	400 V
Degree of pollution	3
Shock resistance	
• at rectangular impulse	
— with AC	7,3g / 5 ms, 4,7g / 10 ms
• with sine pulse	
— with AC	11,4g / 5 ms, 7,3g / 10 ms
Surge voltage resistance Rated value	6 kV
Mechanical service life (switching cycles)	
• of the contactor typical	30 000 000
• of the contactor with added electronics-compatible auxiliary switch block typical	5 000 000
• of the contactor with added auxiliary switch block typical	10 000 000
Protection class IP	
• on the front	IP20
Equipment marking	

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

Q
Q

Main circuit:

Number of poles for main current circuit	4
Number of NC contacts for main contacts	2
Number of NO contacts for main contacts	2
Operating current	
<ul style="list-style-type: none"> • at AC-1 <ul style="list-style-type: none"> — up to 690 V at ambient temperature 40 °C Rated value — up to 690 V at ambient temperature 60 °C Rated value • at AC-2 at AC-3 at 400 V <ul style="list-style-type: none"> — per NO contact Rated value — per NC contact Rated value 	22 A 20 A 16 A 9 A
Operating current with 1 current path	
<ul style="list-style-type: none"> • at DC-1 <ul style="list-style-type: none"> — at 24 V Rated value — at 110 V Rated value — at 220 V Rated value — at 440 V Rated value • at DC-3 at DC-5 <ul style="list-style-type: none"> — at 24 V per NC contact Rated value — at 24 V per NO contact Rated value — at 110 V per NC contact Rated value — at 110 V per NO contact Rated value — at 220 V per NC contact Rated value — at 220 V per NO contact Rated value 	20 A 2.1 A 0.8 A 0.6 A 20 A 20 A 0.075 A 0.15 A 0.375 A 0.75 A
Operating current with 2 current paths in series	
<ul style="list-style-type: none"> • at DC-1 <ul style="list-style-type: none"> — at 24 V Rated value — at 110 V Rated value — at 220 V Rated value — at 440 V Rated value • at DC-3 at DC-5 <ul style="list-style-type: none"> — at 110 V per NC contact Rated value — at 110 V per NO contact Rated value — at 24 V per NC contact Rated value — at 24 V per NO contact Rated value 	20 A 12 A 1.6 A 0.8 A 0.175 A 0.35 A 20 A 20 A
Operating power	
<ul style="list-style-type: none"> • at AC-2 at AC-3 	