

Safety device - PSR-MM30-2NO-2DO-24DC-SC - 2702357

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Two-channel zero-speed and over-speed safety relays up to SIL 3, Cat. 4, PL e, 2 safe relay outputs, suitable for connecting HTL, TTL or sine/cosine encoders as well as proximity switches, plug-in screw terminal block, width: 22.5 mm

Your advantages

- ✓ Monitoring of up to three different speeds as well as downtime
- ✓ Compatible with a range of motion sensors
- ✓ Easy parameterization and online monitoring with the PSRmotion software, which can be downloaded free of charge
- ✓ Force-guided relay contacts, parameterizable signal outputs
- ✓ Up to Cat.4/PL e according to ISO 13849-1, SILCL 3 according to IEC 62061



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 133225
GTIN	4055626133225
Weight per Piece (excluding packing)	196.300 g
Sales Key	DNA242

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	22.5 mm
Height	112.2 mm
Depth	114.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 55 °C (observe derating)
---------------------------------	-------------------------------------

Safety device - PSR-MM30-2NO-2DO-24DC-SC - 2702357

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Max. permissible relative humidity (operation)	75 % (on average, 85% infrequently, non-condensing)
Max. permissible humidity (storage/transport)	75 % (on average, 85% infrequently, non-condensing)
Maximum altitude	≤ 2000 m (Above sea level)

Power supply

Designation	A1/A2
Rated control circuit supply voltage U_s	24 V DC -15 % / +10 % (provide external protection)
Rated control supply current I_s	typ. 74 mA
Power consumption at U_s	typ. 1.78 W
Inrush current	< 18 A ($\Delta t = 500 \mu s$ at U_s)
Filter time	2 ms (at A1 in the event of voltage dips at U_s)
Protective circuit	Serial protection against polarity reversal 33 V suppressor diode

Digital inputs

Input name	Operating mode and monitoring inputs
Description of the input	NPN, IEC 61131-2, type 1
Number of inputs	1 (Non-safety-related start input: S34)
	3 (Safety-related operating mode inputs: I1, I2, I3)
	2 (Safety-related monitoring inputs: MI1, MI2)
Input voltage range "0" signal	0 V DC ... 5 V DC
Input voltage range "1" signal	15 V DC ... 30 V DC
Input current range "0" signal	0 mA ... 1.5 mA
Inrush current	< 5 mA
Current consumption	typ. 4 mA (at U_s)
Filter time	max. 2 ms (Test pulse width; low test pulses for operating mode and monitoring inputs)
	Test pulse rate = 5 x Test pulse width
Max. permissible overall conductor resistance	150 Ω
Discrepancy time	2 s (I1, I2, I3)
	2.5 s (MI1, MI2)
Protective circuit/component	33 V suppressor diode

Measuring inputs

Input name	Proximity switch inputs
Description of the input	NPN, IEC 61131-2, type 1
Number of inputs	2 (Safety-related proximity switch inputs: IN1 IN2)
Precision	± 2 % (in reference to the parameterized limit value)
Inrush current	< 12 mA
Current consumption	typ. 10 mA (at U_s)
Input voltage range "0" signal	0 V DC ... 5 V DC
Input voltage range "1" signal	15 V DC ... 30 V DC