


Pluggable interface relays CR-U

Universal relays

Data sheet

2CDC 233 036 F0004



CR-U

- ① Interface relay
- ② Pluggable function module
- ③ Socket
- ④ Holder

Features

- Standard universal relays with mechanical status indication
- 10 different supply voltages:
DC versions: 12 V, 24 V, 48 V, 110 V, 125 V, 220 V
AC versions: 24 V, 48 V, 60 V, 110 V, 120 V, 230 V
- Output: 2 c/o (SPDT) contacts (10 A) or 3 c/o (SPDT) contacts (10 A)
- Available with or without LED
- Integrated test button for manual operation and locking of output contacts (blue = DC, orange = AC), that can be removed if necessary
- Cadmium-free contact material
- Width on socket: 38 mm
- Pluggable function modules: reverse polarity protection/free wheeling diode, LED indication, RC elements, overvoltage protection, multifunction time module

Approvals

- UL508
- CAN/CSA C22.2 No.14
- CAN/CSA C22.2 No.14
- VDE
- GOST
- Lloyds Register
- CCC
- RMRS

Marks

CE

Order data

Type	Rated control supply voltage U_s	Order code
Interface relays without LED, 2 c/o (SPDT) contacts: 250 V, 10 A		
CR-U012DC2	12 V DC	1SVR 405 621 R4000
CR-U024DC2	24 V DC	1SVR 405 621 R1000
CR-U048DC2	48 V DC	1SVR 405 621 R6000
CR-U110DC2	110 V DC	1SVR 405 621 R8000
CR-U220DC2	220 V DC	1SVR 405 621 R9000
CR-U024AC2	24 V AC	1SVR 405 621 R0000
CR-U048AC2	48 V AC	1SVR 405 621 R5000
CR-U110AC2	110 V AC	1SVR 405 621 R7000
CR-U120AC2	120 V AC	1SVR 405 621 R2000
CR-U230AC2	230 V AC	1SVR 405 621 R3000
Interface relays without LED, 3 c/o (SPDT) contacts: 250 V, 10 A		
CR-U012DC3	12 V DC	1SVR 405 622 R4000
CR-U024DC3	24 V DC	1SVR 405 622 R1000
CR-U048DC3	48 V DC	1SVR 405 622 R6000
CR-U110DC3	110 V DC	1SVR 405 622 R8000
CR-U125DC3	125 V DC	1SVR 405 622 R8200
CR-U220DC3	220 V DC	1SVR 405 622 R9000
CR-U024AC3	24 V AC	1SVR 405 622 R0000
CR-U048AC3	48 V AC	1SVR 405 622 R5000
CR-U060AC3	60 V AC	1SVR 405 622 R5200
CR-U110AC3	110 V AC	1SVR 405 622 R7000
CR-U120AC3	120 V AC	1SVR 405 622 R2000
CR-U230AC3	230 V AC	1SVR 405 622 R3000

Bold printed products = stocked products. Packing unit = 10 pieces.

Pluggable interface relays CR-U

Universal relays

Data sheet

Type	Rated control supply voltage U_s	Order code
Interface relays with LED 2 c/o (SPDT) contacts: 250 V, 10 A		
CR-U012DC2L	12 V DC	1SVR 405 621 R4100
CR-U024DC2L	24 V DC	1SVR 405 621 R1100
CR-U048DC2L	48 V DC	1SVR 405 621 R6100
CR-U110DC2L	110 V DC	1SVR 405 621 R8100
CR-U220DC2L	220 V DC	1SVR 405 621 R9100
CR-U024AC2L	24 V AC	1SVR 405 621 R0100
CR-U048AC2L	48 V AC	1SVR 405 621 R5100
CR-U110AC2L	110 V AC	1SVR 405 621 R7100
CR-U120AC2L	120 V AC	1SVR 405 621 R2100
CR-U230AC2L	230 V AC	1SVR 405 621 R3100
Interface relays with LED 3 c/o (SPDT) contacts: 250 V, 10 A		
CR-U012DC3L	12 V DC	1SVR 405 622 R4100
CR-U024DC3L	24 V DC	1SVR 405 622 R1100
CR-U048DC3L	48 V DC	1SVR 405 622 R6100
CR-U110DC3L	110 V DC	1SVR 405 622 R8100
CR-U220DC3L	220 V DC	1SVR 405 622 R9100
CR-U024AC3L	24 V AC	1SVR 405 622 R0100
CR-U048AC3L	48 V AC	1SVR 405 622 R5100
CR-U110AC3L	110 V AC	1SVR 405 622 R7100
CR-U120AC3L	120 V AC	1SVR 405 622 R2100
CR-U230AC3L	230 V AC	1SVR 405 622 R3100
Interface relays with LED and freewheeling diode 3 c/o (SPDT) contacts: 250 V, 10 A		
CR-U024DC3LD	24 V DC	1SVR 405 623 R1100

Order data - Accessories

Sockets

Type	Version	Order code
Sockets		
CR-U2S	for 2 c/o (SPDT) contacts + module	1SVR 405 670 R0000
CR-U3S	for 3 c/o (SPDT) contacts + module	1SVR 405 660 R0000
CR-U3E	for 3 c/o (SPDT) contacts	1SVR 405 660 R0100
Small sockets		
CR-U2SM	for 2 c/o (SPDT) contacts	1SVR 405 670 R1100
CR-U3SM	for 3 c/o (SPDT) contacts	1SVR 405 660 R1100
Accessories for CR-U sockets		
CR-UH	Metall holder	1SVR 405 669 R0000

Bold printed products = stocked products. Packing unit = 10 pieces.