

About Labfacility

specialize in the field of

Measurement.

Temperature and Process

Formed in 1971, Labfacility



Thermocouple Extension & Compensating Cable PVC Insulated Flat Pair

- PVC insulated flat pair construction
- Conductors laid flat PVC insulated with overall PVC sheath
- All round general purpose cable, both waterproof and very flexible
- Thermocouple extension types for K, J, T & N
- Compensating types VX (KCB) & U (RCA) for types K & R/S Thermocouples respectively
- Stranded conductors available, either 7/0.2mm or 13/0.2mm
- Tolerance Class 2
- Insulation rating -10°C to 105°C
- Colour code (cores & jacket) to IEC-584-3

We are the largest UK	Туре	Conductors	Cores	Jacket	Reel Length	Manufacturers Code	order code
manufacturer of both	кх	7/0.2mm	+Green/-White	Green	10 metres	WK-150-D	7082307
	KX	7/0.2mm	+Green/-White	Green	25 metres	WK-150-D	XF-1323-FAR
temperature sensors and	KX	7/0.2mm	+Green/-White	Green	50 metres	WK-150-D	7082319
thermocouple connectors	KX	7/0.2mm	+Green/-White	Green	100 metres	WK-150-D	8598460
thermocoupie connectors	KX	7/0.2mm	+Green/-White	Green	200 metres	WK-150-D	XF-1303-FAR
		, -	,				
	JX	7/0.2mm	+Black/-White	Black	10 metres	WJ-200-D	7082289
	JX	7/0.2mm	+Black/-White	Black	25 metres	WJ-200-D	XF-1286-FAR
Quality & Service	JX	7/0.2mm	+Black/-White	Black	50 metres	WJ-200-D	7082290
	JX	7/0.2mm	+Black/-White	Black	100 metres	WJ-200-D	8598479
Quality and Service are key	JX	7/0.2mm	+Black/-White	Black	200 metres	WJ-200-D	XF-1264-FAR
elements in the continued growth							
	TX	7/0.2mm	+Brown/-White	Brown	25 metres	WT-200-D	XF-1312-FAR
of Labfacility.	TX	7/0.2mm	+Brown/-White	Brown	50 metres	WT-200-D	7082344
	TX	7/0.2mm	+Brown/-White	Brown	100 metres	WT-200-D	2420292
	TX	7/0.2mm	+Brown/-White	Brown	200 metres	WT-200-D	XF-1284-FAR
Technical support is always freely							
311.6	NX	7/0.2mm	+Pink/-White	Pink	10 metres	WN-100-D	7082320
available from our	NX	7/0.2mm	+Pink/-White	Pink	25 metres	WN-100-D	XF-1285-FAR
experienced technical sales teams	NX	7/0.2mm	+Pink/-White	Pink	50 metres	WN-100-D	XF-1289-FAR
	NX	7/0.2mm	+Pink/-White	Pink	100 metres	WN-100-D	XF-1283-FAR
and the company has ISO9001) () ((CD)	7/0.0	6 / 114 %		40 .	1404 400 5	VE 4004 E40
accreditation.	VX (KCB)	7/0.2mm	+Green/-White	Green	10 metres	WV-100-D	XF-1304-FAR
accieutation.	VX (KCB)	7/0.2mm 7/0.2mm	+Green/-White	Green	25 metres	WV-100-D	7082370
	VX (KCB) VX (KCB)	7/0.2mm 7/0.2mm	+Green/-White +Green/-White	Green	50 metres 100 metres	WV-100-D WV-100-D	XF-1319-FAR 7082381
	VX (KCB)	7/0.2mm	+Green/-White	Green Green	200 metres	WV-100-D WV-100-D	XF-1302-FAR
	VA (NCB)	7/0.2111111	+Green/-winte	Green	200 metres	VV V-100-D	VL-1205-LW
	VX (KCB)	13/0.2mm	+Green/-White	Green	10 metres	WV-101-D	XF-1317-FAR
	VX (KCB)	13/0.2mm	+Green/-White	Green	25 metres	WV-101-D	XF-1313-FAR
	VX (KCB)	13/0.2mm	+Green/-White	Green	50 metres	WV-101-D	XF-1321-FAR
	VX (KCB)	13/0.2mm	+Green/-White	Green	100 metres	WV-101-D	7082400
	(- /	-, -	,				
Contact Details	U (RCA)	7/0.2mm	+Orange/-White	Orange	10 metres	WU-099-D	XF-1297-FAR
	U (RCA)	7/0.2mm	+Orange/-White	Orange	25 metres	WU-099-D	XF-1318-FAR
Email	U (RCA)	7/0.2mm	+Orange/-White	Orange	50 metres	WU-099-D	XF-1320-FAR
sales@labfacility.com	, ,		-	=			
	U (RCA)	13/0.2mm	+Orange/-White	Orange	10 metres	WU-100-D	XF-1322-FAR
Website	U (RCA)	13/0.2mm	+Orange/-White	Orange	25 metres	WU-100-D	XF-1311-FAR
www.labfacility.com	U (RCA)	13/0.2mm	+Orange/-White	Orange	50 metres	WU-100-D	XF-1299-FAR