

**2 CO relay interface modules,  
15.8 mm wide**

**Ideal interface for PLC and electronic systems**

### Type 48.P5

- 2 CO 8 A
- Push-in terminals

### Type 48.52

- 2 CO 8 A
- Screw terminals

- AC coils or DC sensitive coils
- Supply status indication and EMC coil suppression module as standard
- Identification label
- UL Listing (certain relay/socket combinations)
- 35 mm rail (EN 60715) mounting
- Cadmium-free contact material

48.P5

Push-in terminal



48.52

Screw terminal



For outline drawing see page 9

### Contact specification

| Contact configuration                       |           | 2 CO (DPDT) | 2 CO (DPDT) |
|---------------------------------------------|-----------|-------------|-------------|
| Rated current/Maximum peak current          | A         | 8/15        | 8/15        |
| Rated voltage/<br>Maximum switching voltage | V AC      | 250/250     | 250/250     |
| Rated load AC1                              | VA        | 2000        | 2000        |
| Rated load AC15 (230 V AC)                  | VA        | 400         | 400         |
| Single phase motor rating (230 V AC)        | kW        | 0.3         | 0.3         |
| Breaking capacity DC1: 30/110/220 V         | A         | 8/0.3/0.12  | 8/0.3/0.12  |
| Minimum switching load                      | mW (V/mA) | 300 (5/5)   | 300 (5/5)   |
| Standard contact material                   |           | AgNi        | AgNi        |

### Coil specification

|                           |                 |                           |                           |
|---------------------------|-----------------|---------------------------|---------------------------|
| Nominal voltage ( $U_N$ ) | V AC (50/60 Hz) | 12 - 24 - 110 - 120 - 230 | 12 - 24 - 110 - 120 - 230 |
|                           | V DC            | 12 - 24 - 125             | 12 - 24 - 125             |
| Rated power AC/sens. DC   | VA (50 Hz)/W    | 1.2/0.5                   | 1.2/0.5                   |
| Operating range           | AC              | $(0.8 \dots 1.1) U_N$     | $(0.8 \dots 1.1) U_N$     |
|                           | sens. DC        | $(0.73 \dots 1.5) U_N$    | $(0.73 \dots 1.5) U_N$    |
| Holding voltage           | AC/DC           | $0.8 U_N / 0.4 U_N$       | $0.8 U_N / 0.4 U_N$       |
| Must drop-out voltage     | AC/DC           | $0.2 U_N / 0.1 U_N$       | $0.2 U_N / 0.1 U_N$       |


### Technical data

|                                                       |              |                       |                       |
|-------------------------------------------------------|--------------|-----------------------|-----------------------|
| Mechanical life                                       | cycles       | $10 \cdot 10^6$       | $10 \cdot 10^6$       |
| Electrical life at rated load AC1                     | cycles       | $100 \cdot 10^3$      | $100 \cdot 10^3$      |
| Operate/release time                                  | ms           | 7/4 (AC) - 12/12 (DC) | 7/4 (AC) - 12/12 (DC) |
| Insulation between coil and contacts (1.2/50 $\mu$ s) | kV           | 6 (8 mm)              | 6 (8 mm)              |
| Dielectric strength between open contacts             | V AC         | 1000                  | 1000                  |
| Ambient temperature range                             | $^{\circ}$ C | -40...+70             | -40...+70             |
| Protection category                                   |              | IP 20                 | IP 20                 |


**Approvals relay** (according to type)




**NEW 48.P5**




- 2 CO 8 A
- Push-in terminals



**48.52**



- 2 CO 8 A
- Screw terminals



**1 CO relay interface modules,  
15.8 mm wide**
**Ideal interface for PLC and electronic systems**
**Type 48.P6**

- 1 CO 16 A
- Push-in terminals

**Type 48.61**

- 1 CO 16 A
- Screw terminals

- AC coils or DC sensitive coils
- Supply status indication and EMC coil suppression module as standard
- Identification label
- UL Listing (certain relay/socket combinations)
- 35 mm rail (EN 60715) mounting
- Cadmium-free contact material available

48.P6  
Push-in terminal

48.61  
Screw terminal


For outline drawing see page 9

**Contact specification**

|                                             |           | 1 CO (SPDT) | 1 CO (SPDT) |
|---------------------------------------------|-----------|-------------|-------------|
| Contact configuration                       |           | 1 CO (SPDT) | 1 CO (SPDT) |
| Rated current/Maximum peak current          | A         | 16*/30      | 16*/30      |
| Rated voltage/<br>Maximum switching voltage | V AC      | 250/400     | 250/400     |
| Rated load AC1                              | VA        | 4000        | 4000        |
| Rated load AC15 (230 V AC)                  | VA        | 750         | 750         |
| Single phase motor rating (230 V AC)        | kW        | 0.55        | 0.55        |
| Breaking capacity DC1: 30/110/220 V         | A         | 16/0.3/0.12 | 16/0.3/0.12 |
| Minimum switching load                      | mW (V/mA) | 500 (10/5)  | 500 (10/5)  |
| Standard contact material                   |           | AgCdO       | AgCdO       |

**Coil specification**


|                           |                 |                           |                           |
|---------------------------|-----------------|---------------------------|---------------------------|
| Nominal voltage ( $U_N$ ) | V AC (50/60 Hz) | 12 - 24 - 110 - 120 - 230 | 12 - 24 - 110 - 120 - 230 |
|                           | V DC            | 12 - 24 - 125             | 12 - 24 - 125             |
| Rated power AC/sens. DC   | VA (50 Hz)/W    | 1.2/0.5                   | 1.2/0.5                   |
| Operating range           | AC              | $(0.8 \dots 1.1) U_N$     | $(0.8 \dots 1.1) U_N$     |
|                           | sens. DC        | $(0.8 \dots 1.5) U_N$     | $(0.8 \dots 1.5) U_N$     |
| Holding voltage           | AC/DC           | $0.8 U_N / 0.4 U_N$       | $0.8 U_N / 0.4 U_N$       |
| Must drop-out voltage     | AC/DC           | $0.2 U_N / 0.1 U_N$       | $0.2 U_N / 0.1 U_N$       |

**Technical data**

|                                                       |        |                       |                       |
|-------------------------------------------------------|--------|-----------------------|-----------------------|
| Mechanical life                                       | cycles | $10 \cdot 10^6$       | $10 \cdot 10^6$       |
| Electrical life at rated load AC1                     | cycles | $100 \cdot 10^3$      | $100 \cdot 10^3$      |
| Operate/release time                                  | ms     | 7/4 (AC) - 12/12 (DC) | 7/4 (AC) - 12/12 (DC) |
| Insulation between coil and contacts (1.2/50 $\mu$ s) | kV     | 6 (8 mm)              | 6 (8 mm)              |
| Dielectric strength between open contacts             | V AC   | 1000                  | 1000                  |
| Ambient temperature range                             | °C     | -40...+70             | -40...+70             |
| Protection category                                   |        | IP 20                 | IP 20                 |

**Approvals relay** (according to type)



- 1 CO 16 A
- Push-in terminals



\* For currents > 10 A, contact terminals must be connected in parallel (21 with 11, 24 with 14, 22 with 12).



- 1 CO 16 A
- Screw terminals



\* For currents > 10 A, contact terminals must be connected in parallel (21 with 11, 24 with 14, 22 with 12).