


Rexroth IndraControl V The full-featured platform for controlling, operating and monitoring



Rexroth IndraControl V – individual control, operation and monitoring

Rexroth IndraControl V is the HMI platform that gives you the tools you need to control, operate and monitor your machines and systems.

IndraControl V offers scalable performance and functionality, ranging from controller-based devices and compact embedded PCs to powerful industrial PCs. Standardized hardware and software interfaces make it easy to add Indra-Motion control solutions and the IndraLogic PLC system.

The right solution for your application

IndraControl V integrates the functions you need for cost-effective automation: ease of operation, easy-to-understand visualization, integrated control and diagnostics. When you use IndraControl V in conjunction with Rexroth's proven system solutions, you have a complete automation solution for:


- · machine tools
- transfer machines
- printing and converting machines
- food and packaging machines
- forming machines
- woodworking machines
- textile machines
- handling and assembly systems

Scalable to meet your specific needs

The comprehensive product portfolio, consisting of the following items, opens up a world of possibilities:

- controller-based HMIs
- · embedded PC-based HMIs
- PC-based HMIs
- ergonomic machine control panels and industrial grade keyboards
- innovative visualization software

Systems and Solutions



IndraControl V is a scalable control, operation and visualization platform from Rexroth's Automation House. Our unique Automation House has everything you need to implement your automation designs: From drive and control systems right through to the high-performance framework for standardized engineering and user-friendly operation.

This innovation is the result of our many years of applications-related experience and provides you with all the freedom you expect of modern automation technology – well engineered, intelligent and future-proof

Dependable PC technology

Our PCs deliver high reliability. We have versions with special hard disk designs which can withstand vibration up to 1 g and shock up to 15 g to ensure dependable operation in harsh industrial environments. An uninterruptable power supply (UPS) provides maximum data protection – even during power failures.

Tapping into the open PC world

Our embedded and industrial PCs exploit all of the advantages of the open PC world. Open architecture makes it easy to incorporate IndraControl V devices into our proven industry solutions and facilitates integration into your automation architecture.

Ready for the future

Processors continue to develop at a rapid pace. Flexibility has been designed into the IndraControl V to ensure that future innovation can quickly be deployed. We also guarantee long-term availability of the components we use.

IndraControl V – the comprehensive product portfolio for control, operation and visualization in all segments of industry.



Rexroth IndraControl V – the ideal way to control and operate your machines and systems

The broad IndraControl V product portfolio, consisting of controller-based, embedded PC-based and PC-based HMIs always offers you the ideal solution regardless of how simple or complex your application is. Our complete range of compatible accessories, such as machine control panels and visualization software packages, give you all of the freedom you need to design tomorrow's plant automation solutions.

IndraControl VCP and VCH – controller-based terminals

These cost-effective, compact operator terminals are ideal for applications which have low to medium visualization requirements.

Ethernet, Fieldbus or serial ports are used to communicate with the controllers and drives.


Our powerful VI-Composer visualization software simplifies your work during the design phase.

IndraControl VEP and VEH – embedded PC-based terminals

These compact, Windows CE-based terminals offer excellent mid-range performance. In combination with WinStudio visualization software, you can adapt them to your particular machine. When equipped with the IndraLogic PLC system, these terminals become full-fledged autmation controllers.

IndraControl VSP, VPP, VDP, VSB and VPB – PC-based terminals

Our industrial PCs provide highend performance for your applications. Included in this series are complete PC-based HMI solutions with PC and display integrated or rack-mount PCs with detached displays. With a wide range of expansion options and a powerful visualization software, WinStudio, these PC-based terminals are predestined for use in CNC, motion control and PLC applications.



VAK and VAM – additional hardware components


You can choose from a variety of standard and membrane keyboards, machine control panels and uninterruptable power supplies to expand your system and adapt it to your specific machine.

VI-Composer – visualization software

VI-Composer gives you an easy way of visualizing your system data. Pre-designed templates and extensive libraries are provided in the development environment to facilitate the implementation of your particular application. In addition, you can reuse your design work on all IndraControl VCP devices.

WinStudio – visualization software

WinStudio is the powerful visualization software for embedded PC-based and PC-based HMIs. Integration into Rexroth systems speeds up and simplifies your design work. Various WinStudio performance levels enable you to implement your operating philosophy exactly the way you want it on your machine.



Rexroth IndraControl VCP – the controller-based solution

Rexroth's IndraControl VCPs are extremely compact control terminals. They give you maximum hardware flexibility, simple operation and design as well as complete freedom to choose your interfaces.


This package combines powerful hardware and software to create a very cost-effective visualization solution.

You can use the keyed or touch screen version of these controller-based terminals to modify your production data. There are a number of variations to choose from ranging from text-based monochrome displays to full-graphic color touch screens – our portfolio also includes devices for mobile and stationary use.

The huge freedom of choice in interfaces leaves nothing more to be desired, regardless of whether communication is via Ethernet, Fieldbus or serial ports.

VI-Composer development software is designed specifically for these devices. Graphic-based dragand-drop functionality gives you all of the freedom you need to develop your applications.

- cost-effective investment in terms of maintenance and monitoring
- hot plugging increases the flexibility of the handheld device
- simple development of machine or system visualization
- standardized analysis of controller data
- a wide range of functions using VI-Composer visualization software
- supports Asian characters



	1.7		100	147		120	.00
Туре	VCP 02	VCP 05	VCP 08	VCP 11	VCP 20	VCP 25	VCH 08
	W STATE OF S			Description of the control of the co			000 1000 1000 1000 1000 1000 1000 1000
	-12/14/1.	FSTN	1100 m	FSTN touch	FSTN	STN color touch	FSTN
Display			grafic			full-grafic	grafic
6		- 6	5 grey levels	6		125 colors	5 grey levels
Resolution	160 x 80	160 x 80	320 x 240	320 x 240	320 x 240	320 x 240, 1/4 VGA	320 x 240
Keyboard/ Touch screen		membrane keyboa	urd	touch screen	membrane keyboard	touch screen	membrane keyboard
Function keys/ System keys	4/ 7 (2 with LED)	6/ 24 (3 with LED)	15 (12 with LED)/ 22 (3 with LED)	- 44	16 (8 with LED)/	**************************************	18/22
Stop button	27		27	- 4		17,	yes
Accept button		32		<u>-</u> 3			2 pushbuttons, 2-circuit, 3-step
Override potentiometer	-0	IL STATE	· Ollife	_	· Strike	-c	Optional
Hand wheel	79 ₂₂		7500 E	_	7.00°	793°	Optional
RAM	750,		7/0, 3	B MB	0,	7/0,	64 MB
Memory Flash	122			6 MB		240	64 MB
Slots for expansions		9		1	6		9-
Supply Voltage		Though .	3	24 V DC	: How		7/2,
Interfaces	, jic	1 x Ethe	rnet, 2 x USB-Host,	Option: 1 Modul R	RS232/RS485	, Jite	1 x Ethernet, 2 x USB host
Fieldbus	1900		PROFIBUS DE	P-Slave, DeviceNet	Sp.	(9)	-
Approvals	Thu.		CE/I	UL/CSA	*	My.	UL508, UL1740, SIBI
Protection on front	20	~	IP65 (front side)		4,	IP65 (on all sides)
Temperature				5° C – 45°	'C		
(W x H x D in mm)	144 x 96 x 58	120 x 168 x 55	155 x 205 x 55	130 x 96 x 55	300 x 160 x 55	203 x 147 x 66	Ø 250 x 55 + handle 37
Weight	38	100	:00	_	2015	xC	1,1 kg
max. fall height	70807		7020	-	1020	70,000	1,5 m
Cable length	7410.		77/0	- 4	(0)		8 m
Junction box	No.	,,,,,?\	N _{II} ,	10 dd	, a (The state of the s	VAC 30 RJ45, Ethernet, terminal block for stop and accept button
Wall bracket		Sid.	20		15%		VAS 01.1-002

IndraControl VCP and VCH - small controller-based terminals for cost-effective operating and visualization.

Rexroth VI-Composer – easy-to-use development software for simple visualization and parameterization


VI-Composer is a simple yet powerful tool used to develop visualization and parameterization of machine and system data for IndraControl VCP and VCH terminals. The user-friendly development environment with the look-and-feel of Windows applications is a very efficient tool for creating your specific application. You can transfer your programming to other IndraControl VCP and VCH terminals for maximum reusability.

The graphical, WYSIWYG VI-Composer software lets you create text, variables and graphics which will appear exactly the same on your IndraControl VCP and VCH terminals. Rexroth provides predesigned templates and extensive libraries which include a large selection of graphic objects for industrial applications to help you develop your applications quickly and easily.

Using Windows look-and-feel software, you define all of your variables for the particular controller, but you can create templates, graphics and recipes that are not controller specific. Using VI-Composer, you have direct access to the IndraWorks database which contains all variables for a wide range of Rexroth controllers and drives. Extensive auxiliary functions round off the performance spectrum.

Advantages

- application language management with up to 16 languages
- · message and log system
- font editor for creation of userdefined character sets
- simple graphic integration using OLF
- direct access to all controller and drive variables
- project and firmware download for reusable functions
- integrated documentation generation and online help
- predesigned templates as well as line and bar graphs
- · user defined menu structures
- graphic objects: text, variables, graphics, switches, buttons, dropdown fields, tables, etc.




VI-Composer – efficient application programs in a user-friendly development environment

12/4.	- '4 ₁ . '4 ₁ .			
Туре	VI-Composer VI-Composer			
Developer's license for the operationg system	Windows XP/2000/NT			
Firmware	integrated into all VCP and VCH devices			
Variables	65.535			
Connections	download: Ethernet			
Communications	serial, PROFIBUS DP, DeviceNet			
Messages	9.999			
Message buffer	3.000			
Protocol driver	3S seriell, Rexroth BUEP19E, BRC-Symbolism DeviceNet, IndraLogic, PROFIBUS DP			
Supports Asian characters	2.9			
Print protocol	.or.•			
Firmware download	~ ~ ~			
Application upload	7(0)			
Recipe management	"I'II." • "I'II."			
Message and log system	•			
Online help	• 8			
Integrated document generation				
Line and bar graph for variables	- CO.			
Translation support for multilingual projects	, ji ⁰ • , i			
Graphics links using OLE	on graphics terminals			
Developer's license	German/English			

Basic equipment

Technical features

- full-graphics development software
- representation of text, variables and graphics
- drag-and-drop support
- controller-independent definition of variables
- simple graphic integration using OLE
- controller-independent definition of templates, graphics and recipes
- parallel processing of variables, graphics and messages
- integrated document generation and online help
- font editor for creation of user-defined character sets
- automatic application download
- support for multiple controllers in a project



Rexroth IndraControl VEP – the embedded PC solution for stationary applications

IndraControl VEP terminals are an excellent choice for mid-range performance. They offer ease of use, large storage capacity and a number of interfaces. They do not have a hard disk and are designed for maximum reliability. In conjunction with our software packages, they give you a powerful solution for your control and visualization applications.

You can use the touch screen or virtual keyboard to easily operate the embedded PC terminals. The brilliant 8.4" and 12.1" color displays offer the same screen resolution, giving you a choice of display sizes to suit your application. A 15" display is also available. The rugged design of these PC-like terminals is based exclusively on embedded components.

Various interfaces and expansion slots allow you to tailor the Indra-Control VEP terminals to your specific machine and system requirements. An uninterruptable power supply (UPS) protects controller and visualization data for a short period of time. These terminals can be used purely for visualization or the functionality can be enhanced by the addition of our soft PLC solution IndraLogic.

- compact design
- · no hard drive, no rotating media
- controller and visualization in a single unit
- integrated UPS provides protection against power surges and outages
- WinStudio gives you the power to configure, manage and monitor the flow of information in and out of your HMI environment.



Туре	VEP 30	VEP 40	VEP 50	VEP 30
Display	8,4"-TFT	12,1"-TFT	15"-TFT	8,4"-TFT
Resolution	800 x 600, SVGA	800 x 600, SVGA	1024 x 768, XGA	800 x 600, SVGA
Touch screen	9	9 9 9		9
Keyboard -	"H3",	virtual k	eyboard	. No.,
Reyboard	May,	100°,-	Kg,	5 additional keys
Processor	"Z _C .	Celeron	400 MHz	"Z _C ".
RAM	20	128	MB	,8 ²
CompactFlash	The state of the s	128	МВ	May.
Slots	12	2	4	1
Supply voltage		24 \	/ DC	
Interfaces	798	RS232, VGA, PS/2	2, 2 x USB, Ethernet	18.5
Fieldbus	2/2/	fieldbus module (PROFIBU	S DP master) uses one slot	² 10,
UPS	bri	ef UPS protection for saving of	data (512 kB) to CompactFlas	h™
Operating system	5 ³	Windo	ws CE	.1070
Approvals	7/1/2	CE/U	L/CSA	
Protection on front	The state of the s	IP65	3	Front IP64/overall IP40
Temperature		5° C -	45° C	•
Dimensions (1 slot version) (W x H x D in mm)	296 x 200 x 72	350 x 290 x 78	407 x 370 x 82	306 x 241 x 90
Dimensions (2 slots version) (W x H x D in mm)	296 x 200 x 92	350 x 290 x 98	407 x 370 x 103	-difference
Keyboard enhancement option	Natural L	- ⁿ n,	100	VAS 02.1 (start button, stop button, emergency off)

Basic equipment

Rexroth IndraControl VEH 30 – the embedded PC solution for mobile applications

IndraControl VEH 30, Rexroth's universal handheld HMI, is setting new standards for mobile communications, visualization, operation and monitoring. The unit gives you flexible communications from different locations as well as an ergonomic, touch screen design.

The IndraControl VEH 30 lets you operate, setup, parameterize and run diagnostics via Ethernet TCP/IP from any location. We have designed in the capability to handle individual machines, stations or complex production lines. The Hot Plug principle permits disruption-free connection and disconnection during working operations, as well as automatic by-passing of the stop function.

Maximum ease of use and ergonomics were major design goals. The compact, lightweight design reduces fatigue. A three-step accept button, which is integrated into the handle, and redundant-circuit stop button ensure maximum safety. The stop and accept buttons are connected to the safety circuit of the machine via the VAC 30 terminal.

- hot plugging gives you maximum handling flexibility
- safety functions protect humans and machines
- rugged design for industrial use
- excellent ergonomics ensure safe, non-fatigue handling
- 8.4" touch screen for brilliant visualization and ease of operation



147.		147	12/4.
Туре	The state of the s	VEH 30	
Shireting Marks by	onatha di		"Apolitolisiako ta
Display	Th ₂₁ .	8,4"-TFT	744,
Resolution		800 x 600, SVGA	-7/2
Touch screen	8	9 • 9	
Keyboard	16° 2	virtual keyboard	Mo.x
Function keys	34 membrane keys: 2 x 6 jog l	keys, 2 x 8 user definable, 4 navigation	keys, 1 x OK key, 1 x ESC key
Stop button	6, 70,	2 cicuit	76
Accept buttons	1900	2 buttons, 2 circuit, 3 step (optional)	180
Override potentiometer	24,		74/
Handwheel	27,	0	200
Processor		300 MHz, Intel based	
RAM		128 MB	
CompactFlash™	12) 12)	128 MB	The same of the sa
Supply voltage	, of C ,	24 V DC	*0[1]
Operating system	(60)	Windows CE	292
Approvals	710	CE/UL/CSA/BG approval	"Y' _(O)
Protection	21/24	IP65	My,
Temperature		5° C - 45° C	
Dimensions (W x H x D in mm)	9	240 x 250 x 80 + handle 55	6
Weight	740.	1,6 kg	"7/ _{50.3}
Max. drop height	-U.S.	1 m	-40°2,
Cable lenght	Sc. 1720	8 m	NJC.
200	700	70,	70,

Accessories

(A)	- CC		
Terminal	VAC 30		
Santo Legaliko d	portidua il		
Interfaces	RJ45, Ethernet, series terminal blocks for stop and accept buttons		



Basic equipmentOptional

Rexroth IndraControl VSP and VPP – always the right PC technology for the job

The outstanding performance of the latest PC generation enables us to provide all of the functions you need in a single unit. You can use it for visualization or in conjunction with our CNC, MC and PLC for soft control solutions. We offer a wide range of PC products so that you can select exactly the right product to develop your system solutions for standard and high-end applications.

We have two product families which are designed to meet varying requirements for industrial suitability, investment protection, technology and long-term availability:

- standard industrial PCs offer top of the line performance
- high-end industrial PCs for extreme industrial environments

Standard industrial PC IndraControl VSP and VSB

This series is an economical solution designed to meet normal industrial requirements. You always get the latest PC technology and top of the line performance.

High-end industrial PC IndraControl VPP and VPB

This series meets the most demanding shock and vibration requirements for harsh industrial environments. Long-term component availability means that you can support these products for maximum investment protection.

Standard or High-End - a summary of our innovative PC technology

Standard industrial PC	High-end industrial PC
VSP and VSB series	VPP and VPB series
suitable for normal industrial environments • vibration during operation 0.25 g • shock 5 g	suitable for harsh industrial environments • vibration during operation 1 g • shock 15 g • compact design • low heat dissipation
standard investment protection high rate of component innovation	high investment protection high component continuity
latest PC technology current processors, motherboards, etc. lower price segment	long-term availability of components including processors, motherboards, etc
guaranteed serviceability min. 3 years	guaranteed serviceability min. 5 years

Whether you choose standard or high-end, you can count on Rexroth PC solutions.

Rexroth IndraControl VSP, VDP and VPP – a wide range of mounting options

No single design is suitable for all system configurations. The Rexroth industrial PC range offers you three mounting options. You can decide for yourself whether the panel PC, the rack-mount PC with remote display or a complete PC control unit is the best choice for your application.



Panel PC IndraControl VSP and VPP

This standard version combines a control and visualization panel with an industrial PC into one unit. It is ideal for mounting on a machine or in a control cabinet. The high-end IndraControl VPP industrial PC gives you the choice of 3 or 4 expansion slots. With the IndraControl VSP standard industrial PC, you even have six slots available.



Rack-mount PC and Displays IndraControl VSB and VPB with VDP

The industrial PC is safely mounted in the control cabinet, and the display is mounted remotely at the machine. This version is available as a standard or high-end industrial PC. Advantages compared to the panel PC include:

- · display has lower mounting depth
- less heat dissipation allows more compact design
- significant weight reduction on support arm
- simple cabling, because the control unit is mounted in the control cabinet



PC control terminals IndraControl VPP 21

On this version, the industrial PC, control, visualization and housing form a complete control terminal. This compact design offers perfectly matched components and passive heat management.

- compact overall solution
- proven heat management concept
- ready for mounting on a support arm

Rexroth IndraControl VSP – economical PC technology for industrial use

Rexroth IndraControl VSP is a very economical solution for PC-based control, operation and monitoring. These PC-based control terminals offer high-performance while leaving plenty of scope for individual solutions. They are designed for a wide variety of industries and applications that require top of the line PC performance combined with suitability for use in industrial environments under standard ambient conditions.

IndraControl VSP series control terminals contain the PC, control and visualization device in a single, low-cost, compact unit. You can use them to control, operate and monitor single machines, stations or complete production lines to achieve maximum transparency in your production operations. IndraControl VSP is the ideal platform for all PC-based automation tasks.

- compact control, operation and visualization solution
- the use of standardized components keep costs down
- latest PC technology
- the use of standard hardware and software provides good investment protection
- open and flexible for customerspecific solutions

- optimum adaptability to your system:
 - keyed or touch screen versions
 - 12" or 15" TFT color displays
- EMC-certified design enhances the reliability of your production operations
- · user- and service-friendly design
- complete traceability of all changes throughout the entire life cycle



Туре	VSP 16	VSP 16	VSP 40	VSP 40			
Display	12"-	TFT	15	-TFT			
Resolution	800 x 600), SVGA	1024 x	768, XGA			
Touch screen	•	- 2	• 2	- 2			
Machines/functions/extra keys	70°×	16/16/14	-72%	16/16/14			
Alphanumeric keyboard	190	additional o	components VAK	190			
Front USB (IP65 protection)	100	O 10,000 1 1000					
Processor/Main memory	100°	Celeron 2 GHz/512 MB					
Slots (PCI/multi-function)	3	6/0					
Supply voltage	77,	90 - 264 V AC, alternative 24 V DC					
Hard disk > 30 GB			•				
DVD-ROM/DVD-RW	20	28	0	20			
Interfaces	PS/2 n	nouse, PS/2 keyboard, VGA	, LPT, COM, 2 x USB (2.0), 1 x E	thernet			
Status LEDs	Ollio.	voltag	e, hard disk	N.C.			
UPS	-925	e e	external	- 1100			
Operating system	\$	Win	ndows XP	70,			
Approvals	-14 ₁₂	CE	/UL/CSA	Mar.			
Protection on front		~	IP65				
Vibration/Schock	À	0,2	25 g/5 g	A			
Temperature	15.7	5° (C - 45° C	163			
Dimensions (W x H x D in mm)	350 x 290 x 210	350 x 290 x 210	407 x 370 x 210	407 x 370 x 210			

Basic equipmentOptional

Rexroth IndraControl VPP – the PC solution for high-end industrial requirements

Rexroth IndraControl VPP is a rugged, reliable solution for your control, operation and monitoring needs. Suitability for harsh industrial environments, standardized components and long-term availability of the PC control terminals provide the ideal basis for a wide range of industries and applications. They set new standards for PC technology in harsh industrial environments.

IndraControl VPP PC-based control terminals are designed for use in harsh industrial environments. They have an integrated UPS and a shock-mounted hard disk which absorbs shock and vibration. Optimal cooling and temperature monitoring also contribute to excellent system reliability. All components used in the IndraControl VPP control terminals are designed to withstand harsh industrial environments.

Long-term availability of the terminals and software packages gives you maximum investment protection when you design and duplicate your machines. IndraControl VPP is the ideal platform for all CNC, motion control and PLC visualization tasks in your PC-based automation solutions.

- vibration and shock resistance and optimized cooling designed for harsh industrial environments
- long-term availability of software and functionally-compatible versions
- standardized components deliver excellent overall performance
- complete traceability of all changes throughout the entire life cycle of the product



Туре	VPP 16	VPP 16	VPP 40	VPP 40			
Display	12"-	TFT	15	"-TFT			
Resolution	800 x 60	0, SVGA	1024 x	768, XGA			
Touch screen	>.●	3	• &	- &			
Machines/funktions/ extra keys	"14 _{6.y} -	16/16/14	19 ₇ 0 ₃₄	16/16/14			
Alphanumeric keyboard	*OLL .	additonal cor	nponents VAK	*OLC			
Front USB (IP65 protection)	2						
Processor/main memory	Celeron M 1,3 GHz/mind. 512 MB						
Slots (PCI/multi-function)	2/1 or 3/1						
Supply voltage		85 - 264 V AC, a	Iternative 24 V DC				
Hard disk	9	> 20 GB, vib	ration damping	9			
DVD-ROM/DVD-RW	They	Mo.	O 7/6	Mr.			
Interfaces	PS/2	mouse, PS/2 keyboard, VGA	, LPT, COM, 2 x USB , 1 x Et	hernet			
UPS	30	integrated electronics, ex	ternal rechargeable battery	"Jio.			
Monitoring software	, 3	voltage, UPS battery vol	tage, temperature and fan	'12 ₀ _			
Status LEDs	Thy.	voltage, hard disk, l	JPS and temperature	N _d ,			
Operating system	12,	Winde	ows XP				
Approvals		CE/U	L/CSA				
Protection on front	IP65						
Vibration/Schock	1 g/15 g						
Temperatur	x0[1]	5° C	- 45° C	70/2			
Dimensions (3 slots) (W x H x D in mm)	350 x 290 x 146	350 x 290 x 146	407 x 370 x 146	407 x 370 x 146			
Dimensions (4 slots) (W x H x D in mm)	350 x 290 x 166	350 x 290 x 166	407 x 370 x 166	407 x 370 x 166			

Basic equipmentOptional

Rexroth IndraControl VSB, VPB and VDP – the ideal PC solution for remote configurations

Do you need to separate the PC and the control unit for your application? If so, we recommend our solution featuring an industrial PC in the control cabinet and a remote display at the machine. Suitability for harsh industrial environments and perfect standardized component matching give you the ideal platform for a wide variety of applications.

IndraControl VSB

This standard rack-mount PC is our economical solution designed for all normal ambient conditions and industrial environments. The latest PC technology along with standardized hardware and software give you all of the advantages of today's highly-flexible PC world. You always keep up with the rapid pace of innovation.

IndraControl VPB

This high-end rack-mount PC has been specially designed for harsh industrial environments. A robust mechanical and electrical design gives you the reliability and durability on the production floor that you expect. We use high-end components to ensure long-term availability and protect your investment.

IndraControl VDP

These ultra-thin, flat panel displays are ideal for applications where there are space constraints.

A single cable to the control cabinet PC supplies power and all digital video, touch, key and mouse signals. 4 USB ports and a PROFIBUS DP slave for the machine function keys provide optimal connectivity.



Туре	VSB 40	VPB 40	VDP 16	VDP 40
Display	The state of the s	- 174	12"-TFT	15"-TFT
Resolution	19	- 47,	800 x 600, SVGA	1024 x 768, XGA
Touch screen		-		•
Machines/functions-/	- 28		200	
extra keys	de	- 33/2	alternative to t	ouch 16/16/14
Alphanumeric keyboard	- Ollie	- "044"	additional cor	nponents VAK
Front-USB (IP65 protection)	S	~3/2°	~9 ₂ ~	1 2000
Processor/main memory	Celeron 2 GHz/ 512 MB	Celeron M 1,3 GHz/ 512 MB	S. Marine	
Slots (PCI/multi function)	6/0	2/1 or 3/1		_
Supply voltage	90 - 264 V AC	85 – 264 V AC	via VP	B/VSB
Alternative supply voltage	16y -	24 V DC	Hay.	- 16. _{12.}
Hard disk > 30 GB, fixed		- 100 -		- 1
Hard disk > 20 GB, vibration and oscillation absorbing mounting	0	90000	B _{UIC}	- ^{'''} iq _{Dalito'} ,
DVD-ROM/DVD-RW	71/10	0	12	
Interfaces	PS/2-mouse, PS/2-ke 2 x USB,	eyboard, VGA, LPT, COM, , 1 x Ethernet		-keyboard 4 x USB, machine keys (optional)
Connection PC-VDP	G4	G1/G3/G4	10° X	G4 (20)
UPS	external	electronics integrated, external rechargeable battery	Ti _{OU} _{OD}	- Molusey
Status LEDs	- 45	voltage, HDD, UPS, temperature	LEDs same	as VPP/VSP
Operating system	Wind	dows XP	-57	7
Approvals	CE/	UL/CSA	CE/U	L/CSA
Protection	9	IP20	front IP65	
Vibration/schock	0,25 g/5 g	1 g/15 g	1 g/	15 g
Temperature	5° C	– 45° C	5° C -	- 45° C
Dimensions (W x H x D in mm)	see below	see below	350 x 290 x 65	407 x 370 x 69
Dimensions, 3 slots		364 x 130 x 214	100 m	- 120
Dimensions, 4 slots	- 24	364 x 150 x 214	2	-14. ·
Dimensions, 6 slots	360 x 260 x 190	- 10,	40	_

Basic equipmentOptional

IndraControl VSP, VPB and VDP professional solutions when you need to separate the industrial PC from the con-trol panel

Rexroth IndraControl VPP 21 – a complete PC control terminal for mounting on a support arm

Rexroth IndraControl VPP 21 integrates the PC, visualization and associated controls in one enclosure. Passive cooling is used to achieve a very compact design. As a result, low size and weight make the device suitable for mounting on machines and system support arms.

Both the keyed and touch screen versions have a brilliant 14" display and are enclosed in an ergonomically-designed case. All ports are integrated including a PROFIBUS DP master for control functions and two Ethernet ports for programming and networking.

There is also an expansion slot for fieldbus cards, etc. Start, stop and emergency stop buttons are mounted on the front. They can be used directly in the controller or wired separately. An internal buffer saves non-volatile data for your control applications.

- complete control, operation and visualization solution
- ready for mounting on a support arm
- optimized cooling design with no internal fan
- · user- and service-friendly design
- software and functional compatibility ensures long-term availability



	- Here	- 10 m
Туре	VPP 21	VPP 21
Display	74,	14,1"-TFT
Resolution	102	4 x 768, XGA
Touch screen	• 6	9 - 9
Machines/functions/extra keys	3 push buttons (start, stop, emergency off) /-/ 6 navigation buttons	3 push buttons (start, stop, emergency off) /12 function buttons/6 navigation buttons, 16 control buttons, 8 special buttons, numeric keypad, cursor buttons with button mouse
Processor/main memory	Pentium II	I 700 MHz/512 MB
Slots (PCI)	344	1 354
Supply voltage		24 V DC
Hard disk > 20GB	9	• 6
External CompactFlash™	"7¢.,	o 16.,
Interfaces	PS/2 mouse, PS/2 keyboard,	VGA, LPT, COM, 1 x USB, 2 x Ethernet
Fieldbus master	PR	POFIBUS DP
UPS		external
Monitor functions	PC Box status LEDs: voltage, h	nard disk, SRAM battery and temperature
Operating system	7, W	/indows XP
Approvals	C	CE/UL/CSA
Protection (front/overall)	72.5	IP64/40
Vibration/schock		0,25 g/5 g
Temperature	50	° C - 45° C
Dimensions (W x H x D in mm)	402 x 302 x 140	402 x 468 x 140

Basic equipmentOptional

Rexroth WinStudio – visualization software which enables you to create greater transparency in your production process


WinStudio is an innovative visualization module which is part of the powerful IndraWorks software framework. It combines standardized engineering with ease of use. You can use the WinStudio graphical environment to develop your individual applications. The Windows look-and-feel enables you to work quickly and efficiently. You need only one tool to create different applications for a variety of platforms.

WinStudio together with Rexroth's embedded PCs and PC-based solutions offers excellent functionality and performance. Our flexible licensing model gives you the choice of developers and runtime versions. You only need one developers version to modify your applications as often as you want and use them on various runtime versions.

With this approach, you can make modifications as you need them, and it is a very cost-effective solution. We distribute upgrades to ensure that you benefit from our ongoing development work and are able to add innovative functions to your applications to meet future requirements.

Advantages

- UNICODE character set
- auto screen scaling
- standardized visualization reduces your development and maintenance costs
- user-friendly object selection using the project explorer
- simple graphics generation using extensive libraries
- · dynamic web page generation
- numerous interfaces for connecting drive and control equipment
- develop applications without a knowledge of a higher-level language
- a range of software packages gives you the just the right level of performance you need
- ongoing development protects your investment




WinStudio – simple, effective application design software using a drag-and-drop development environment

Туре	WinStudio lite	WinStudio 1,5 k	WinStudio 4 k	WinStudio 64 k	WinStudio 512 k	WinStudio CE lite	WinStudio CE 1,5 k	WinStudio CE 4 k
System includes 1)	•	- 6	() ()		•) ()
Developer license		Wii	ndows XP/2000	/NT		Thom	_	"Tho
Runtime license		Wii	ndows XP/2000	/NT		Go.,	Windows CE	1000
Variables	500	1.500	4.000	64.000	512.000	500	1.500	4.000
Size arrays	2	56	512	1.024	16.384	2	56	512
Classes	TIN.	32	44.	64	512		32	•
Recipe management	_	- 3		•	1/4	-	E.	•
ODBC			•				_	
Mathematics		73.5	•	736		13.8	•	13.5
Alarm/events	- ,	20,		8g,		90, -		8) ₍₂₎
History	- 50		70%	•	703	_	20%	•
Drivers	.d0	3	5		8 200	1	7000	3
OPC server	'71'.S-		11/10	•	-4°C	_	11/0	•
OPC client	120	3	74 ·		77.74		1144	
TCP/IP server			•				•	
TCP/IP client	-	- 6		• 0		- 6		• 2
DDE server and client	-	The same	(No.,		Mrs.	_	The.
Tags database	200	O.	2.	0	3	C.	• 3	100
Web clients	7/20	-	7/1/0.	1/4/8	-720		-726	
50								

Basic equipmentOptional

1) included in the Rexroth IndraMotion and IndraLogic system solutions or available as an option



Rexroth VAK and VAM – additional hardware for ergonomic operation

You can add the compact VAK industrial keyboards and easy-to-use VAM machine control panels to perfect the specific operation and visualization design of your machine. These optional components are designed specifically for our IndraControl V series. They are designed to give you reliable performance in an industrial environment.

VAK 10 and VAK 40

These compact, drawer-based keyboards with alphanumeric keys and an integrated mouse offer IP65 protection. Opened or closed, they provide increased splash and contamination protection.

VAK 11 and VAK 41

These rugged membrane keyboards contain a full set of keys, configurable keys, a separate numeric keypad and an integrated keyboard mouse. Their high protection rating and low mounting depth make them suitable for a wide range of industrial applications.

VAM 10/11 and VAM 40/41

These control panels are designed for use with standard machine tools and production automation equipment. When we designed them, we thought of everything: buttons and lights with customizable labels, key and override switches, emergency off button, digital I/Os and an optional port for an external handwheel.



Туре	VAK 10/40	VAK 11/41	VAM 10/40	VAM 11/41	
Salte Malika di				- 20 _ 30 _ 30 _ 30 _ 30 _ 30 _ 30 _ 30 _	
Version	drawer-based keyboard (full keyboard)	membrane keyboard (full keyboard)	control panel for standard machines	control panel for automated production	
Keyboard	short-str	oke keys		- 3	
Functions and extra keys	86 keys, alphanumeric block, integrated mouse pointer	106 keys, alphanumeric block, 4 variable keys, keyboard mouse	VIII/O.	- Kalyka,	
Illuminated pushbuttons	. 10		2 x 15 short-stroke keys	3 x 5 short-stroke keys	
Emergency off button	70° - 70° -		2 normally-closed		
Override		7	feed and	d spindle	
Configurable modules	The state of the s	27,	VAM 40	VAM 41	
Key switch	6	- 6		th positive action, lated contacts	
2.5 mm diameter knockouts	The.	- %.,	, \$10°°	7 ea./8 ea.	
Fieldbus	The state of the s	- 100	PROFIBU	S DP slave	
Interfaces	PS/2		7 ea.	/8 ea.	
Supply voltage	5 V DC ((via PS/2)	24 V DC		
Approvals	CE/U		JL/CSA		
Protection on front	IP65		IP54		
Temperature	5° C -		- 45° C		
Dimensions (W x H x D in mm)	350/407 x 88 x 200	350/407 x 140 x 40	350/407 x 169 x 80	350/407 x 210 x 80	
Cable	(P) 1	m (F	Car.	- 4	



Bosch Rexroth AG
Electric Drives and Controls
P.O. Box 13 57
97803 Lohr, Germany
Bgm.-Dr.-Nebel-Str. 2
97816 Lohr, Germany
Phone +49 9352-40-0
Fax +49 9352-40-4885
www.boschrexroth.com



The data specified above only serve to describe the product.
As our products are constantly being further developed, no statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.

72 503 AE/06-11 - A3 - HW R911310804 © Bosch Rexroth AG 2006 Subject to revisions! Printed in Germany