



Sensing Accessories

Mounting Brackets page 350

- Using the right bracket ensures optimum performance from your Banner sensors.
- Stainless steel and reinforced thermoplastic polyester mounts reduce installation time and lower total installed cost.
- Choice includes angled, through-hole brackets and split-clamp models that mount to a flat surface.
- Versatile swivel-mount models mount flat and have an adjustable ball to position the sensor at any angle.
- Custom brackets can be designed for your unique applications.



Quick-Disconnect (QD) Cables page 378

- Allow sensors to be replaced or moved quickly, minimizing downtime.
 - Pico- (M8), Euro- (M12), and Mini-styles are available for dc powered sensors.
 - Micro- and Mini-styles are available for ac powered sensors.
 - Choose straight or right-angle connectors.



Retroreflectors and Tape page 391

- Banner offers a complete line of high-quality acrylic targets, high-temperature targets and adhesive-backed retroreflective tapes (not shown).
- Numerous sizes, shapes and mounting options meet your application requirements.
- New high-reflectivity models dramatically increase sensing ranges, with reflectivity factors up to 3x.
- Maximum temperature ratings range from 50° to 480° C.
- Various mounting options are available.



EZ-LIGHT™ Indicator Lights page 402

- Indicator lights show the status of remote or inaccessible sensors, mimicking the sensor's indicators.
- Four model families are available: the 18 mm barrel-shaped, 18 or 30 mm T-style and the dome-shaped K50L.
- A single light displays multiple colors, eliminating the need for multiple post or stack lights.



Miscellaneous

Apertures and Aperture Kits page 406

Replacement Lens Assemblies 408

Alignment Tools 409

Miscellaneous Accessories 410



Banner Bracket



WORLD-BEAM® Q12	MINI-BEAM® 2	WORLD-BEAM® Q518	MINI-BEAM®	WORLD-BEAM® Q530	SM30/SM130	PicoDot®	OMNI-BEAM™		
T8	V51	Q23	S18	S30	T30	Q40	Q60		
V52	V53	M18	T18	T30	Q40	Q45	D10		
V54	Q25	Q25	Q25	Q25	Q25	Q25	D12		

Page	References	44	47	50	53	56	59	62	66	75	88	92	92	98	103	108	115	119	123	127	131	134	140	153	159	166	172
354	DIN-35-..																										
354	MSMB-3																										
355	SMB1815SF																										
355	SMB18A																										
355	SMB18FA																										
356	SMB18Q																										
356	SMB18SF																										
356	SMB18UR																										
356	SMB3018SC																										
357	SMB30A																										
357	SMB30FA																										
357	SMB30MM																										
357	SMB30Q																										
358	SMB30SC																										
358	SMB30SK																										
358	SMB30SUS																										
358	SMB30UR																										
359	SMB312B																										
359	SMB312PD																										
359	SMB312S																										
359	SMB42T																										
360	SMB46A																										
360	SMB46L																										
360	SMB46S																										
360	SMB46U																										
361	SMB55A																										
361	SMB55F																										
361	SMB55RA																										
361	SMB55S																										
362	SMB8MM																										
362	SMBAMS18P																										
362	SMBAMS18RA																										
362	SMBAMS30P																										
363	SMBAMS30RA																										
363	SMBAMSBRA																										
363	SMBAMSLT3IP																										
363	SMBAMSLT3P																										
364	SMBAMSQ60IP																										
364	SMBAMSQ60P																										
365	SMBLG																										
366	SMBLGA																										
366	SMBLT31																										
366	SMBLT32																										