Mounting Position:	Position 1 to 6
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Actuator Type:	Rotary Handle
Contact Position Indication:	ON / OFF
Standards:	IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1

Environmental

Ambient Air Temperature:	Around the Enclosure 0 ... +40 °C Operation -25 ... +50 °C Operation Compensated -25 ... +50 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	Yes
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6:	5g / 10 ... 150 Hz
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Ampere Rating UL/CSA:	2.5 A
Horsepower Rating UL/CSA:	(220 ... 240 V AC) Three Phase 0.5 Hp (440 ... 480 V AC) Three Phase 1 Hp (550 ... 600 V AC) Three Phase 1.5 Hp
Connecting Capacity Main Circuit UL/CSA:	Flexible 1/2x 14-8 AWG Stranded 1/2x 14-8 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in·lb Main Circuit 14 in·lb

Certificates and Declarations (Document Number)

ATEX Certificate:	1SAA918000-3903
BV Certificate:	1SAA918000-0205
CB Certificate:	1SAA918000-2003
CCC Certificate:	1SAA918000-3806

cUL Certificate:	cUL_E137861 cUL_E345003
Declaration of Conformity - CE:	1SAD938514-0003
DNV Certificate:	1SAA918000-0305
Environmental Information:	1SAA918000-2702
GL Certificate:	1SAA918000-0403
GOST Certificate:	1SAA918000-2703
Instructions and Manuals:	2CDC131005M5703
LR Certificate:	1SAA918000-0504
RINA Certificate:	1SAA918000-0803
RMRS Certificate:	1SAA918000-0704
RoHS Information:	1SAA918001-4401
UL Certificate:	UL_E137861 UL_E345003

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	92 mm
Package Level 1 Depth / Length:	58 mm
Package Level 1 Height:	78 mm
Package Level 1 Gross Weight:	0.37 kg
Package Level 1 EAN:	4013614195037
Package Level 2 Units:	24 piece
Package Level 2 Width:	280 mm
Package Level 2 Depth / Length:	395 mm
Package Level 2 Height:	210 mm
Package Level 2 Gross Weight:	0.61 kg
Package Level 2 EAN:	4013614494451

Classifications

Object Classification Code:	F
ETIM 4:	EC000074 - Motor protective circuit-breaker
ETIM 5:	EC000074 - Motor protective circuit-breaker
ETIM 6:	EC000074 - Motor protection circuit-breaker
ETIM 7:	EC000074 - Motor protection circuit-breaker
eClass:	7.0 27370401
UNSPSC:	39121521