



OBT200.-18GM70-.-V1

Reflection light scanner

OBT200.-18GM70-.-V1

with 4-pin, M12 connector

CE

Sensors in
threaded housings



- ◆ Sensing range up to 200 mm
- ◆ Light/dark ON, programmable
- ◆ Sensitivity adjuster for optimal adaptation to the application
- ◆ Strong metallic housing in cylindrical shape M18 x 1
- ◆ LED indicating for a simple operation start
- ◆ Protection degree IP67
- ◆ For glass fibre optics
- ◆ Sensing range depends on the fibre optics being used

For suitable cable sockets, reflectors and mounting aids refer to chapter "accessories".

Date of issue 10/15/01

Ordering code		OBT200-18GM70-E4-V1	OBT200-18GM70-E5-V1	OBT200L-18GM70-E4-V1	OBT200L-18GM70-E5-V1
Detection range	Depends on the fibre optics being used				
	0 ... 200 mm	◆	◆	◆	◆
Reference target	Standard white 200 mm x 200 mm	◆	◆		
	Standard white 50 mm x 50 mm (in direct detection)			◆	◆
Adjustment range	20 ... 200 mm			◆	◆
	5 ... 200 mm	◆	◆		
Light source	LED	◆	◆	◆	◆
Light type	Infrared, alternating light	◆	◆	◆	◆
Ambient light limit	10000 Lux	◆	◆	◆	◆
Standard conformity	EN 60947-5-2	◆	◆	◆	◆
Approvals	CE	◆	◆	◆	◆
Function display	LED yellow: switching state	◆	◆	◆	◆
Controls	sensitivity adjuster	◆	◆		◆
Operating voltage	10 ... 30 V DC	◆	◆	◆	◆
Ripple	10 %	◆	◆	◆	◆
No-load supply current	≤ 20 mA	◆	◆	◆	◆
Time delay before availability	≤ 50 ms	◆	◆	◆	◆
Signal output	1 switch output npn	◆		◆	
	1 switch output pnp		◆		◆
Switching type	Light/dark ON, programmable	◆	◆	◆	◆
Switching voltage	max. 30 V DC	◆	◆	◆	◆
Switching current	max. 100 mA	◆	◆	◆	◆
Voltage drop	≤ 2.5 V	◆	◆	◆	◆
Switching frequency	≤ 300 Hz	◆	◆	◆	◆
Switch-on delay	1.5 ms	◆	◆	◆	◆
Response time	≤ 1.5 ms	◆	◆	◆	◆
Range hysteresis	≤ 10 %	◆	◆	◆	◆
Ambient temperature	-25 ... +55 °C	◆	◆	◆	◆
Storage temperature	-40 ... +70 °C	◆	◆	◆	◆
Protection degree	IP67	◆	◆	◆	◆
Connection type	Connector M12 x 1, 4-pin	◆	◆	◆	◆
Housing	brass, nickel plated	◆	◆	◆	◆
Light exit	PC	◆	◆		
	PMMA			◆	◆
Mass	15 g	◆	◆		
	45 g			◆	◆

Sensors in threaded housings