

RXM2AB2BD

miniature plug-in relay - Zelio RXM - 2 C/O - 24 V DC - 12 A - with LED



Main

| | |
|---|---------------------|
| Commercial Status | Commercialised |
| Range of product | Zelio Relay |
| Series name | Miniature |
| Product or component type | Plug-in relay |
| Device short name | RXM |
| Contacts type and composition | 2 C/O |
| Contacts operation | Standard |
| Control circuit voltage | 24 V DC |
| [the] conventional enclosed thermal current | 12 A at -40...55 °C |
| Status LED | With |
| Control type | Pushbutton |
| Coil interference suppression | Without |
| Utilisation coefficient | 20 % |
| Sale per indivisible quantity | 10 |

Complementary

| | |
|--|--|
| Shape of pin | Flat |
| [Ui] rated insulation voltage | 300 V conforming to UL 300 V conforming to CSA 250 V conforming to IEC |
| [Uimp] rated impulse withstand voltage | 4 kV 1.2/50 µs IEC 61000-4-5 |
| Contacts material | Silver alloy (Ag/Ni) |
| [Ie] rated operational current | 6 A (AC-1/DC-1) NC conforming to IEC 12 A (AC-1/DC-1) NO conforming to IEC 12 A (AC-1/DC-1) conforming to UL |
| Minimum switching current | 10 mA |
| Maximum switching voltage | 250 V DC 250 V AC conforming to IEC |
| Minimum switching voltage | 17 V |
| Resistive rated load | 12 A at 28 V DC 12 A at 250 V AC |
| Maximum switching capacity | 336 W, DC circuit 3000 VA, AC circuit |
| Minimum switching capacity | 170 mW |
| Operating rate | <= 18000 cycles/hour no-load <= 1200 cycles/hour under load |
| Mechanical durability | 10000000 cycles |
| Electrical durability | 100000 cycles for resistive load |
| Average consumption in W | 1.1 W, DC circuit |
| Drop-out voltage threshold | >= 0.1 U _c DC |
| Operating time | 20 ms between coil energisation and making of the On-delay contact 20 ms between coil de-energisation and making of the Off-delay contact |
| Average resistance | 650 Ohm, DC circuit at 20 °C +/- 10 % |
| Rated operational voltage limits | 19.2...26.4 V DC |
| Protection category | RT I |
| Operating position | Any position |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|--------------------|----------|
| CAD overall width | 21 mm |
| CAD overall height | 27 mm |
| CAD overall depth | 55 mm |
| Product weight | 0.037 kg |

Environment

| | |
|---------------------------------------|---|
| Dielectric strength | 2000 V AC (between poles) 2000 V AC (between coil and contact) 1300 V AC (between contacts) |
| Product certifications | CSA GOST Lloyds UL |
| Standards | EN/IEC 61810-1 UL 508 CSA C22.2 No 14 |
| Ambient air temperature for storage | -40...85 °C |
| Ambient air temperature for operation | -40...55 °C |
| Vibration resistance | 5 gn (f = 10...150 Hz), amplitude +/- 1 mm (on 10 cycles not operating) conforming to EN/IEC 60068-2-27 3 gn (f = 10...150 Hz), amplitude +/- 1 mm (on 10 cycles in operation) conforming to EN/IEC 60068-2-27 |
| IP degree of protection | IP40 conforming to EN/IEC 60529 |
| Shock resistance | 30 gn for 11 ms not operating conforming to EN/IEC 60068-2-27 10 gn for 11 ms in operation conforming to EN/IEC 60068-2-27 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|