


ASDX Series Silicon Pressure Sensors

Low Pressure and Ultra-Low Pressure Digital Output,
 $\pm 2\%$ Total Error Band,
10 Inches H₂O to 100 psi



DESCRIPTION

The ASDX Series is a Silicon Pressure Sensor offering either an I²C or SPI digital interface for reading pressure over the specified full scale pressure span and temperature range.

The ASDX is fully calibrated and temperature compensated for sensor offset, sensitivity, temperature effects and non-linearity using an on-board Application Specific Integrated Circuit (ASIC). Calibrated output values for pressure are updated at approximately 1 kHz.

The standard ASDX is calibrated over the temperature range of 0 °C to 85 °C [32 °F to 185 °F]. The sensor is characterized for operation from a single power supply of either 3.3 Vdc or 5.0 Vdc.

FEATURES

- Output options: I²C- or SPI-compatible 12-bit digital
- Precision ASIC conditioning and temperature compensated over 0 °C to 85 °C [32 °F to 185 °F] temperature range
- Low operating voltage
- Absolute, differential and gage types
- Pressure ranges from 10 inches H₂O to 100 psi
- Standard calibrations in inches H₂O, cm H₂O, psi, mbar, bar, kPa
- Total error band of $\pm 2.0\%$ of full scale span maximum
- RoHS compliant

These sensors are available to measure absolute, differential and gage pressures. The absolute versions have an internal vacuum reference and an output value proportional to absolute pressure. Differential versions allow application of pressure to either side of the sensing diaphragm. Gage versions are referenced to atmospheric pressure and provide an output proportional to pressure variations from atmosphere.

The ASDX Series sensors are intended for use with non-corrosive, non-ionic working fluids such as air and dry gases. They are designed and manufactured according to standards in ISO 9001.

POTENTIAL APPLICATIONS

- Flow calibrators
- Ventilation and air flow monitors
- Gas flow instrumentation
- Sleep apnea monitoring and therapy equipment
- Barometry
- Pneumatic controls
- HVAC

ASDX Series Silicon Pressure Sensors

Table 1. Absolute Maximum Ratings¹

Parameter	Min	Max	Unit
Supply voltage (V_{supply})	-0.3	6.0	Vdc
Voltage to any pin	-0.3	$V_{\text{supply}} + 0.3$	Vdc
Digital clock frequency:			
I ² C	100	400	kHz
SPI	50	800	
ESD susceptibility (human body model)	3	-	kV
Storage temperature	-50 [-58]	125 [257]	°C [°F]
Lead temperature (2 s to 4 s)	-	250 [482]	°C [°F]
External capacitance between V_{supply} and ground ²	100	470	nF

Table 2. Operating Specifications

Parameter	Min.	Typ.	Max.	Unit
Supply voltage: (V_{supply}) ³				Vdc
3.3 Vdc	3.0	3.3 ⁴	3.6	
5.0 Vdc	4.75	5.0 ⁴	5.25	
<i>Sensors are either 3.3 Vdc or 5.0 Vdc per the Order Guide (see Figure 1).</i>				
Supply current	2.0	3.5	5.0	mA
Compensated temperature range ⁵	0 [32]	-	85 [185]	°C [°F]
Operating temperature range ⁶	-20 [-4]	-	105 [221]	°C [°F]
Overpressure ⁷	2X operating pressure range minimum			
Burst pressure ⁸	3X operating pressure range minimum			
Startup time (power up to data ready)	-	2.8	7.3	ms
Response time	-	0.46	-	ms
I ² C or SPI voltage level low	-	-	0.2	V_{supply}
I ² C or SPI voltage level high	0.8	-	-	V_{supply}
Pull-up on SDA and SCL (I ² C output only)	1	-	-	kOhm
Total error band ⁹	-	-	2.0	%FSS ¹⁰
Output resolution	12	-	-	bits

Table 3. Environmental Specifications

Parameter	Characteristic
Humidity	0% to 95% RH non-condensing
Vibration	10 G at 20 Hz to 2000 Hz
Shock	100 G for 11 ms
Life	1 million cycles minimum

Table 4. Wetted Materials¹¹

Parameter	Port 1 (Pressure Port) ¹²	Port 2 (Reference Port) ¹²
Covers	glass-filled PBT	glass-filled PBT
Adhesives	silicone	silicone and epoxy
Electronic components	silicon and glass	silicon, glass, and gold

Notes:

- Absolute maximum ratings are the extreme limits that the device will withstand without damage to the device.
- An external bypass capacitor is **required** across the supply voltage (Pins 6 and 3 – see Figure 4) as close to the sensor supply pin as possible for correct sensor operation.
- Ratiometricity of the sensor (the ability of the output to scale to the input voltage) is achieved within the specified operating voltage for each option. Other custom supply voltages are available, please contact Honeywell Customer Service.
- The sensor is not reverse polarity protected. Incorrect application of excitation voltage or ground to the wrong pin may cause electrical failure.
- The compensated temperature range is the temperature range (or ranges) over which the sensor will produce an output proportional to pressure within the specified performance limits.
- The operating temperature range is the temperature range over which the sensor will produce an output proportional to pressure but may not remain within the specified performance limits.
- Overpressure is the maximum pressure which may safely be applied to the product for it to remain in specification once pressure is returned to the operating pressure range. Exposure to higher pressures may cause permanent damage to the product.
- Burst pressure is the maximum pressure that may be applied to any port of the product without causing escape of pressure media. Product should not be expected to function after exposure to any pressure beyond the burst pressure.
- Total error band is the maximum deviation in output from ideal transfer function over the entire compensated temperature and pressure range. Includes all errors due to offset, full scale span, pressure non-linearity, pressure hysteresis, repeatability, thermal effect on offset, thermal effect on span and thermal hysteresis. Specification units are in percent of full scale span (%FSS).
- Full scale span (FSS) is the algebraic difference between the output signal measured at the maximum (Pmax.) and minimum (Pmin.) limits of the pressure range.
- Consult Honeywell Customer Service for detailed material information.
- For AC pressure port configuration, the “pressure” and “reference” ports are reversed.