

# A9-40-00 230-240V 50Hz / 240-260V 60Hz

## General Information

Extended Product Type:	A9-40-00 230-240V 50Hz / 240-260V 60Hz
Product ID:	1SBL141201R8800
EAN:	3471522032881
Catalog Description:	A9-40-00 230-240V 50Hz / 240-260V 60Hz Contactor
Long Description:	<p>A 9 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design.</p> <ul style="list-style-type: none"><li>- Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks</li><li>- Control circuit: AC operated with laminated magnet circuit</li><li>- Accessories: a wide range of accessories is available.</li></ul>

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

EAN:	3471522032881
Minimum Order Quantity:	1 piece
Country of Origin:	France (FR)
Customs Tariff Number:	85369085

## Dimensions

Product Net Width:	44 mm
Product Net Depth:	74 mm
Product Net Height:	74 mm
Product Net Weight:	0.340 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	78 mm
Package Level 1 Length:	79 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.340 kg

## Environmental

Ambient Air Temperature:	Near Contactor for Operation in Free Air (0.85 - 1.1 U <sub>c</sub> ) -40 ... +55 °C Near Contactor for Operation in Free Air (U <sub>c</sub> ) -40 ... +70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible:	3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Shock Direction: A 20 g<sub>n</sub></sub> Closed, Shock Direction: B1 10 g<sub>n</sub></sub> Open, Shock Direction: B1 5 g<sub>n</sub></sub> Shock Direction: B2 15 g<sub>n</sub></sub> Shock Direction: C1 20 g<sub>n</sub></sub> Shock Direction: C2 20 g<sub>n</sub></sub>
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical

Rated Operational Current AC-1 (I <sub>e</sub> ):	(690V) 40°C 25 A (690V) 55°C 22 A (690V) 70°C 18 A
Number of Main Contacts NO:	4
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Rated Control Circuit Voltage (U <sub>c</sub> ):	50 Hz 230 ... 240 V 60 Hz 240 ... 260 V
Terminal Type:	Screw Terminals

## Certificates and Declarations (Document Number)

BV Certificate:	<a href="#">BV_2634H07559B1</a>
CCC Certificate:	<a href="#">CCC_2002010304016447</a>
CSA Certificate:	<a href="#">CSA_1041746A</a>
Declaration of Conformity - CE:	<a href="#">1SBD250804C1000</a>
DNV Certificate:	<a href="#">DNV_E6481</a>

<b>GL Certificate:</b>	<a href="#">GL_9949797HH</a>
<b>GOST Certificate:</b>	<a href="#">GOST_POCCFRME01B03022</a>
<b>LR Certificate:</b>	<a href="#">LRS_9830011E2</a>
<b>RINA Certificate:</b>	<a href="#">RINA_ELE400503CS1</a>
<b>RMRS Certificate:</b>	<a href="#">RMRS_0507015250</a>
<b>UL Certificate:</b>	<a href="#">UL_071301E39231</a>

---

### **Classifications**

<b>E-nummer:</b>	E3228005
<b>UNSPSC:</b>	39121529

---