


Radial Lead Micro Fuseholder



TR5 Style Fuses



Dimensions : Millimetres

Features :

- Precision turned pins
- Twist free construction
- Low profile
- High retention design prevents fuse walkout during heavy vibrations
- Side and end stackable
- Anti wicking pin design
- High solderability pin design
- 200 operations minimum life

Specifications :

Housing	: Glass filled polyester
Insulation Resistance	: 10^3 M Ω at 100 V
Temperature Range	: -55 to 125°C
Contact	: Beryllium copper, heat treated
Plating	: 2 μ m / 80 μ Inches nickel 5 μ m / 200 μ Inches tin
Current Rating	: 3 A
Contact Resistance	: <4 m Ω
Insertion Force	: <250 g
Withdrawal Force	: >50 g

Part Number Table

Number of Poles	Part Number
2	MCBK/PCS

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.