Ordering Information

Square Sockets

Model / Number of pins	P2RF (front-mounting), page 9			P2R (back-mounting), pages 11 and 12			P7TF (front-mounting), page 12
				Solder terminals	PCB terminals		
5 pins	**P2RF-05** Approx. 27 g 	**P2RF-05-E*** Approx. 38 g 	**P2RF-05-S** Approx. 36 g 	**P2R-05A** Approx. 5 g 	**P2R-05P** Approx. 5 g 	**P2R-057P** Approx. 5.5 g 	**P7TF-05** Approx. 28 g 
8 pins	**P2RF-08** Approx. 33 g 	**P2RF-08-E*** Approx. 38 g 	**P2RF-08-S** Approx. 40 g 	**P2R-08A** Approx. 5 g 	**P2R-08P** Approx. 5 g 	**P2R-087P** Approx. 5.5 g 	---

Note: 1. The structure of □-E models provides finger protection. Round terminals cannot be used. Use forked crimp terminals.
2. To remove the Relay, pull the lever on the Socket with your fingers supporting the lever and the opposite side of the Relay case, and jiggle the Relay.
✻ Use a #1 Phillips screwdriver to tighten the screws on this Socket.

Minimum Order Lot The following models are available at the minimum order lot specified below.

Number of pins / Model	P2RF	P2R		P7TF	Minimum order lot (pcs)
5 pins	P2RF-05	P2R-05A	P2R-05P	P7TF-05	10
8 pins	P2RF-08	P2R-08A	P2R-08P	---	

Model / Number of pins	PYF (front-mounting), page 14	PY (back-mounting), page 15		
		Solder terminals	Wrapping terminals	PCB terminals
8 pins	**PYF08A** Approx. 32 g  **PYF08A-E** *1  **PYF08M** Approx. 26 g  **PYF08S** Approx. 46 g 	**PY08** Approx. 8 g **PY08-Y1** **PY08-Y3**  	**PY08QN** Approx. 12 g **PY08QN2** **PY08QN-Y1** **PY08QN2-Y1**  	**PY08-02** *2 Approx. 7.2 g 
11 pins	**PYF11A** Approx. 43 g 	**PY11** Approx. 9 g **PY11-Y1** 	**PY11QN** **PY11QN2** **PY11QN-Y1** **PY11QN2-Y1**  	**PY11-02** *2 
14 pins	**PYF14A** Approx. 49 g  **PYF14A-E***1  **PYF14T** Approx. 53 g  **PYF14S** Approx. 62 g 	**PY14** Approx. 10 g **PY14-Y1** **PY14-Y3** 	**PY14QN** Approx. 14 g **PY14QN2** **PY14QN-Y1** **PY14QN2-Y1** **PY14QN-Y3** **PY14QN2-Y3** 	**PY14-02** *2

Note: 1. The structure of □-E models provides finger protection. Round terminals cannot be used. Use forked crimp terminals.
2. Refer to Models with Standards Certification for detailed information on the models of Common Sockets that are certified for standards.
✻1. Use a #1 Phillips screwdriver to tighten the screws on this Socket.
✻2. The structure does not resist flux. Manual soldering is recommended for this product.

Model / Number of pins	PTF (front-mounting), page 17		PT (back-mounting), page 18		
			Solder terminals	Wrapping terminals	PCB terminals
8 pins	**PTF08A** Approx. 47 g  **PTF08A-E** *1 		**PT08** Approx. 11 g 	**PT08QN** Approx. 10.4 g 	**PT08-0** *2 Approx. 8 g 
11 pins	**PTF11A** Approx. 61 g 		**PT11** Approx. 13 g 	**PT11QN** 	**PT11-0** *2 Approx. 12.2 g 
14 pins	**PTF14A** Approx. 77 g  **PTF14A-E** *1 		**PT14** Approx. 17 g 	**PT14QN** Approx. 20 g 	**PT14-0** *2 Approx. 16.2 g

Note: The structure of □-E models provides finger protection. Round terminals cannot be used. Use forked crimp terminals.
✻ Use a #1 Phillips screwdriver to tighten the screws on this Socket.
✻ The structure does not resist flux. Manual soldering is recommended for this product.

Minimum Order Lot

The following models are available at the minimum order lot specified below.

Number of pins / Model	PYF	PY	PTF	PT	Minimum order lot (pcs)
8 pins	PYF08A PYF08M	PY08	PTF08A	PT08	10
11 pins	PYF11A	PY11	PTF11A	PT11	
14 pins	PYF14A	PY14	PTF14A	PT14	

Model / Number of pins	P7LF (front-mounting), page 20
6 pins	**P7LF-06** Approx. 60 g 

Model / Number of pins	P7S/P7SA, pages 20 and 21	
	Front-mounting	PCB terminals
10 pins	**P7SA-10F** Approx. 44 g **P7SA-10F-ND** Approx. 44 g 	**P7SA-10P** Approx. 9 g 
14 pins	**P7S-14F-END** Approx. 110 g  **P7SA-14F** Approx. 59 g **P7SA-14F-ND** Approx. 59 g 	**P7S-14P-E** Approx. 25 g  **P7SA-14P** Approx. 10 g 

Note: Refer to *Models with Standards Certification* for detailed information on the models of Common Sockets that are certified for standards.