

Ferrule fuse-links 10x38 gG 400 to 690VAC

Product range

Size 10,3x38 690VAC without indicator

| Catalog number | Reference number | Rated voltage AC (IEC) | Rated current I _n | Rated breaking capacity AC | Power dissipation at I _n | Weight |
|----------------|------------------|------------------------|------------------------------|----------------------------|-------------------------------------|--------|
| FR10GG69V1 | R302787 | 690 V | 1 A | 120 kA | 0.45 W | 9 g |
| FR10GG69V2 | S302788 | 690 V | 2 A | 120 kA | 0.55 W | 9 g |
| FR10GG69V4 | T302789 | 690 V | 4 A | 120 kA | 0.6 W | 9 g |
| FR10GG69V6 | V302790 | 690 V | 6 A | 120 kA | 0.9 W | 9 g |
| FR10GG69V8 | W302791 | 690 V | 8 A | 120 kA | 1 W | 9 g |
| FR10GG69V10 | X302792 | 690 V | 10 A | 120 kA | 1.15 W | 9 g |
| FR10GG69V12 | Y302793 | 690 V | 12 A | 120 kA | 1.4 W | 9 g |
| FR10GG69V16 | Z302794 | 690 V | 16 A | 120 kA | 1.9 W | 9 g |

Ferrule fuse-links 10x38 gG 400 to 690VAC

Time current characteristic curves

Size 10x38 500V gG without striker

