Reflective Object Sensor

OPB608A, OPB608B, OPB608C, OPB608R, OPB608V

Features:

- Phototransistor output
- Unfocused for sensing diffuse surface
- Low cost plastic housing
- Enhanced signal to noise ratio
- Reduced ambient light sensitivity





Description:

OPB608 reflective switches consist of an infrared emitting device (LED or VCSEL) and a NPN silicon phototransistor mounted "sideby-side" on a parallel axis in a black opaque plastic housing. All OPB608's (*except* **OPB608R**) have an emitting device and a phototransistor that are encapsulated in a visible filtering epoxy. The phototransistor responds to radiation from the emitter only when a reflective object passes within its field of view. The phototransistor has enhanced low current roll-off to improve the contrast ratio and immunity to background irradiance. LED versions are designed for near-field applications. The VCSEL version is designed for longer distances.

OPB608A, **OPB608B** and **OPB608C** devices are designed for applications with reflective distances between 0.050" (1.270 mm) and 0.375" (9.525 mm). **OPB608V** is designed for applications with reflective distances between 0.050" (1.270 mm) and 1.200" (30.480 mm). All of these are designed for light patterns not visible to the human eye. By utilizing the night enhancement function of a camera, the near infrared light pattern can be seen. This allows a user to see the pattern shining on the reflective object.

OPB608R is designed for applications with reflective distances between 0.050" (1.270 mm) and 0.300" (7.620 mm). It is designed for light patterns visible to the human eye. The efficiency of this sensor is lower for optical wavelengths in the visible range, thus reducing the distance that can be used.

Reflective distances are dependent upon the drive current for the light emitting device, the wavelength of the light source, and the type of reflective material; therefore, each application should be checked for the ability to meet each requirement.

Custom electrical, wire and cabling and connectors are available. Contact your local representative or OPTEK for more information.

Applications:

- Non-contact reflective object sensor
- Assembly line automation
- Machine automation
- Machine safety
- End of travel sensor
- Door sensor



Ordering Information					
Part Number	LED Peak Wavelength	Sensor	Reflection Distance Inch (mm)	Lead Length	
OPB608A					
OPB608B	890 nm				
OPB608C		Rbe Transistor	See Graph	0.18" (Mip)	
OPB608R	650 nm		UII Fage 4	(11111)	
OPB608V	850 nm				



Additional laser safety information can be found on the Optek website. See application #221.

Classification is not marked on the device due to space limitations. See package outline for centerline of optical radiance. Operating devices beyond maximum rating may cause devices to exceed rated classification

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Optek Technology, Inc. 1645 Wallace Drive, Ste. 130, Carrollton, TX USA 75006 |Ph: +1 972 323 2200 www.ttelectronics.com | sensors@ttelectronics.com

Reflective Object Sensor

OPB608A, OPB608B, OPB608C, OPB608R, OPB608V



Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

Storage Temperature Range	-40° C to +85° C			
Operating Temperature Range OPB608 A, B, C & R OPB608V	-40° C to +85° C 0° C to +70° C			
Lead Soldering Temperature [1/16 inch (1.6mm) from the case for 5 sec. with soldering iron] $^{(1)}$	260° C			
Total Power Dissipation	100 mW			
OPB608A, OPB608B, OPB608C (Infrared-LED — 890 nm)				
Forward DC Current	50 mA			
Peak Forward Current (1 μs pulse width, 300 pps)	3 A			
Reverse DC Voltage	2 V			
OPB608R (Visible Red-LED — 650 nm)				
Forward DC Current	50 mA			
Reverse DC Voltage	5 V			
OPB608V (Infrared-VCSEL — 850 nm)				
Forward DC Current	12 mA			
Reverse DC Voltage	5 V			
Phototransistor				
Collector-Emitter Voltage	30 V			
Emitter Reverse Current	10 mA			
Collector DC Current	25 mA			

Notes:

(1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.

(2) Methanol or isopropanol are recommended as cleaning agents. The plastic housing is soluble in chlorinated hydrocarbons and keytones.





DIMENSIONS ARE IN INCHES AND [MILLIMETERS]. UNLESS OTHERWISE SPECIFIED ALL TOLERANCES ARE ±.005 [±.13]

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Optek Technology, Inc. 1645 Wallace Drive, Ste. 130, Carrollton, TX USA 75006 |Ph: +1 972 323 2200 www.ttelectronics.com | sensors@ttelectronics.com