



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF22140-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	730 @ 0°C	340	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		 JKL COMPONENTS CORPORATION TITLE: MINIATURE COLD CATHODE FLUORESCENT LAMP					
		DRAWN BY: L. WENGSTROM APPVD BY: FD DATE: 10/17/00	SIZE: A					FSCM NO.: 55335	DRAWING NO.: BF22140-24B
REV. NO. A DIM LINE CORRECT. AND 140 +/- 5.0 TO 140 +/- 3.0 RELEASED	DESCRIPTION/ECO NUMBER	APPVD DATE: 6/7/00	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE: NONE	RELEASED DATE: 6/7/00	REVISION DATE: 10/17/00	REV. NO. A	SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JKL Components:](#)

[BF22140-24B](#)