



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		JKL COMPONENTS CORPORATION				
C X Y AND BRIGHTNESS RATINGS CHANGE 11/12/08 B BRIGHTNESS ±10% TO ±20% 6/13/08 A CHANGE + ADDITIONAL DIMENSIONS 3/21/08 RELEASE & CANCEL P-0701-05 2/21/07			DRAWN BY L. WENGSTROM APP'VD BY L.R. DATE 11/12/08		SIZE A	FSCM NO. 55335	DRAWING NO. BF23312-24B	TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP	
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 2/21/07	REVISION DATE 11/12/08	REV. NO. C	SHEET 1 OF 1