



SIMATIC S7-300 STABILIZED POWER SUPPLY PS307  
INPUT: 120/230 V AC OUTPUT: DC 24 V DC/5 A

### Technical specifications

Product	PS 307
Power supply, type	24 V/5 A
<b>Input</b>	
Input	1-phase AC
Supply voltage / 1 / with AC / Rated value	120 V
Supply voltage / 2 / with AC / Rated value	230 V
Supply voltage	
• Note	Automatic range selection
Input voltage / 1 / with AC	85 ... 132 V
Input voltage / 2 / with AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering at lout rated, min.	20 ms
Mains buffering	at Vin = 93/187 V
Rated line frequency	50 / 60 Hz
Rated line range	47 ... 63 Hz
Input current / at rated input voltage 120 V	2.3 A
Input current / at rated input voltage 230 V	1.2 A
Switch-on current limiting (+25 °C), max.	20 A
Duration of inrush current limiting / at 25 °C / maximum	3 ms

I <sup>2</sup> t, max.	1.2 A <sup>2</sup> ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic C
<b>Output</b>	
Output	Controlled, isolated DC voltage
Rated voltage V <sub>out</sub> DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	50 mV
Residual ripple peak-peak, typ.	10 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	20 mV
Product function / Output voltage adjustable	No
Output voltage setting	-
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of V <sub>out</sub> (soft start)
Startup delay, max.	2 s
Voltage rise, typ.	10 ms
Rated current value I <sub>out</sub> rated	5 A
Current range	0 ... 5 A
Active power supplied / typical	120 W
Short-term overload current / on short-circuiting during the start-up / typical	20 A
Duration of overloading capability for excess current / on short-circuiting during the start-up	100 ms
Short-term overload current / at short-circuit during operation / typical	20 A
Duration of overloading capability for excess current / at short-circuit during operation	100 ms
Parallel switching for enhanced performance	Yes
<b>Efficiency</b>	
Efficiency at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	87 %
Power loss at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	18 W
<b>Closed-loop control</b>	
Dynamic mains compensation (V <sub>in</sub> rated ±15 %), max.	0.1 %
Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> ± typ.	1 %
Load step setting time 50 to 100%, typ.	0.3 ms
Load step setting time 100 to 50%, typ.	0.3 ms
<b>Protection and monitoring</b>	
Output overvoltage protection	Additional control loop, shutdown at < 28.8 V, automatic restart

Current limitation	5.5 ... 6.5 A
Property of the output / Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current / RMS value / maximum	7 A
<b>Safety</b>	
Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current / maximum	3.5 mA
Leakage current / typical	0.5 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	ATEX (EX) II 3G Ex nA II T4; cULus (ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	No
Marine approval	In S7-300 system
Degree of protection (EN 60529)	IP20
<b>EMC</b>	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
<b>Operating data</b>	
Ambient temperature / during operation	0 ... 60 °C
• Note	with natural convection
Ambient temperature / during transport	-40 ... +85 °C
Ambient temperature / during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
<b>Mechanics</b>	
Connection technology	screw-type terminals
Connections / Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded
Connections / Output	L+, M: 3 screw terminals each for 0.5 ... 2.5 mm <sup>2</sup>
Connections / Auxiliary	-
Width / of the enclosure	60 mm
Height / of the enclosure	125 mm
Depth / of the enclosure	120 mm
Installation width	60 mm

Mounting height	205 mm
Weight, approx.	0.6 kg
Product property / of the enclosure / housing for side-by-side mounting	Yes
Mounting type / wall mounting	No
Mounting type / Standard rail mounting	No
Mounting type / S7 rail mounting	Yes
Installation	Can be mounted onto S7 rail
Mechanical accessories	Mounting adapter for standard mounting rail (6EP1971-1BA00)
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

**letzte Änderung:**

Dec 19, 2014