

FUSERBLOC

Fuse combination switches

for industrial fuses up to 1250 A

References

BS 88 - External front and side operation - 20 to 160 A

Rating (A) Fuse size Frame size	Number of poles	Reference Switch I - 0 - TEST	Reference Changeover I - 0 - II	External front handle I - 0	TEST External front handle I - 0 - TEST	External right side handle I - 0	Changeover external front handle I - 0 - II	Shaft extensions for handle	Terminal shrouds ⁽³⁾	U type A/C ⁽²⁾	Integrated solid neutral link
CD 20 A A1 0	3 P	3641 3000	3680 3000					320 mm 1401 0532			
	3 P + switched neutral	3641 4000	3680 4000								
	3 P+solid neutral	3641 5000									
CD 32 A A1 0	3 P	3641 3001	3680 3001					IP2x as standard			
	3 P + switched neutral	3641 4001	3680 4001	S1 type	S1 type	S1 type	S1 type				
	3 P + solid neutral	3641 5001		Black IP65 1413 2111 ⁽¹⁾	Black IP65 1413 2115 ⁽¹⁾	Black IP65 1417 2111 ⁽¹⁾	Black IP65 1413 2113 ⁽¹⁾				
32 A A1 11	2 P	3841 2003									
	3 P	3841 3003	3880 3003	Red/Yellow IP65 1414 2111	Red/Yellow IP65 1414 2115	Red/Yellow IP65 1418 2111	Red/Yellow IP65 1414 2113				
	4 P	3841 6003	3880 6003								
63 A A2-A3 12	2 P	3841 2006								1 contact NO 3999 0701	3829 9310
	3 P	3841 3006	3880 3006								
	4 P	3841 6006	3880 6006								
100 A A4 ⁽⁴⁾ 13	2 P	3841 2010						320 mm 1400 1032		1 contact NC 3999 0702	
	3 P	3841 3010	3880 3010								
	4 P	3841 6010	3880 6010								
CD 160 A A3-A4 ⁽⁴⁾ 13 A	2 P	3841 2014							2 P 3998 2016 3 P 3998 3016 4 P 3998 4016		
	3 P	3841 3014	3880 3014	S2 type	S2 type	S2 type	S2 type				
	4 P	3841 6014	3880 6014	Black IP65 1423 2111 ⁽¹⁾	Black IP65 1423 2115 ⁽¹⁾	Black IP65 1427 2111 ⁽¹⁾	Black IP65 1421 2113 ⁽¹⁾				
160 A A4 14	2 P	3841 2015									3829 9320
	3 P	3841 3015	3880 3015	Red/Yellow IP65 1424 2111	Red/Yellow IP65 1424 2115	Red/Yellow IP65 1428 2111	Red/Yellow IP65 1424 2113				
	4 P	3841 6015	3880 6015								
160 A B1-B2 14	2 P	3841 2016									
	3 P	3841 3016	3880 3016								
	4 P	3841 6016	3880 6016								

(1) Standard.

(2) 4 auxiliary contacts as standard without additional contact holder.

(3) Top/bottom.

(4) For fuse size A4: max diameter 31 mm.

BS 88 - External front and side operation - 200 to 1250 A

Rating (A) Fuse size Frame size	Number of poles	Reference Switch I - 0 - TEST	Reference Changeover I - 0 - II	External front handle I - 0	TEST External front handle I - 0 - TEST	External right side handle I - 0	Changeover external front handle I - 0 - II	Shaft extensions for handle	Terminal shrouds ⁽³⁾	U type A/C ⁽²⁾	Integrated solid neutral link
CD 200 A A3-A4 (5) 13 A	2 P	3841 2019							2 P 3998 2016		3829 9320
	3 P	3841 3019	3880 3019					3 P 3998 3016	3 P 3998 4016		
	4 P	3841 6019	3880 6019					4 P 3998 4016			
200 A B1-B2 15	2 P	3841 2021							2 P 3998 2025		3829 9325
	3 P	3841 3021	3880 3021					3 P 3998 3025	3 P 3998 4025		
	4 P	3841 6021	3880 6021	S2 type	S2 type	S2 type	S2 type	4 P 3998 4025			
250 A B1-B2-B3 15	2 P	3841 2024							2 P 3998 2025		3829 9325
	3 P	3841 3024	3880 3024	Black IP65 1423 2111 ⁽¹⁾	Black IP65 1423 2115 ⁽¹⁾	Black IP65 1425 2111 ⁽¹⁾	Black IP65 1422 2113 ⁽¹⁾	320 mm 1400 1032	3 P 3998 3025		
	4 P	3841 6024	3880 6024	Red/Yellow IP65 1424 2111	Red/Yellow IP65 1424 2115	Red/Yellow IP65 1428 2111	Red/Yellow IP65 1424 2113	4 P 3998 4025			
315 A B1-B2-B3 16	2 P	3841 2031								1 contact NO 3999 0701	3829 9339
	3 P	3841 3031	3880 3032 ⁽⁶⁾						2 P 3898 2040		
	4 P	3841 6031	3880 6032 ⁽⁶⁾					3 P 3898 3040	4 P 3898 4040		
400 A B1-B2- B3-B4 16	2 P	3841 2038								1 contact NC 3999 0702	3829 9339
	3 P	3841 3038									
	4 P	3841 6038									
630 A C1-C2 17	2 P	3821 2063									3829 9308
	3 P	3821 3063							2 P 3898 2080		
	4 P	3821 6063		S3 type		S3 type		320 mm 1400 1232	3 P 3898 3080		
800 A C1-C2-C3 17	2 P	3821 2080							4 P 3898 4080		3829 9312
	3 P	3821 3080		Black IP65 1433 3111 ⁽¹⁾		Black IP65 1437 3111 ⁽¹⁾					
	4 P	3821 6080		Red/Yellow IP65 1434 3111		Red/Yellow IP65 1438 3111					
1250 A D1 18	2 P	3821 2120									3829 9312
	3 P	3821 3120							3898 2120		
	4 P	3821 6120		S4 type					3898 3120		
				Black IP65 1443 3111 ⁽¹⁾					3898 4120		

(1) Standard.

(2) 4 auxiliary contacts as standard without additional contact holder.

(3) Top/bottom.

(4) 8 AC as standard without support (the support is for 8 additional auxiliary contacts).

(5) For fuse size A4: max diameter 31 mm.

(6) Terminal shrouds: 3 P - 3998 3025, 4 P - 3998 4025.