Sentry SSR32 24VDC



Products + Low Voltage Products and Systems + Control Products + Electronic Relays and Controls + Safety Relays

Products + Low Voltage Products and Systems + Control Products + Safety Products + Safety Relays

General Information

Extended Product Type: Sentry SSR32 24VDC
Product ID: 2TLA010052R0400
EAN: 7350024483321

Catalog Description: Safety relay Sentry SSR32 24VDC - 24 volt DC - 2 NO + 2 NO (delayed) -

OFF-Delay - 0.5 second

Long Description: SSR32 is a safety relay with relay outputs, 2 NO + 2 delayed NO, and a +2

4 VDC supply voltage.

SSR32 is used with safety devices with contacts, 1 or 2 channels, and saf

ety devices with OSSD outputs.

The reset function, automatic or manual, is set with a switch on the front. The two delayed NO relay outputs have an OFF-delay time of 0,5 second.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85364110

Popular Downloads

Data Sheet, Technical Information: 2TLC010001L0201

Instructions and Manuals: 2TLC010002M0201

Dimension Diagram: 2TLC010001U0201

Wiring Diagram: 2TLC010011T0001

Dimensions

Product Net Depth / Length: 120 mm

Product Net Height: 120 mm

Product Net Width: 22.5 mm

Product Net Weight: 0.207 kg

Technical

Performance Level (PL): Up to e

Supply Voltage: 24 V DC

Certificates and Declarations (Document Number)

cUL Certificate: 2TLC010006D0201

Declaration of Conformity - CE: 2TLC010010D0201

Instructions and Manuals:	2TLC010002M0201
TÜV Certificate:	2TLC010009D0201

Classifications

Object Classification Code:	K
ETIM 4:	EC001449 - Device for monitoring of safety-related circuits
ETIM 5:	EC001449 - Device for monitoring of safety-related circuits
ETIM 6:	EC001449 - Device for monitoring of safety-related circuits
ETIM 7:	EC001449 - Device for monitoring of safety-related circuits
E-nummer:	3860823

