

DATASHEET

IXYS

VUO 55-12 N07

OTHER SYMBOLS:

**RGB ELEKTRONIKA AGACIAK CIACIEK
SPÓŁKA JAWNA**

Jana Długosza 2-6 Street
51-162 Wrocław
Poland

✉ biuro@rgbelektronika.pl

☎ +48 71 325 15 05



www.rgbelektronika.pl



www.rgbautomatyka.pl

YOUR PARTNER IN MAINTENANCE

Repair **this product** with RGB ELEKTRONIKA

[ORDER A DIAGNOSIS »](#)



At our premises in Wrocław, we have a fully equipped servicing facility. Here we perform all the repair works and test each later sold unit. Our trained employees, equipped with a wide variety of tools and having several testing stands at their disposal, are a guarantee of the highest quality service.

Buy **this product** at RGB AUTOMATYKA

[BUY »](#)



Three Phase Rectifier Bridge

$$I_{dAVM} = 58 \text{ A}$$

$$V_{RRM} = 1200-1800 \text{ V}$$

V_{RSM} V	V_{RRM} V	Type
1200	1200	VUO 55-12NO7
1400	1400	VUO 55-14NO7
1600	1600	VUO 55-16NO7
1800	1800	VUO 55-18NO7*

* delivery time on request



Symbol	Test Conditions	Maximum Ratings
I_{dAVM}	$T_C = 85^\circ\text{C}$, module	58 A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $V_R = 0$	$t = 10 \text{ ms}$ (50 Hz), sine 750 A
		$t = 8.3 \text{ ms}$ (60 Hz), sine 820 A
	$T_{VJ} = T_{VJM}$ $V_R = 0$	$t = 10 \text{ ms}$ (50 Hz), sine 670 A
		$t = 8.3 \text{ ms}$ (60 Hz), sine 740 A
I^2t	$T_{VJ} = 45^\circ\text{C}$ $V_R = 0$	$t = 10 \text{ ms}$ (50 Hz), sine 2800 A ² s
		$t = 8.3 \text{ ms}$ (60 Hz), sine 2820 A ² s
	$T_{VJ} = T_{VJM}$ $V_R = 0$	$t = 10 \text{ ms}$ (50 Hz), sine 2250 A ² s
		$t = 8.3 \text{ ms}$ (60 Hz), sine 2300 A ² s
T_{VJ}		-40...+150 °C
T_{VJM}		150 °C
T_{stg}		-40...+150 °C
V_{ISOL}	50/60 Hz, RMS $I_{ISOL} \leq 1 \text{ mA}$	$t = 1 \text{ min}$ 2500 V~
		$t = 1 \text{ s}$ 3000 V~
M_d	Mounting torque (M5)	5 ± 15 % Nm
		44 ± 15 % lb.in.
	Terminal connection torque (M5)	3 ± 15 % Nm
		26 ± 15 % lb.in.
Weight	typ.	260 g

Features

- Package with screw terminals
- Isolation voltage 3000 V~
- Planar passivated chips
- Blocking voltage up to 1800 V
- Low forward voltage drop
- UL registered E 72873


Applications

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling

Dimensions in mm (1 mm = 0.0394")



Data according to IEC 60747 and refer to a single diode unless otherwise stated.
IXYS reserves the right to change limits, test conditions and dimensions.




Fig. 1 Forward current versus voltage drop per diode




Fig. 2 Surge overload current per diode
 I_{FSM} : Crest value. t : duration




Fig. 3 I^2t versus time (1-10 ms) per diode




Fig. 4 Power dissipation versus direct output current and ambient temperature




Fig. 5 Maximum forward current at case temperature




Fig. 6 Transient thermal impedance per diode

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.036	0.013
2	0.149	0.034
3	0.615	1.35
4	1.9	23.0

Constants for Z_{thJK} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.036	0.013
2	0.149	0.034
3	0.615	1.35
4	1.9	23.0
5	0.36	52.0