



SIMATIC DP, INTERFACE IM 153-1,
FOR ET 200M, FOR MAX. 8 S7-300 MODULES

General information	
Vendor identification (VendorID)	801Dh
Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
permissible range (ripple included), lower limit (DC)	20.4 V
permissible range (ripple included), upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	not necessary
Mains buffering	
Mains/voltage failure buffering time	5 ms
Input current	
Current consumption, max.	350 mA ; at 24 V DC
Rated value at 24 V DC	625 mA
Inrush current, typ.	2.5 A
I^2t	0.1 A ² ·s
Output voltage	
Rated value (DC)	5 V
Rated value, 5 V DC	Yes

Output current	
for backplane bus (5 V DC), max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Addressing volume	
Inputs	128 byte
Outputs	128 byte
Hardware configuration	
Number of modules per DP slave interface, max.	8
Interfaces	
Interface physics, RS 485	Yes
Interface physics, FOC	No
PROFIBUS DP	
Node addresses	1 to 125 permitted
automatic detection of transmission rate	Yes
PROFIBUS DP, output current, max.	90 mA
Transmission rate, max.	12 Mbit/s
Transmission procedure	RS 485
SYNC capability	Yes
FREEZE capability	Yes
Direct data exchange (slave-to-slave communication)	Yes ; Sender
PROFIBUS DP	9-pin sub D socket
1. Interface	
DP slave	
GSD file	(for DPV1) SIEM801D.GSD; SI01801D.GSG
automatic baud rate search	Yes
Communication functions	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
Isolation	
Isolation tested with	Isolation voltage 500 V
Degree and class of protection	
IP20	Yes
Ambient conditions	
Operating temperature	
min.	0 °C
max.	60 °C
Air pressure	

Operating altitude above sea level, max.	3000 m
Configuration	
Configuration software	
STEP 7	STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	360 g
Status	Jul 24, 2014