

VIPA 300S+ w skrócie



VIPA 300S+ CPU Standardowe

| Standardowe CPU | 314SE | 314SB DPM | 315SB | 315SN | 315PN ECO | 315PN | 317SE | 317SN | 317PN |
|---------------------------------|---|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Pamięć ładowania [kB] | 1024 | 1024 | 4096 | 4096 | 1024 | 4096 | 8192 | 8192 | 8192 |
| Pamięć robocza [kB] | 256-1024 | 512-1024 | 1024-4096 | 1024-4096 | 512-1024 | 1024-4096 | 4096-8192 | 4096-8192 | 4096-8192 |
| SPEED-BUS | - | - | - | - | - | - | • | • | • |
| Interfejs RJ45 | 1 | 1 | 1 | 2 | 2 | 2 | 1 | 2 | 2 |
| Interfejs RS485 | 1 | 1 | 1 | 2 | 2 | 2 | 1 | 2 | 2 |
| Protokoły szeregowo | MPI, ASCII, STX/ETX, 3964(R), USS Master, ModbusRTU | | | | | | | | |
| Profibus slave | • | • | • | • | • | • | • | • | • |
| Profibus master | • | • | • | • | • | • | • | • | • |
| PROFINET | - | - | - | - | • | • | - | - | • |
| max.liczba dołączalnych modułów | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 |
| narzędzie do programowania | SPEED7 Studio, SIMATIC Manager, TIA Portal | | | | | | | | |

