

PB-DP SUB-D TERM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

General ordering data

Type	PB-DP SUB-D TERM
Order No.	8460860000
Version	Sensor/Actuator plug-in connector
GTIN (EAN)	4032248026364
Qty.	1 pc(s).

PB-DP SUB-D TERM

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 43 g

Temperatures

Humidity Max. 75% at +25°C, non-condensing

Technical specifications for sub-D connector

Data rate	12 Mbit/s	Housing main material	PC UL 94 V-1
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	PROFIBUS DP interface	D-Sub 9-pole
PROFIBUS cable interface	Screw connection	Plug-in connector and pin assignment	In accordance with the PROFIBUS specification
Protection degree	IP40	Temperature range of housing	-25...+80 °C

Classifications

ETIM 3.0	EC000830	ETIM 4.0	EC000830
ETIM 5.0	EC000830	ETIM 6.0	EC001132
UNSPSC	30-21-18-01	eClass 6.2	27-06-91-90
eClass 7.1	27-06-91-90	eClass 8.1	27-06-91-90
eClass 9.0	27-06-91-90	eClass 9.1	27-44-03-90

Approvals

Approvals



ROHS Conform