

Power supply unit - TRIO-PS/3AC/24DC/20 - 2866394

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Primary-switched TRIO POWER power supply for DIN rail mounting, input: 3-phase, output: 24 V DC/20 A

Product Description


TRIO POWER power supplies with standard functionality
TRIO POWER is particularly suited to standard machine production, thanks to 1- and 3-phase versions up to 960 W. The wide-range input and the international approval package enable worldwide use.
The robust metal housing, the high electric strength, and the wide temperature range ensure a high level of power supply reliability.

Why buy this product

- ✔ Use the third negative terminal block as a grounding terminal block and minimize installation costs
- ✔ Maximum operational reliability thanks to high MTBF (mean time between failures) of more than 500,000 hours and high dielectric strength of up to 300 V AC
- ✔ Rugged design with metal housing and wide temperature range from -25 to +70°C
- ✔ Compensation of voltage drops by means of output voltage that can be adjusted on the front



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 046671 |
| GTIN | 4046356046671 |
| Weight per Piece (excluding packing) | 2,000.000 g |
| Custom tariff number | 85044030 |
| Country of origin | China |

Technical data

Dimensions

| | |
|--------|----------|
| Width | 115 mm |
| Height | 130 mm |
| Depth | 152.5 mm |

Ambient conditions

Power supply unit - TRIO-PS/3AC/24DC/20 - 2866394

Technical data

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -25 °C ... 70 °C (> 55° C derating : 2.5%/K) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Max. permissible relative humidity (operation) | ≤ 95 % (at 25 °C, non-condensing) |
| Noise immunity | EN 61000-6-2:2005 |

Input data

| | |
|-------------------------------------|---|
| Nominal input voltage range | 3x 400 V AC ... 500 V AC |
| Input voltage range | 3x 320 V AC ... 575 V AC (Derating < 360 V AC: 1,5 %/V) |
| | 2x 360 V AC ... 575 V AC (for 2-phase operation) |
| AC frequency range | 45 Hz ... 65 Hz |
| Discharge current to PE | < 3.5 mA |
| Current consumption | 3x 1.1 A (400 V AC) |
| | 3x 0.8 A (480 V AC) |
| Inrush surge current | < 15 A |
| Power failure bypass | > 17 ms (3x 400 V AC) |
| Choice of suitable circuit breakers | 6 A ... 16 A (Characteristics B, C, D, K) |
| Power factor (cos phi) | 0.67 |
| Type of protection | Transient surge protection |
| Protective circuit/component | Varistor |

Output data

| | |
|---|---|
| Nominal output voltage | 24 V DC ±1 % |
| Setting range of the output voltage (U _{Set}) | 22.5 V DC ... 29.5 V DC (> 24 V DC, constant capacity restricted) |
| Nominal output current (I _N) | 20 A (U _{OUT} = 24 V DC) |
| Derating | 55 °C ... 70 °C (2.5%/K) |
| Connection in parallel | Yes, for redundancy and increased capacity |
| Connection in series | yes |
| Max. capacitive load | Unlimited |
| Active current limitation | Approx. 25 A |
| Control deviation | < 1 % (change in load, static 10 % ... 90 %) |
| | < 2 % (change in load, dynamic 10 % ... 90 %) |
| | < 0.1 % (change in input voltage ±10 %) |
| Residual ripple | < 10 mV _{PP} |
| Output power | 480 W |
| Typical response time | < 1 s |
| Peak switching voltages nominal load | < 30 mV _{PP} |
| Maximum power dissipation in no-load condition | < 6 W |
| Power loss nominal load max. | < 48 W |

General

| | |
|------------|------|
| Net weight | 2 kg |
|------------|------|