

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output	
18 mm - Embeddable eurofast® Connection 	Bi 5-M18-AD4X-H1141	T4414500		5	2-Wire DC	
	Bi 7-M18-AD4X-H1141	T4414541	<i>Extended Range</i>	7		
	Bi 5-EM18-AN6X-H1141	T4614601		5	3-Wire DC NPN	
	Bi 5-M18-AN6X-H1141	T4614600		5		
	Bi 5U-EM18-AN6X-H1141	M1635350	<i>Uprox</i>	5		
	Bi 5U-M18-AN6X-H1141	M1635150	<i>Uprox</i>	5		
	Bi 7-EM18WD-AN6X-H1141	M4614534	<i>Washdown</i>	7		
	Bi 8-M18-AN6X-H1141	T4615100	<i>Extended Range</i>	8		
	Bi 5U-M18-ASIX-H1140	M1901004	<i>Uprox</i>	5	2-Wire ASI-BUS	
	Bi 5-EM18-AP6X-H1141	T4614501		5	3-Wire DC PNP	
	Bi 5-M18-AP6X-H1141	T4614500		5		
	Bi 5U-EM18-AP6X-H1141	M1635340	<i>Uprox</i>	5		
	Bi 5U-M18-AP6X-H1141	M1635140	<i>Uprox</i>	5		
	Bi 7-EM18WD-AP6X-H1141	M4614531	<i>Washdown</i>	7		
	Bi 7-M18WD-AP6X-H1141	M4614529	<i>Washdown</i>	7		
	Bi 8-M18-AP6X-H1141	T4615000	<i>Ext. Range</i>	8		
	Bi 8-EM18H-AP6X-H1141	T4615094	<i>Ext. Range</i>	8		
	Bi 8-EM18H-AP6X-H1141/S1589	T4615099	<i>weldguard</i>	8		
	Bi 5-EM18-VN4X-H1141	T4614699	<i>Comp. Output</i>	5	4-Wire DC NPN	
	Bi 5-M18-VN4X-H1141	T1571800	<i>Comp. Output</i>	5		
	Bi 8-M18-VN4X-H1141	T4590702	<i>Ext. Range</i>	8	4-Wire DC PNP	
	Bi 5-M18-VP4X-H1141	T1561800	<i>Comp. Output</i>	5		
	Bi 8-M18-VP4X-H1141	T4590701	<i>Ext. Range</i>	8	4-Wire DC PNP	
		Bi 5-M18-Y1X-H1141	M4015200		5	2-Wire NAMUR
	18 mm - Embeddable eurofast Connection, Stainless Steel 	Bi 5-EM18FM-AP6X-H1141	M4614539	<i>Stainless Steel Front Cap</i>	5	3-Wire DC PNP

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-65 VDC	1000	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	Diagram 1
	1000	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	
10-30 VDC	1000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4T-*	2	Diagram 2
	1000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	2	
	2500	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	2	
	2500	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RKV 4T-*	2	
	1000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	2	
18-33 VDC	200	N/A	-30 to +85	IP 68	CPB	PA 12	N/A	YE	RKC 254-*M	7	Diagram 3
	200	N/A	-30 to +85	IP 68	CPB	PA 12	N/A	YE	RKC 254-*M	7	
10-30 VDC	1000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4T-*	3	Diagram 4
	1000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	2500	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	3	
	2500	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	1000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	3	
	1000	≤200	-25 to +85	IP 68, 69K	CPB	PA 12	N/A	YE	RK 4T-*	3	
	500	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	3	
	500	≤200	-25 to +70	IP 67	SS	SF	N/A	YE	RKV 4T-*	3	
10-65 VDC	1000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4.4T-*	4	Diagram 5
	1000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	4	
	500	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4.4T-*	4	
10-65 VDC	1000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	Diagram 6
	500	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4.4T-*	5	
5-30 VDC	1000	Remote	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.21T-*	6	Diagram 7
10-30 VDC	180	≤200	-25 to +80	IP 68, 69K	SS	SS	N/A	YE	RKV 4T-*	3	Diagram 7

Barrels

* Length in meters.

For material descriptions see page M22.