




TECHNICAL DATA SHEET


Digitron Probes

Code	Description and Application	Tip Dimension
K0234D	GENERAL PURPOSE PROBE K type sensor. Strong, fast responding and suitable for a wide range of applications - liquids, semisolids, air and granular penetration. Can be used for general food penetration.	
Connector Type 2 pin mini	Time const.(secs)	Max. Tip Temp.
	0.6	1000°C/1832°F

Code	Description and Application	Tip Dimension
T0234D	GENERAL PURPOSE PENETRATION T type sensor version of K0234	
Connector Type 2 pin mini	Time const.(secs)	Max. Tip Temp.
	0.6	250°C/482°F


Code	Description and Application	Tip Dimension
TO234LS	GENERAL PURPOSE PENETRATION With 'T' type sensor, straight cable, 0.7m long and Lumberg connector and set of coloured thumb tabs (2106T only)	
Connector Type Lumberg	Time const.(secs)	Max. Tip Temp.
	0.6	250°C/482°F


Code	Description and Application	Tip Dimension
TO234LC	GENERAL PURPOSE PENETRATION With 'T' type sensor, curly cable and Lumberg connector – includes colour coded thumb tabs (2106T only)	
Connector Type Lumberg	Time const.(secs)	Max. Tip Temp.
	0.6	250°C/482°F


Code	Description and Application	Tip Dimension
H0234D	GENERAL PURPOSE PROBE Thermistor sensor version of K0234, with a straight cable and dedicated connection to the 2046T.	
Connector Type Plug	Time const.(secs)	Max. Tip Temp.
	1.9	120°C/248°F

TECHNICAL DATA SHEET

Digitron Probes

Code	Description and Application	Tip Dimension
P0234D Connector Type TCM Screw	GENERAL PURPOSE PROBE General Purpose Probe. Pt 100 sensor version of the K0234, ideal for laboratory use	
	Time const.(secs) Max. Tip Temp.	
	2 600°C/1110°F	
	0.5 1000°C/1832°F	

Code	Description and Application	Tip Dimension
DK0455D 2 Pin Mini	SURFACE PROBE	
	Time const.(secs) Max. Tip Temp.	
	0.5 400°C/752°F	

Code	Description and Application	Tip Dimension
H0234LC Connector Type Lumberg	GENERAL PURPOSE PENETRATION Thermistor version of K0234 with Lumberg connector and curly cable. Includes colour coded thumb tabs. (2146T only)	
	Time const.(secs) Max. Tip Temp.	
	1.9 120°C/248°F	