



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>				
TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>			SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF23312-24B</b>				
REV. NO. <b>C</b>	DESCRIPTION/ECO NUMBER <b>X Y AND BRIGHTNESS RATINGS CHANGE</b>	APPVD DATE <b>11/12/08</b>	DRAWN BY <b>L. WENGSTROM</b>	APPVD BY <b>L.R.</b>	DATE <b>11/12/08</b>	RELEASED DATE <b>2/21/07</b>	REVISION DATE <b>11/12/08</b>	REV. NO. <b>C</b>	SHEET <b>1 OF 1</b>
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE <b>NONE</b>		RELEASED DATE <b>2/21/07</b>		REVISION DATE <b>11/12/08</b>		REV. NO. <b>C</b>